


**DRAINAGE REPORT
FOR COMPREHENSIVE PERMIT DEVELOPMENT
AT
AT 250 TURNPIKE ROAD, SOUTHBOROUGH, MA**

Job #245-502 Client #502

APRIL 15, 2024
REVISED NOVEMBER 20, 2024



11/20/2024

INTRODUCTION

The purpose of this Drainage Report is to confirm that, following the construction of 32 townhouse style rental units in a combination of duplex and triplex layouts under a comprehensive permit process, that the peak rate of runoff from this property to the two properties that receive runoff from it, Turnpike Road (Route 9) and Parkerville Road, will not increase in any of the 2, 10, 25 or 100 year return frequency storm events.

The property at 250 Turnpike Road receives runoff from the abutting Eagle Leasing site and from the Sarsen Stone Way subdivision. There are two existing detention basins on site that receive discharge from the existing drainage systems behind the existing building and from the lower parking area. There is also an existing detention basin on the east side of two Sarsen Stone Way lots and a small existing detention basin on the Eagle Leasing site.

In addition to constructing 32 townhouse style units, the Applicant proposes to construct parking spaces, driving aisles, sidewalks and landscaped areas that would all increase the peak rate of flow of runoff from the property if no mitigation was undertaken. The Applicant will construct a total of four in ground detention/infiltration structures to both infiltrate and detain runoff. (Additionally, there will be another installed on lot A for the proposed contractor's yard use building proposed on that site). Through the use of these infiltration/detention structures, the peak rate of flow from the site will be kept at or below the predevelopment rate of flow.

On the right side of the proposed main access drive at station 5+50, a detention/infiltration structure with 46 8'x8'x5'high Retain-it modules will be constructed. In addition, at three locations on site (behind units 9-11, behind unit 24 and behind units 20&21) smaller infiltration structures will be installed to receive roof runoff from nearby units.

Flow from parking areas discharged into both structures will pass through CDS stormwater filtration units to remove TSS before infiltration.


Soils on site are a mix of Woodbridge series soils categorized as hydrologic soil group C soils and Canton series soils categorized as hydrologic soil group B soils.

Calculations were made using the HydroCAD stormwater modeling program. The first table, below, compares the peak predevelopment and postdevelopment rates of flows of stormwater at the design points:

DESIGN POINT	PEAK FLOW RATE (in cfs)			
	2 yr storm	10 yr storm	25 yr storm	100 yr storm
Flow to Turnpike Road				
Reach #4 pre	14.41 pre	34.86 pre	57.74 pre	92.67 pre
Reach #14 post	14.41	34.86	57.74	92.67
Flow to Parkerville Road				
Reach #1 pre	3.71 pre	9.01 pre	12.61 pre	18.40 pre
Reach #11 post	2.49	6.84	9.58	14.72

The next table compares the volume of runoff leaving the site in the pre and postdevelopment conditions at the design points.

DESIGN POINT	VOLUME OF FLOW (in acre-feet)			
	2 yr storm	10 yr storm	25 yr storm	100 yr storm
Flow to Turnpike Road				
Reach #4 pre	2.744 pre	5.781 pre	7.857 pre	11.205 pre
Reach #14 post	2.744	5.781	7.857	11.205
Flow to Parkerville Road				
Reach #1 pre	0.550 pre	1.199 pre	1.664 pre	2.435 pre
Reach #11 post	0.383	0.956	1.414	2.191



2 YEAR STORM

PREDEVELOPMENT

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Printed 11/23/2024

Page 1

Area Listing (all nodes)

Area (acres)	CN	Description (subcatchment-numbers)
2.878	68	1 acre lots, 20% imp, HSG B (7S)
7.286	84	1 acre lots, 20% imp, HSG D (7S)
1.998	70	1/2 acre lots, 25% imp, HSG B (9S)
0.311	85	1/2 acre lots, 25% imp, HSG D (9S)
2.200	61	>75% Grass cover, Good, HSG B (1S, 3S, 4S, 5S, 8S)
0.927	74	>75% Grass cover, Good, HSG C (1S, 4S, 5S, 8S)
0.142	80	>75% Grass cover, Good, HSG D (8S)
2.814	98	Paved parking, HSG B (1S, 4S, 5S, 8S)
2.638	98	Paved parking, HSG C (4S, 5S, 8S)
0.005	98	Paved parking, HSG D (8S)
0.018	98	Roofs, HSG B (3S)
0.143	98	Water Surface, HSG B (2S, 9S)
0.057	98	Water Surface, HSG C (6S)
5.548	55	Woods, Good, HSG B (2S, 3S, 4S, 8S, 9S)
5.715	70	Woods, Good, HSG C (2S, 3S, 4S, 6S, 9S)
32.681	75	TOTAL AREA

Summary for Subcatchment 1S: PREDEV FLOW FROM PARKING AREA

Runoff = 3.14 cfs @ 12.08 hrs, Volume= 0.247 af, Depth> 2.98"
Routed to Pond 1P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
41,985	98	Paved parking, HSG B
280	74	>75% Grass cover, Good, HSG C
1,049	61	>75% Grass cover, Good, HSG B
43,314	97	Weighted Average
1,329		3.07% Pervious Area
41,985		96.93% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
6.0					Direct Entry,

Summary for Subcatchment 2S: PREDEV OVERLAND FLOW TO DETENTION BASIN

Runoff = 0.16 cfs @ 12.20 hrs, Volume= 0.020 af, Depth> 0.54"
Routed to Pond 1P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
2,913	98	Water Surface, HSG B
1,161	70	Woods, Good, HSG C
14,991	55	Woods, Good, HSG B
19,065	62	Weighted Average
16,152		84.72% Pervious Area
2,913		15.28% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
10.5	50	0.0300	0.08		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
0.5	58	0.1600	2.00		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
11.0	108				Total

Summary for Subcatchment 3S: PREDEV OVERLAND FLOW TO PARKERVILLE ROAD

Runoff = 2.02 cfs @ 12.42 hrs, Volume= 0.284 af, Depth> 0.66"
 Routed to Reach 1R : PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description			
144,569	70	Woods, Good, HSG C			
63,690	55	Woods, Good, HSG B			
16,200	61	>75% Grass cover, Good, HSG B			
780	98	Roofs, HSG B			
225,239	65	Weighted Average			
224,459		99.65% Pervious Area			
780		0.35% Impervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
9.9	754	0.0640	1.26		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.9	243	0.0370	4.76	57.07	Channel Flow, 2' WIDE BOTTOM, 10:1 SIDE SLOPES, 1'DEEP Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
24.6	1,047				Total

Summary for Subcatchment 4S: OVERLAND FLOW TO ROUTE 9

Runoff = 3.03 cfs @ 12.28 hrs, Volume= 0.342 af, Depth> 0.90"
 Routed to Reach 4R : ROUTE 9

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description			
54,059	55	Woods, Good, HSG B			
24,068	55	Woods, Good, HSG B			
36,060	70	Woods, Good, HSG C			
33,500	61	>75% Grass cover, Good, HSG B			
1,900	74	>75% Grass cover, Good, HSG C			
42,307	98	Paved parking, HSG B			
2,250	98	Paved parking, HSG B			
4,349	98	Paved parking, HSG C			
198,493	70	Weighted Average			
149,587		75.36% Pervious Area			
48,906		24.64% Impervious Area			

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 2 YEAR Rainfall=3.33"

Printed 11/23/2024

Page 3

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.0400	0.13		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
1.1	242	0.0600	3.67		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
9.1	709	0.0680	1.30		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.9	365	0.0160	3.13	37.53	Channel Flow, Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
18.3	1,366				Total

Summary for Subcatchment 5S: DRAINAGE COLLECTED BY CB'S SW OF SELF STORAGE BUILDING

Runoff = 1.04 cfs @ 12.09 hrs, Volume= 0.075 af, Depth> 1.79"
 Routed to Pond 5P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
6,345	61	>75% Grass cover, Good, HSG B
3,301	74	>75% Grass cover, Good, HSG C
6,254	98	Paved parking, HSG B
5,860	98	Paved parking, HSG C
21,760	84	Weighted Average
9,646		44.33% Pervious Area
12,114		55.67% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 6S: OVERLAND FLOW TO EXISTING DETENTION BASIN

Runoff = 0.93 cfs @ 12.19 hrs, Volume= 0.090 af, Depth> 0.95"
 Routed to Pond 5P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
46,762	70	Woods, Good, HSG C
2,500	98	Water Surface, HSG C
49,262	71	Weighted Average
46,762		94.93% Pervious Area
2,500		5.07% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	50	0.0450	0.09		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
3.8	324	0.0800	1.41		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
12.7	374	Total			

Summary for Subcatchment 7S: RUNOFF COLLECTED BY SARSEN STONE WAY

Runoff = 15.43 cfs @ 12.13 hrs, Volume= 1.214 af, Depth> 1.43"
Routed to Pond 7P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
317,393	84	1 acre lots, 20% imp, HSG D
125,360	68	1 acre lots, 20% imp, HSG B
442,753	79	Weighted Average
354,202		80.00% Pervious Area
88,551		20.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
2.0	214	0.1300	1.80		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.6	175	0.1000	4.74		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
0.5	210	0.1000	6.42		Shallow Concentrated Flow, Paved Kv= 20.3 fps
8.4	649	Total			

Summary for Subcatchment 8S: PREDEV FLOW ON EAGLE LEASING

Runoff = 8.93 cfs @ 12.18 hrs, Volume= 0.788 af, Depth> 1.57"
Routed to Pond 8P : DET BASIN ON EAGLE LEASING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Type III 24-hr 2 YEAR Rainfall=3.33"

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 2 YEAR Rainfall=3.33"

Printed 11/23/2024

Page 5

Area (sf)	CN	Description		
24,658	98	Paved parking, HSG B		
8,220	61	>75% Grass cover, Good, HSG B		
104,681	98	Paved parking, HSG C		
34,894	74	>75% Grass cover, Good, HSG C		
235	98	Paved parking, HSG D		
6,197	80	>75% Grass cover, Good, HSG D		
30,530	61	>75% Grass cover, Good, HSG B		
5,140	98	Paved parking, HSG B		
48,076	55	Woods, Good, HSG B		
262,631	81	Weighted Average		
127,917		48.71% Pervious Area		
134,714		51.29% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)		
		Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16	Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
4.2	413	0.1100	1.66	Shallow Concentrated Flow, Woodland Kv= 5.0 fps
2.9	360	0.0440	2.10	Shallow Concentrated Flow, Nearly Bare & Untilled Kv= 10.0 fps
12.4	823	Total		

Summary for Subcatchment 9S: OVERLAND FLOW TO DET BASIN BEHIND 5 & 7 SARSEN STONE

Runoff = 2.99 cfs @ 12.10 hrs, Volume= 0.247 af, Depth> 0.80"

Routed to Pond 7P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description		
20,407	70	Woods, Good, HSG C		
3,300	98	Water Surface, HSG B		
36,775	55	Woods, Good, HSG B		
13,560	85	1/2 acre lots, 25% imp, HSG D		
87,016	70	1/2 acre lots, 25% imp, HSG B		
161,058	68	Weighted Average		
132,614		82.34% Pervious Area		
28,444		17.66% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)		
		Velocity (ft/sec)	Capacity (cfs)	Description
6.0				Direct Entry,

Summary for Reach 1R: PARKERVILLE ROAD

Inflow Area = 6.603 ac, 15.88% Impervious, Inflow Depth > 1.00" for 2 YEAR event
Inflow = 3.71 cfs @ 12.36 hrs, Volume= 0.550 af
Outflow = 3.71 cfs @ 12.36 hrs, Volume= 0.550 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 4R: ROUTE 9

Inflow Area = 26.078 ac, 27.75% Impervious, Inflow Depth > 1.26" for 2 YEAR event
Inflow = 14.41 cfs @ 12.38 hrs, Volume= 2.744 af
Outflow = 14.41 cfs @ 12.38 hrs, Volume= 2.744 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 7R: FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 1.26" for 2 YEAR event
Inflow = 5.74 cfs @ 12.51 hrs, Volume= 1.456 af
Outflow = 5.74 cfs @ 12.56 hrs, Volume= 1.454 af, Atten= 0%, Lag= 2.9 min

Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 3.96 fps, Min. Travel Time= 1.7 min
Avg. Velocity = 2.18 fps, Avg. Travel Time= 3.0 min

Peak Storage= 575 cf @ 12.53 hrs

Average Depth at Peak Storage= 0.40', Surface Width= 5.21'

Bank-Full Depth= 2.00' Flow Area= 20.0 sf, Capacity= 198.41 cfs

2.00' x 2.00' deep channel, n= 0.040 Earth, cobble bottom, clean sides

Side Slope Z-value= 4.0 '/' Top Width= 18.00'

Length= 397.0' Slope= 0.0642 '/'

Inlet Invert= 349.00', Outlet Invert= 323.50'

‡

Summary for Reach 8R: FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE


Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 1.57" for 2 YEAR event
Inflow = 5.25 cfs @ 12.40 hrs, Volume= 0.788 af
Outflow = 5.24 cfs @ 12.41 hrs, Volume= 0.787 af, Atten= 0%, Lag= 0.7 min

Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 7.09 fps, Min. Travel Time= 0.4 min
Avg. Velocity = 3.30 fps, Avg. Travel Time= 0.8 min

Peak Storage= 116 cf @ 12.40 hrs
Average Depth at Peak Storage= 0.36', Surface Width= 3.14'
Bank-Full Depth= 2.00' Flow Area= 14.0 sf, Capacity= 271.03 cfs

1.00' x 2.00' deep channel, n= 0.025 Earth, clean & winding
Side Slope Z-value= 3.0 '/' Top Width= 13.00'
Length= 157.0' Slope= 0.1025 '/'
Inlet Invert= 342.10', Outlet Invert= 326.00'




Summary for Reach 22R: FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Inflow Area = 21.521 ac, 28.41% Impervious, Inflow Depth > 1.34" for 2 YEAR event
Inflow = 11.90 cfs @ 12.46 hrs, Volume= 2.405 af
Outflow = 11.90 cfs @ 12.50 hrs, Volume= 2.402 af, Atten= 0%, Lag= 2.1 min
Routed to Reach 4R : ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 5.42 fps, Min. Travel Time= 1.2 min
Avg. Velocity = 2.72 fps, Avg. Travel Time= 2.3 min

Peak Storage= 841 cf @ 12.48 hrs
Average Depth at Peak Storage= 0.34', Surface Width= 9.84'
Bank-Full Depth= 2.00' Flow Area= 46.0 sf, Capacity= 707.92 cfs

3.00' x 2.00' deep channel, n= 0.030 Earth, grassed & winding
Side Slope Z-value= 10.0 '/' Top Width= 43.00'
Length= 383.0' Slope= 0.0888 '/'
Inlet Invert= 349.00', Outlet Invert= 315.00'



‡

Summary for Pond 1P: EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Inflow Area = 1.432 ac, 71.98% Impervious, Inflow Depth > 2.24" for 2 YEAR event
 Inflow = 3.23 cfs @ 12.09 hrs, Volume= 0.267 af
 Outflow = 2.00 cfs @ 12.20 hrs, Volume= 0.266 af, Atten= 38%, Lag= 6.8 min
 Primary = 2.00 cfs @ 12.20 hrs, Volume= 0.266 af
 Routed to Reach 1R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 309.29' @ 12.20 hrs Surf.Area= 3,644 sf Storage= 1,431 cf

Plug-Flow detention time= 9.9 min calculated for 0.266 af (100% of inflow)
 Center-of-Mass det. time= 8.8 min (783.9 - 775.0)

Volume	Invert	Avail.Storage	Storage Description
#1	308.50'	20,440 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
308.50	0	0	0
310.00	6,960	5,220	5,220
312.00	8,260	15,220	20,440

Device	Routing	Invert	Outlet Devices
#1	Primary	308.50'	12.0" Round Culvert L= 30.0' Ke= 0.500 Inlet / Outlet Invert= 308.50' / 308.10' S= 0.0133 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	311.50'	20.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)

Primary OutFlow Max=2.00 cfs @ 12.20 hrs HW=309.29' (Free Discharge)

1=Culvert (Inlet Controls 2.00 cfs @ 3.02 fps)
 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 5P: EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Inflow Area = 1.630 ac, 20.58% Impervious, Inflow Depth > 1.21" for 2 YEAR event
 Inflow = 1.75 cfs @ 12.13 hrs, Volume= 0.164 af
 Outflow = 1.02 cfs @ 12.38 hrs, Volume= 0.164 af, Atten= 42%, Lag= 15.3 min
 Primary = 1.02 cfs @ 12.38 hrs, Volume= 0.164 af
 Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 326.08' @ 12.38 hrs Surf.Area= 3,729 sf Storage= 1,230 cf

Plug-Flow detention time= 18.4 min calculated for 0.164 af (99% of inflow)
 Center-of-Mass det. time= 15.5 min (868.1 - 852.6)

Volume	Invert	Avail.Storage	Storage Description
#1	325.50'	12,719 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 2 YEAR Rainfall=3.33"

Printed 11/23/2024

Page 9

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
325.50	0	0	0
326.00	3,700	925	925
328.00	4,400	8,100	9,025
328.75	5,450	3,694	12,719

Device	Routing	Invert	Outlet Devices
#1	Primary	325.50'	12.0" Round Culvert L= 38.0' Ke= 0.500 Inlet / Outlet Invert= 325.50' / 325.25' S= 0.0066 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	328.25'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68 2.72 2.81 2.92 2.97 3.07 3.32

Primary OutFlow Max=1.02 cfs @ 12.38 hrs HW=326.08' (Free Discharge)

1=Culvert (Barrel Controls 1.02 cfs @ 3.10 fps)
 2=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 7P: EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 1.26" for 2 YEAR event

Inflow = 18.37 cfs @ 12.12 hrs, Volume= 1.461 af

Outflow = 5.74 cfs @ 12.51 hrs, Volume= 1.456 af, Atten= 69%, Lag= 23.4 min

Primary = 5.74 cfs @ 12.51 hrs, Volume= 1.456 af

Routed to Reach 7R : FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Peak Elev= 353.80' @ 12.51 hrs Surf.Area= 8,316 sf Storage= 16,011 cf

Plug-Flow detention time= 26.3 min calculated for 1.456 af (100% of inflow)

Center-of-Mass det. time= 24.3 min (875.2 - 850.9)

Volume	Invert	Avail.Storage	Storage Description
#1	351.00'	44,275 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
351.00	0	0	0
352.00	6,070	3,035	3,035
354.00	8,560	14,630	17,665
356.00	18,050	26,610	44,275

Device	Routing	Invert	Outlet Devices
#1	Primary	351.00'	12.0" Round Culvert L= 60.0' Ke= 0.500 Inlet / Outlet Invert= 351.00' / 349.00' S= 0.0333 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	355.00'	20.0' long x 4.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00

2.50 3.00 3.50 4.00 4.50 5.00 5.50
 Coef. (English) 2.38 2.54 2.69 2.68 2.67 2.67 2.65 2.66 2.66
 2.68 2.72 2.73 2.76 2.79 2.88 3.07 3.32

Primary OutFlow Max=5.74 cfs @ 12.51 hrs HW=353.80' (Free Discharge)

1=Culvert (Inlet Controls 5.74 cfs @ 7.31 fps)

2=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 8P: DET BASIN ON EAGLE LEASING

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 1.57" for 2 YEAR event
 Inflow = 8.93 cfs @ 12.18 hrs, Volume= 0.788 af
 Outflow = 5.25 cfs @ 12.40 hrs, Volume= 0.788 af, Atten= 41%, Lag= 13.2 min
 Primary = 5.25 cfs @ 12.40 hrs, Volume= 0.788 af

Routed to Reach 8R : FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 344.92' @ 12.40 hrs Surf.Area= 5,269 sf Storage= 3,684 cf

Plug-Flow detention time= 4.4 min calculated for 0.788 af (100% of inflow)
 Center-of-Mass det. time= 4.2 min (846.2 - 842.0)

Volume	Invert	Avail.Storage	Storage Description
#1	342.50'	46,903 cf	Custom Stage Data (Prismatic) Listed below (Recalc)


Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
342.50	0	0	0
344.00	1,030	773	773
346.00	10,200	11,230	12,003
348.00	24,700	34,900	46,903

Device	Routing	Invert	Outlet Devices
#1	Primary	342.50'	12.0" Round Culvert L= 33.0' Ke= 0.500 Inlet / Outlet Invert= 342.50' / 342.10' S= 0.0121 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	347.00'	12.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 4.5' Crest Height

Primary OutFlow Max=5.25 cfs @ 12.40 hrs HW=344.92' (Free Discharge)

1=Culvert (Inlet Controls 5.25 cfs @ 6.68 fps)

2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)



POSTDEVELOPMENT

POSTDEV for Ch40B at 250 Turnpike Rd Southborough CURRENT

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Printed 11/23/2024

Page 1

Area Listing (all nodes)

Area (acres)	CN	Description (subcatchment-numbers)
2.878	68	1 acre lots, 20% imp, HSG B (17S)
7.286	84	1 acre lots, 20% imp, HSG D (17S)
1.998	70	1/2 acre lots, 25% imp, HSG B (19S)
0.311	85	1/2 acre lots, 25% imp, HSG D (19S)
2.470	61	>75% Grass cover, Good, HSG B (11S, 12S, 13S, 14S, 15S, 18S, 25S)
2.755	74	>75% Grass cover, Good, HSG C (11S, 12S, 13S, 14S, 15S, 18S, 25S, 26S)
0.142	80	>75% Grass cover, Good, HSG D (18S)
3.057	98	Paved parking, HSG B (11S, 14S, 15S, 18S, 25S)
3.656	98	Paved parking, HSG C (15S, 18S, 25S, 26S)
0.005	98	Paved parking, HSG D (18S)
0.044	98	Roofs, HSG B (13S)
0.380	98	Roofs, HSG C (13S, 14S, 27S, 28S, 29S)
0.143	98	Water Surface, HSG B (12S, 19S)
0.057	98	Water Surface, HSG C (16S)
4.318	55	Woods, Good, HSG B (12S, 13S, 14S, 18S, 19S, 25S)
3.180	70	Woods, Good, HSG C (12S, 13S, 14S, 16S, 19S)
32.681	77	TOTAL AREA

Summary for Subcatchment 11S: POSTDEV FLOW FROM PARKING AREA

Runoff = 3.14 cfs @ 12.08 hrs, Volume= 0.247 af, Depth> 2.98"
 Routed to Pond 23P : INFILTRATION BASIN WITH 76 R902s

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
41,985	98	Paved parking, HSG B
280	74	>75% Grass cover, Good, HSG C
1,049	61	>75% Grass cover, Good, HSG B
43,314	97	Weighted Average
1,329		3.07% Pervious Area
41,985		96.93% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
6.0	Direct Entry,				

Summary for Subcatchment 12S: POSTDEV OVERLAND FLOW TO DETENTION BASIN

Runoff = 0.60 cfs @ 12.17 hrs, Volume= 0.053 af, Depth> 1.12"
 Routed to Pond 11P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
2,913	98	Water Surface, HSG B
12,916	70	Woods, Good, HSG C
189	55	Woods, Good, HSG B
7,152	74	>75% Grass cover, Good, HSG C
1,644	61	>75% Grass cover, Good, HSG B
24,814	74	Weighted Average
21,901		88.26% Pervious Area
2,913		11.74% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
10.5	50	0.0300	0.08	Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"	
0.5	58	0.1600	2.00	Shallow Concentrated Flow, Woodland Kv= 5.0 fps	
11.0	108	Total			

Summary for Subcatchment 13S: POSTDEV OVERLAND FLOW TO PARKERVILLE ROAD

Runoff = 1.41 cfs @ 12.40 hrs, Volume= 0.184 af, Depth> 0.80"
 Routed to Reach 11R : PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description			
1,943	55	Woods, Good, HSG B			
1,148	98	Roofs, HSG B			
1,254	61	>75% Grass cover, Good, HSG B			
183	70	Woods, Good, HSG C			
1,148	98	Roofs, HSG C			
5,275	74	>75% Grass cover, Good, HSG C			
22,271	55	Woods, Good, HSG B			
789	98	Roofs, HSG B			
19,728	61	>75% Grass cover, Good, HSG B			
26,543	70	Woods, Good, HSG C			
4,032	98	Roofs, HSG C			
36,320	74	>75% Grass cover, Good, HSG C			
120,634	68	Weighted Average			
113,517		94.10% Pervious Area			
7,117		5.90% Impervious Area			
Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
9.9	754	0.0640	1.26		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.9	243	0.0370	4.76	57.07	Channel Flow, 2' WIDE BOTTOM, 10:1 SIDE SLOPES,1'DEEP Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
24.6	1,047	Total			

Summary for Subcatchment 14S: OVERLAND FLOW TO ROUTE 9

Runoff = 3.03 cfs @ 12.28 hrs, Volume= 0.342 af, Depth> 0.90"
 Routed to Reach 14R : ROUTE 9

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
31,704	70	Woods, Good, HSG C
0	98	Roofs, HSG C
4,306	98	Roofs, HSG C
11,703	74	>75% Grass cover, Good, HSG C
76,405	55	Woods, Good, HSG B
44,135	98	Paved parking, HSG B
30,229	61	>75% Grass cover, Good, HSG B
198,482	70	Weighted Average
150,041		75.59% Pervious Area
48,441		24.41% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.0400	0.13		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
1.1	242	0.0600	3.67		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
9.1	709	0.0680	1.30		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.9	365	0.0160	3.13	37.53	Channel Flow, Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
18.3	1,366				Total

Summary for Subcatchment 15S: DRAINAGE COLLECTED BY CB'S SW OF SELF STORAGE BUILDING

Runoff = 1.04 cfs @ 12.09 hrs, Volume= 0.075 af, Depth> 1.79"
 Routed to Pond 15P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
6,345	61	>75% Grass cover, Good, HSG B
3,301	74	>75% Grass cover, Good, HSG C
6,254	98	Paved parking, HSG B
5,860	98	Paved parking, HSG C
21,760	84	Weighted Average
9,646		44.33% Pervious Area
12,114		55.67% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 16S: OVERLAND FLOW TO EXISTING DETENTION BASIN

Runoff = 0.93 cfs @ 12.19 hrs, Volume= 0.090 af, Depth> 0.95"
 Routed to Pond 15P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
46,762	70	Woods, Good, HSG C
2,500	98	Water Surface, HSG C
49,262	71	Weighted Average
46,762		94.93% Pervious Area
2,500		5.07% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	50	0.0450	0.09		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
3.8	324	0.0800	1.41		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
12.7	374				Total

Summary for Subcatchment 17S: RUNOFF COLLECTED BY SARSEN STONE WAY

Runoff = 15.43 cfs @ 12.13 hrs, Volume= 1.214 af, Depth> 1.43"
 Routed to Pond 17P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
317,393	84	1 acre lots, 20% imp, HSG D
125,360	68	1 acre lots, 20% imp, HSG B
442,753	79	Weighted Average
354,202		80.00% Pervious Area
88,551		20.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
2.0	214	0.1300	1.80		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.6	175	0.1000	4.74		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
0.5	210	0.1000	6.42		Shallow Concentrated Flow, Paved Kv= 20.3 fps
8.4	649				Total

Summary for Subcatchment 18S: POSTDEV FLOW ON EAGLE LEASING

Runoff = 8.93 cfs @ 12.18 hrs, Volume= 0.788 af, Depth> 1.57"
 Routed to Pond 18P : DET BASIN ON EAGLE LEASING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
24,658	98	Paved parking, HSG B
8,220	61	>75% Grass cover, Good, HSG B
104,681	98	Paved parking, HSG C
34,894	74	>75% Grass cover, Good, HSG C
235	98	Paved parking, HSG D
6,197	80	>75% Grass cover, Good, HSG D
30,530	61	>75% Grass cover, Good, HSG B
5,140	98	Paved parking, HSG B
48,076	55	Woods, Good, HSG B
262,631	81	Weighted Average
127,917		48.71% Pervious Area
134,714		51.29% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
4.2	413	0.1100	1.66		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
2.9	360	0.0440	2.10		Shallow Concentrated Flow, Nearly Bare & Untilled Kv= 10.0 fps
12.4	823	Total			

Summary for Subcatchment 19S: OVERLAND FLOW TO DET BASIN BEHIND 5 & 7 SARSEN STONE

Runoff = 2.99 cfs @ 12.10 hrs, Volume= 0.247 af, Depth> 0.80"
 Routed to Pond 17P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
20,407	70	Woods, Good, HSG C
3,300	98	Water Surface, HSG B
36,775	55	Woods, Good, HSG B
13,560	85	1/2 acre lots, 25% imp, HSG D
87,016	70	1/2 acre lots, 25% imp, HSG B
161,058	68	Weighted Average
132,614		82.34% Pervious Area
28,444		17.66% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 25S: AREA CAPTURED IN MAIN DRIVE

Runoff = 3.04 cfs @ 12.22 hrs, Volume= 0.295 af, Depth> 2.02"
 Routed to Pond 24P : INFILTRATION STRUCTURE UNDER PARKING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
37,506	98	Paved parking, HSG C
11,007	98	Paved parking, HSG B
8,588	61	>75% Grass cover, Good, HSG B
16,641	74	>75% Grass cover, Good, HSG C
2,422	55	Woods, Good, HSG B
76,164	87	Weighted Average
27,651		36.30% Pervious Area
48,513		63.70% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
0.5	55	0.1400	1.87		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.0	79	0.0380	1.36		Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps
0.9	167	0.0240	3.14		Shallow Concentrated Flow, Paved Kv= 20.3 fps
16.2	351	Total			

Summary for Subcatchment 26S: DRIVEWAY AND 5 UNITS AT ENTRANCE

Runoff = 0.75 cfs @ 12.20 hrs, Volume= 0.071 af, Depth> 2.37"
 Routed to Reach 26R : FLOW PATH FROM OUTLET TO PARKERVILLE

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
4,449	74	>75% Grass cover, Good, HSG C
11,225	98	Paved parking, HSG C
15,674	91	Weighted Average
4,449		28.38% Pervious Area
11,225		71.62% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
14.3	50	0.0050	0.06		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
0.3	19	0.0050	1.06		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
14.6	69				Total

Summary for Subcatchment 27S: BACK HALF OF ROOFS UNITS 9-11

Runoff = 0.11 cfs @ 12.07 hrs, Volume= 0.009 af, Depth> 3.10"
 Routed to Pond 27P : INFILTRATION STRUCTURE FOR 9-11

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
1,512	98	Roofs, HSG C
1,512		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 28S: BACK HALF OF ROOFS UNITS 22-24

Runoff = 0.11 cfs @ 12.07 hrs, Volume= 0.009 af, Depth> 3.10"
 Routed to Pond 28P : INFILTRATION STRUCTURE FOR 22-24

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
1,512	98	Roofs, HSG C
1,512		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 29S: ROOFS FROM 20,21,26-29

Runoff = 0.31 cfs @ 12.07 hrs, Volume= 0.024 af, Depth> 3.10"
 Routed to Pond 29P : INFILTRATION STRUCTURE FOR 20-21 & 26-29

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 2 YEAR Rainfall=3.33"

Area (sf)	CN	Description
4,032	98	Roofs, HSG C
4,032		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Reach 11R: PARKERVILLE ROAD

Inflow Area = 6.442 ac, 39.83% Impervious, Inflow Depth > 0.71" for 2 YEAR event
Inflow = 2.49 cfs @ 12.35 hrs, Volume= 0.383 af
Outflow = 2.49 cfs @ 12.35 hrs, Volume= 0.383 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 14R: ROUTE 9

Inflow Area = 26.078 ac, 27.71% Impervious, Inflow Depth > 1.26" for 2 YEAR event
Inflow = 14.41 cfs @ 12.38 hrs, Volume= 2.744 af
Outflow = 14.41 cfs @ 12.38 hrs, Volume= 2.744 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 17R: FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 1.26" for 2 YEAR event
Inflow = 5.74 cfs @ 12.51 hrs, Volume= 1.456 af
Outflow = 5.74 cfs @ 12.56 hrs, Volume= 1.454 af, Atten= 0%, Lag= 2.9 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 3.96 fps, Min. Travel Time= 1.7 min
Avg. Velocity = 2.18 fps, Avg. Travel Time= 3.0 min

Peak Storage= 575 cf @ 12.53 hrs
Average Depth at Peak Storage= 0.40', Surface Width= 5.21'
Bank-Full Depth= 2.00' Flow Area= 20.0 sf, Capacity= 198.41 cfs

2.00' x 2.00' deep channel, n= 0.040 Earth, cobble bottom, clean sides
Side Slope Z-value= 4.0 '/' Top Width= 18.00'
Length= 397.0' Slope= 0.0642 '/'
Inlet Invert= 349.00', Outlet Invert= 323.50'


Summary for Reach 18R: FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 1.57" for 2 YEAR event
Inflow = 5.25 cfs @ 12.40 hrs, Volume= 0.788 af
Outflow = 5.24 cfs @ 12.41 hrs, Volume= 0.787 af, Atten= 0%, Lag= 0.7 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 7.09 fps, Min. Travel Time= 0.4 min
Avg. Velocity = 3.30 fps, Avg. Travel Time= 0.8 min

Peak Storage= 116 cf @ 12.40 hrs
Average Depth at Peak Storage= 0.36', Surface Width= 3.14'
Bank-Full Depth= 2.00' Flow Area= 14.0 sf, Capacity= 271.03 cfs

1.00' x 2.00' deep channel, n= 0.025 Earth, clean & winding
Side Slope Z-value= 3.0 '/' Top Width= 13.00'
Length= 157.0' Slope= 0.1025 '/'
Inlet Invert= 342.10', Outlet Invert= 326.00'



Summary for Reach 22R: FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Inflow Area = 21.521 ac, 28.41% Impervious, Inflow Depth > 1.34" for 2 YEAR event
Inflow = 11.90 cfs @ 12.46 hrs, Volume= 2.405 af
Outflow = 11.90 cfs @ 12.50 hrs, Volume= 2.402 af, Atten= 0%, Lag= 2.1 min
Routed to Reach 14R : ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 5.42 fps, Min. Travel Time= 1.2 min
Avg. Velocity = 2.72 fps, Avg. Travel Time= 2.3 min

Peak Storage= 841 cf @ 12.48 hrs
Average Depth at Peak Storage= 0.34', Surface Width= 9.84'
Bank-Full Depth= 2.00' Flow Area= 46.0 sf, Capacity= 707.92 cfs

3.00' x 2.00' deep channel, n= 0.030 Earth, grassed & winding
Side Slope Z-value= 10.0 '/' Top Width= 43.00'
Length= 383.0' Slope= 0.0888 '/'
Inlet Invert= 349.00', Outlet Invert= 315.00'

‡

Summary for Reach 26R: FLOW PATH FROM OUTLET TO PARKERVILLE

Inflow Area = 2.108 ac, 65.05% Impervious, Inflow Depth > 0.83" for 2 YEAR event
Inflow = 0.82 cfs @ 12.53 hrs, Volume= 0.146 af
Outflow = 0.81 cfs @ 12.64 hrs, Volume= 0.145 af, Atten= 1%, Lag= 6.1 min
Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 1.84 fps, Min. Travel Time= 3.3 min
Avg. Velocity = 0.76 fps, Avg. Travel Time= 7.8 min

Peak Storage= 160 cf @ 12.58 hrs
Average Depth at Peak Storage= 0.06', Surface Width= 8.46'
Bank-Full Depth= 1.00' Flow Area= 26.0 sf, Capacity= 232.32 cfs

6.00' x 1.00' deep channel, n= 0.022 Earth, clean & straight
Side Slope Z-value= 20.0 '/' Top Width= 46.00'
Length= 360.0' Slope= 0.0375 '/'
Inlet Invert= 318.00', Outlet Invert= 304.50'

‡

Summary for Pond 11P: EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Inflow Area = 1.564 ac, 65.90% Impervious, Inflow Depth > 0.41" for 2 YEAR event
Inflow = 0.60 cfs @ 12.17 hrs, Volume= 0.053 af
Outflow = 0.44 cfs @ 12.30 hrs, Volume= 0.053 af, Atten= 27%, Lag= 8.0 min
Primary = 0.44 cfs @ 12.30 hrs, Volume= 0.053 af
Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Peak Elev= 308.83' @ 12.30 hrs Surf.Area= 1,526 sf Storage= 251 cf

Plug-Flow detention time= 9.0 min calculated for 0.053 af (100% of inflow)
Center-of-Mass det. time= 7.5 min (870.3 - 862.7)

Volume	Invert	Avail.Storage	Storage Description
#1	308.50'	20,440 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
308.50	0	0	0
310.00	6,960	5,220	5,220
312.00	8,260	15,220	20,440

Device	Routing	Invert	Outlet Devices
#1	Primary	308.50'	12.0" Round Culvert L= 30.0' Ke= 0.500 Inlet / Outlet Invert= 308.50' / 308.10' S= 0.0133 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	311.50'	20.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)

Primary OutFlow Max=0.44 cfs @ 12.30 hrs HW=308.83' (Free Discharge)
 1=Culvert (Inlet Controls 0.44 cfs @ 1.95 fps)
 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 15P: EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Inflow Area = 1.630 ac, 20.58% Impervious, Inflow Depth > 1.21" for 2 YEAR event
 Inflow = 1.75 cfs @ 12.13 hrs, Volume= 0.164 af
 Outflow = 1.02 cfs @ 12.38 hrs, Volume= 0.164 af, Atten= 42%, Lag= 15.3 min
 Primary = 1.02 cfs @ 12.38 hrs, Volume= 0.164 af

Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 326.08' @ 12.38 hrs Surf.Area= 3,729 sf Storage= 1,230 cf

Plug-Flow detention time= 18.4 min calculated for 0.164 af (99% of inflow)
 Center-of-Mass det. time= 15.5 min (868.1 - 852.6)

Volume	Invert	Avail.Storage	Storage Description
#1	325.50'	12,719 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
325.50	0	0	0
326.00	3,700	925	925
328.00	4,400	8,100	9,025
328.75	5,450	3,694	12,719

Device	Routing	Invert	Outlet Devices
#1	Primary	325.50'	12.0" Round Culvert L= 38.0' Ke= 0.500 Inlet / Outlet Invert= 325.50' / 325.25' S= 0.0066 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	328.25'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68

2.72 2.81 2.92 2.97 3.07 3.32

Primary OutFlow Max=1.02 cfs @ 12.38 hrs HW=326.08' (Free Discharge)
 1=Culvert (Barrel Controls 1.02 cfs @ 3.10 fps)
 2=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 17P: EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 1.26" for 2 YEAR event
 Inflow = 18.37 cfs @ 12.12 hrs, Volume= 1.461 af
 Outflow = 5.74 cfs @ 12.51 hrs, Volume= 1.456 af, Atten= 69%, Lag= 23.4 min
 Primary = 5.74 cfs @ 12.51 hrs, Volume= 1.456 af
 Routed to Reach 17R : FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 353.80' @ 12.51 hrs Surf.Area= 8,316 sf Storage= 16,011 cf

Plug-Flow detention time= 26.3 min calculated for 1.456 af (100% of inflow)
 Center-of-Mass det. time= 24.3 min (875.2 - 850.9)

Volume	Invert	Avail.Storage	Storage Description
#1	351.00'	44,275 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
351.00	0	0	0
352.00	6,070	3,035	3,035
354.00	8,560	14,630	17,665
356.00	18,050	26,610	44,275

Device	Routing	Invert	Outlet Devices
#1	Primary	351.00'	12.0" Round Culvert L= 60.0' Ke= 0.500 Inlet / Outlet Invert= 351.00' / 349.00' S= 0.0333 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	355.00'	20.0' long x 4.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.38 2.54 2.69 2.68 2.67 2.67 2.65 2.66 2.66 2.68 2.72 2.73 2.76 2.79 2.88 3.07 3.32

Primary OutFlow Max=5.74 cfs @ 12.51 hrs HW=353.80' (Free Discharge)
 1=Culvert (Inlet Controls 5.74 cfs @ 7.31 fps)
 2=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 18P: DET BASIN ON EAGLE LEASING

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 1.57" for 2 YEAR event
 Inflow = 8.93 cfs @ 12.18 hrs, Volume= 0.788 af
 Outflow = 5.25 cfs @ 12.40 hrs, Volume= 0.788 af, Atten= 41%, Lag= 13.2 min
 Primary = 5.25 cfs @ 12.40 hrs, Volume= 0.788 af

Routed to Reach 18R : FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 344.92' @ 12.40 hrs Surf.Area= 5,269 sf Storage= 3,684 cf

Plug-Flow detention time= 4.4 min calculated for 0.788 af (100% of inflow)
 Center-of-Mass det. time= 4.2 min (846.2 - 842.0)

Volume	Invert	Avail.Storage	Storage Description
#1	342.50'	46,903 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
342.50	0	0	0
344.00	1,030	773	773
346.00	10,200	11,230	12,003
348.00	24,700	34,900	46,903

Device	Routing	Invert	Outlet Devices
#1	Primary	342.50'	12.0" Round Culvert L= 33.0' Ke= 0.500 Inlet / Outlet Invert= 342.50' / 342.10' S= 0.0121 ' / Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	347.00'	12.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 4.5' Crest Height

Primary OutFlow Max=5.25 cfs @ 12.40 hrs HW=344.92' (Free Discharge)

1=Culvert (Inlet Controls 5.25 cfs @ 6.68 fps)
 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 23P: INFILTRATION BASIN WITH 76 R902s

Inflow Area = 0.994 ac, 96.93% Impervious, Inflow Depth > 2.98" for 2 YEAR event
 Inflow = 3.14 cfs @ 12.08 hrs, Volume= 0.247 af
 Outflow = 0.23 cfs @ 11.56 hrs, Volume= 0.247 af, Atten= 93%, Lag= 0.0 min
 Discarded = 0.23 cfs @ 11.56 hrs, Volume= 0.247 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af
 Routed to Pond 11P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD
 Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af
 Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 304.62' @ 13.40 hrs Surf.Area= 3,879 sf Storage= 4,607 cf

Plug-Flow detention time= 173.7 min calculated for 0.247 af (100% of inflow)
 Center-of-Mass det. time= 172.6 min (937.1 - 764.6)

Volume	Invert	Avail.Storage	Storage Description
#1	302.50'	8,272 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 20,681 cf Overall x 40.0% Voids
#2	303.00'	4,966 cf	Cultec R-902HD v2 x 76 Effective Size= 69.1"W x 48.0"H => 17.30 sf x 3.67'L = 63.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap

76 Chambers in 4 Rows
 Cap Storage= 18.0 cf x 2 x 4 rows = 144.2 cf

13,238 cf Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
302.50	2,433	0	0
311.00	2,433	20,681	20,681

Device	Routing	Invert	Outlet Devices
#1	Discarded	302.50'	2.410 in/hr Exfiltration over Surface area
#2	Primary	310.00'	10.0" Round Culvert L= 51.0' Ke= 0.500 Inlet / Outlet Invert= 310.00' / 309.50' S= 0.0098 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.55 sf
#3	Secondary	307.50'	6.0" Round Culvert L= 86.0' Ke= 0.500 Inlet / Outlet Invert= 307.50' / 306.25' S= 0.0145 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.23 cfs @ 11.56 hrs HW=303.00' (Free Discharge)

1=Exfiltration (Exfiltration Controls 0.23 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=302.50' (Free Discharge)

2=Culvert (Controls 0.00 cfs)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=302.50' (Free Discharge)

3=Culvert (Controls 0.00 cfs)

Summary for Pond 24P: INFILTRATION STRUCTURE UNDER PARKING

Inflow Area = 1.748 ac, 63.70% Impervious, Inflow Depth > 2.02" for 2 YEAR event
 Inflow = 3.04 cfs @ 12.22 hrs, Volume= 0.295 af
 Outflow = 0.77 cfs @ 12.74 hrs, Volume= 0.286 af, Atten= 75%, Lag= 31.3 min
 Discarded = 0.18 cfs @ 11.28 hrs, Volume= 0.212 af
 Primary = 0.59 cfs @ 12.74 hrs, Volume= 0.074 af

Routed to Reach 26R : FLOW PATH FROM OUTLET TO PARKERVILLE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 322.64' @ 12.74 hrs Surf.Area= 3,284 sf Storage= 4,942 cf

Plug-Flow detention time= 157.3 min calculated for 0.286 af (97% of inflow)
 Center-of-Mass det. time= 139.9 min (964.8 - 824.8)

Volume	Invert	Avail.Storage	Storage Description
#1	320.50'	3,836 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 26,272 cf Overall - 16,683 cf Embedded = 9,589 cf x 40.0% Voids
#2	321.00'	12,422 cf	retain_it retain_it 5.0' x 46 Inside #1 Inside= 84.0"W x 60.0"H => 36.41 sf x 8.00'L = 291.3 cf Outside= 96.0"W x 68.0"H => 45.33 sf x 8.00'L = 362.7 cf 1 Rows adjusted for 976.7 cf perimeter wall

16,258 cf Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
320.50	3,284	0	0
328.50	3,284	26,272	26,272

Device	Routing	Invert	Outlet Devices
#1	Discarded	320.50'	2.410 in/hr Exfiltration over Surface area
#2	Primary	326.70'	8.0" Round Culvert L= 18.0' Ke= 0.500 Inlet / Outlet Invert= 326.70' / 319.00' S= 0.4278 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf
#3	Primary	322.00'	6.0" Round Culvert L= 18.0' Ke= 0.500 Inlet / Outlet Invert= 322.00' / 320.00' S= 0.1111 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.18 cfs @ 11.28 hrs HW=320.58' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.18 cfs)

Primary OutFlow Max=0.59 cfs @ 12.74 hrs HW=322.63' (Free Discharge)
 ↑2=Culvert (Controls 0.00 cfs)
 ↓3=Culvert (Inlet Controls 0.59 cfs @ 2.99 fps)

Summary for Pond 27P: INFILTRATION STRUCTURE FOR 9-11

Inflow Area = 0.035 ac, 100.00% Impervious, Inflow Depth > 3.10" for 2 YEAR event
 Inflow = 0.11 cfs @ 12.07 hrs, Volume= 0.009 af
 Outflow = 0.01 cfs @ 10.68 hrs, Volume= 0.008 af, Atten= 94%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 10.68 hrs, Volume= 0.008 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 338.17' @ 13.83 hrs Surf.Area= 270 sf Storage= 171 cf

Plug-Flow detention time= 223.2 min calculated for 0.008 af (95% of inflow)
 Center-of-Mass det. time= 192.6 min (946.9 - 754.3)

Volume	Invert	Avail.Storage	Storage Description
#1	337.00'	291 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 1,350 cf Overall - 623 cf Embedded = 727 cf x 40.0% Voids
#2	337.50'	464 cf	Shea Dry Well 300gal x 10 Inside #1 Inside= 42.2"W x 45.0"H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0"W x 51.0"H => 15.58 sf x 4.00'L = 62.3 cf 10 Chambers in 2 Rows
		754 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
337.00	270	0	0
342.00	270	1,350	1,350

Device	Routing	Invert	Outlet Devices
#1	Discarded	337.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 10.68 hrs HW=337.05' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.01 cfs)

Summary for Pond 28P: INFILTRATION STRUCTURE FOR 22-24

Inflow Area = 0.035 ac, 100.00% Impervious, Inflow Depth > 3.10" for 2 YEAR event
 Inflow = 0.11 cfs @ 12.07 hrs, Volume= 0.009 af
 Outflow = 0.01 cfs @ 10.68 hrs, Volume= 0.008 af, Atten= 94%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 10.68 hrs, Volume= 0.008 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 333.17' @ 13.83 hrs Surf.Area= 270 sf Storage= 171 cf

Plug-Flow detention time= 223.2 min calculated for 0.008 af (95% of inflow)
 Center-of-Mass det. time= 192.6 min (946.9 - 754.3)

Volume	Invert	Avail.Storage	Storage Description
#1	332.00'	291 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 1,350 cf Overall - 623 cf Embedded = 727 cf x 40.0% Voids
#2	332.50'	464 cf	Shea Dry Well 300gal x 10 Inside #1 Inside= 42.2"W x 45.0"H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0"W x 51.0"H => 15.58 sf x 4.00'L = 62.3 cf 10 Chambers in 2 Rows
		754 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
332.00	270	0	0
337.00	270	1,350	1,350

Device	Routing	Invert	Outlet Devices
#1	Discarded	332.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 10.68 hrs HW=332.05' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.01 cfs)

Summary for Pond 29P: INFILTRATION STRUCTURE FOR 20-21 & 26-29

Inflow Area = 0.093 ac, 100.00% Impervious, Inflow Depth > 3.10" for 2 YEAR event
 Inflow = 0.31 cfs @ 12.07 hrs, Volume= 0.024 af
 Outflow = 0.01 cfs @ 10.24 hrs, Volume= 0.019 af, Atten= 95%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 10.24 hrs, Volume= 0.019 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 328.46' @ 14.43 hrs Surf.Area= 589 sf Storage= 496 cf

Plug-Flow detention time= 253.1 min calculated for 0.019 af (80% of inflow)
 Center-of-Mass det. time= 177.5 min (931.8 - 754.3)

Volume	Invert	Avail.Storage	Storage Description
#1	327.00'	697 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 3,240 cf Overall - 1,496 cf Embedded = 1,744 cf x 40.0% Voids
#2	327.50'	1,113 cf	Shea Dry Well 300gal x 24 Inside #1 Inside= 42.2"W x 45.0"H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0"W x 51.0"H => 15.58 sf x 4.00'L = 62.3 cf 24 Chambers in 4 Rows
1,811 cf			Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
327.00	589	0	0
332.50	589	3,240	3,240

Device	Routing	Invert	Outlet Devices
#1	Discarded	327.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 10.24 hrs HW=327.06' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.01 cfs)

10 YEAR STORM

PREDEVELOPMENT

Summary for Subcatchment 1S: PREDEV FLOW FROM PARKING AREA

Runoff = 4.92 cfs @ 12.08 hrs, Volume= 0.396 af, Depth> 4.78"
 Routed to Pond 1P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
41,985	98	Paved parking, HSG B
280	74	>75% Grass cover, Good, HSG C
1,049	61	>75% Grass cover, Good, HSG B

43,314	97	Weighted Average
1,329		3.07% Pervious Area
41,985		96.93% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
6.0					Direct Entry,

Summary for Subcatchment 2S: PREDEV OVERLAND FLOW TO DETENTION BASIN

Runoff = 0.61 cfs @ 12.17 hrs, Volume= 0.055 af, Depth> 1.52"
 Routed to Pond 1P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
2,913	98	Water Surface, HSG B
1,161	70	Woods, Good, HSG C
14,991	55	Woods, Good, HSG B

19,065	62	Weighted Average
16,152		84.72% Pervious Area
2,913		15.28% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
10.5	50	0.0300	0.08		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
0.5	58	0.1600	2.00		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
11.0	108				Total

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 10 YEAR Rainfall=5.14"

Printed 11/23/2024

Page 2

Summary for Subcatchment 3S: PREDEV OVERLAND FLOW TO PARKERVILLE ROAD

Runoff = 6.22 cfs @ 12.37 hrs, Volume= 0.748 af, Depth> 1.74"
 Routed to Reach 1R : PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
144,569	70	Woods, Good, HSG C
63,690	55	Woods, Good, HSG B
16,200	61	>75% Grass cover, Good, HSG B
780	98	Roofs, HSG B

225,239	65	Weighted Average
224,459		99.65% Pervious Area
780		0.35% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
9.9	754	0.0640	1.26		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.9	243	0.0370	4.76	57.07	Channel Flow, 2' WIDE BOTTOM, 10:1 SIDE SLOPES, 1'DEEP Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
24.6	1,047				Total

Summary for Subcatchment 4S: OVERLAND FLOW TO ROUTE 9

Runoff = 7.81 cfs @ 12.26 hrs, Volume= 0.810 af, Depth> 2.13"
 Routed to Reach 4R : ROUTE 9

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
54,059	55	Woods, Good, HSG B
24,068	55	Woods, Good, HSG B
36,060	70	Woods, Good, HSG C
33,500	61	>75% Grass cover, Good, HSG B
1,900	74	>75% Grass cover, Good, HSG C
42,307	98	Paved parking, HSG B
2,250	98	Paved parking, HSG B
4,349	98	Paved parking, HSG C
198,493	70	Weighted Average
149,587		75.36% Pervious Area
48,906		24.64% Impervious Area

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 10 YEAR Rainfall=5.14"

Printed 11/23/2024

Page 3

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.0400	0.13		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
1.1	242	0.0600	3.67		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
9.1	709	0.0680	1.30		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.9	365	0.0160	3.13	37.53	Channel Flow, Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
18.3	1,366				Total

Summary for Subcatchment 5S: DRAINAGE COLLECTED BY CB'S SW OF SELF STORAGE BUILDING

Runoff = 1.96 cfs @ 12.09 hrs, Volume= 0.141 af, Depth> 3.40"
 Routed to Pond 5P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
6,345	61	>75% Grass cover, Good, HSG B
3,301	74	>75% Grass cover, Good, HSG C
6,254	98	Paved parking, HSG B
5,860	98	Paved parking, HSG C
21,760	84	Weighted Average
9,646		44.33% Pervious Area
12,114		55.67% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 6S: OVERLAND FLOW TO EXISTING DETENTION BASIN

Runoff = 2.32 cfs @ 12.18 hrs, Volume= 0.209 af, Depth> 2.22"
 Routed to Pond 5P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
46,762	70	Woods, Good, HSG C
2,500	98	Water Surface, HSG C
49,262	71	Weighted Average
46,762		94.93% Pervious Area
2,500		5.07% Impervious Area

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 10 YEAR Rainfall=5.14"

Printed 11/23/2024

Page 4

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	50	0.0450	0.09		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
3.8	324	0.0800	1.41		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
12.7	374	Total			

Summary for Subcatchment 7S: RUNOFF COLLECTED BY SARSEN STONE WAY

Runoff = 31.84 cfs @ 12.12 hrs, Volume= 2.472 af, Depth> 2.92"
 Routed to Pond 7P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
317,393	84	1 acre lots, 20% imp, HSG D
125,360	68	1 acre lots, 20% imp, HSG B
442,753	79	Weighted Average
354,202		80.00% Pervious Area
88,551		20.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
2.0	214	0.1300	1.80		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.6	175	0.1000	4.74		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
0.5	210	0.1000	6.42		Shallow Concentrated Flow, Paved Kv= 20.3 fps
8.4	649	Total			

Summary for Subcatchment 8S: PREDEV FLOW ON EAGLE LEASING

Runoff = 17.78 cfs @ 12.17 hrs, Volume= 1.559 af, Depth> 3.10"
 Routed to Pond 8P : DET BASIN ON EAGLE LEASING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 10 YEAR Rainfall=5.14"

Printed 11/23/2024

Page 5

Area (sf)	CN	Description			
24,658	98	Paved parking, HSG B			
8,220	61	>75% Grass cover, Good, HSG B			
104,681	98	Paved parking, HSG C			
34,894	74	>75% Grass cover, Good, HSG C			
235	98	Paved parking, HSG D			
6,197	80	>75% Grass cover, Good, HSG D			
30,530	61	>75% Grass cover, Good, HSG B			
5,140	98	Paved parking, HSG B			
48,076	55	Woods, Good, HSG B			
262,631	81	Weighted Average			
127,917		48.71% Pervious Area			
134,714		51.29% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
4.2	413	0.1100	1.66		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
2.9	360	0.0440	2.10		Shallow Concentrated Flow, Nearly Bare & Untilled Kv= 10.0 fps
12.4	823				Total

Summary for Subcatchment 9S: OVERLAND FLOW TO DET BASIN BEHIND 5 & 7 SARSEN STONE

Runoff = 8.29 cfs @ 12.09 hrs, Volume= 0.609 af, Depth> 1.98"
 Routed to Pond 7P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description			
20,407	70	Woods, Good, HSG C			
3,300	98	Water Surface, HSG B			
36,775	55	Woods, Good, HSG B			
13,560	85	1/2 acre lots, 25% imp, HSG D			
87,016	70	1/2 acre lots, 25% imp, HSG B			
161,058	68	Weighted Average			
132,614		82.34% Pervious Area			
28,444		17.66% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
6.0					Direct Entry,

Summary for Reach 1R: PARKERVILLE ROAD

Inflow Area = 6.603 ac, 15.88% Impervious, Inflow Depth > 2.18" for 10 YEAR event
Inflow = 9.01 cfs @ 12.36 hrs, Volume= 1.199 af
Outflow = 9.01 cfs @ 12.36 hrs, Volume= 1.199 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 4R: ROUTE 9

Inflow Area = 26.078 ac, 27.75% Impervious, Inflow Depth > 2.66" for 10 YEAR event
Inflow = 34.86 cfs @ 12.38 hrs, Volume= 5.781 af
Outflow = 34.86 cfs @ 12.38 hrs, Volume= 5.781 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 7R: FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 2.66" for 10 YEAR event
Inflow = 19.80 cfs @ 12.33 hrs, Volume= 3.072 af
Outflow = 19.61 cfs @ 12.37 hrs, Volume= 3.069 af, Atten= 1%, Lag= 2.4 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 5.50 fps, Min. Travel Time= 1.2 min
Avg. Velocity = 2.60 fps, Avg. Travel Time= 2.5 min

Peak Storage= 1,420 cf @ 12.35 hrs
Average Depth at Peak Storage= 0.73', Surface Width= 7.82'
Bank-Full Depth= 2.00' Flow Area= 20.0 sf, Capacity= 198.41 cfs

2.00' x 2.00' deep channel, n= 0.040 Earth, cobble bottom, clean sides
Side Slope Z-value= 4.0 '/' Top Width= 18.00'
Length= 397.0' Slope= 0.0642 '/'
Inlet Invert= 349.00', Outlet Invert= 323.50'

†

Summary for Reach 8R: FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 3.10" for 10 YEAR event
Inflow = 6.71 cfs @ 12.53 hrs, Volume= 1.558 af
Outflow = 6.71 cfs @ 12.54 hrs, Volume= 1.558 af, Atten= 0%, Lag= 0.6 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Max. Velocity= 7.56 fps, Min. Travel Time= 0.3 min

Avg. Velocity = 3.89 fps, Avg. Travel Time= 0.7 min

Peak Storage= 139 cf @ 12.53 hrs

Average Depth at Peak Storage= 0.40', Surface Width= 3.41'


Bank-Full Depth= 2.00' Flow Area= 14.0 sf, Capacity= 271.03 cfs

1.00' x 2.00' deep channel, n= 0.025 Earth, clean & winding

Side Slope Z-value= 3.0 '/' Top Width= 13.00'

Length= 157.0' Slope= 0.1025 '/'

Inlet Invert= 342.10', Outlet Invert= 326.00'



Summary for Reach 22R: FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Inflow Area = 21.521 ac, 28.41% Impervious, Inflow Depth > 2.77" for 10 YEAR event

Inflow = 28.52 cfs @ 12.37 hrs, Volume= 4.975 af

Outflow = 28.34 cfs @ 12.40 hrs, Volume= 4.971 af, Atten= 1%, Lag= 1.9 min

Routed to Reach 4R : ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Max. Velocity= 6.81 fps, Min. Travel Time= 0.9 min

Avg. Velocity = 3.20 fps, Avg. Travel Time= 2.0 min

Peak Storage= 1,598 cf @ 12.38 hrs

Average Depth at Peak Storage= 0.51', Surface Width= 13.26'


Bank-Full Depth= 2.00' Flow Area= 46.0 sf, Capacity= 707.92 cfs

3.00' x 2.00' deep channel, n= 0.030 Earth, grassed & winding

Side Slope Z-value= 10.0 '/' Top Width= 43.00'

Length= 383.0' Slope= 0.0888 '/'

Inlet Invert= 349.00', Outlet Invert= 315.00'



‡

Summary for Pond 1P: EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Inflow Area = 1.432 ac, 71.98% Impervious, Inflow Depth > 3.79" for 10 YEAR event
 Inflow = 5.38 cfs @ 12.09 hrs, Volume= 0.452 af
 Outflow = 2.89 cfs @ 12.24 hrs, Volume= 0.451 af, Atten= 46%, Lag= 9.3 min
 Primary = 2.89 cfs @ 12.24 hrs, Volume= 0.451 af
 Routed to Reach 1R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 309.58' @ 12.24 hrs Surf.Area= 5,028 sf Storage= 2,725 cf

Plug-Flow detention time= 11.0 min calculated for 0.451 af (100% of inflow)
 Center-of-Mass det. time= 9.9 min (778.9 - 769.0)

Volume	Invert	Avail.Storage	Storage Description
#1	308.50'	20,440 cf	Custom Stage Data (Prismatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
308.50	0	0	0
310.00	6,960	5,220	5,220
312.00	8,260	15,220	20,440

Device	Routing	Invert	Outlet Devices
#1	Primary	308.50'	12.0" Round Culvert L= 30.0' Ke= 0.500 Inlet / Outlet Invert= 308.50' / 308.10' S= 0.0133 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	311.50'	20.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)

Primary OutFlow Max=2.89 cfs @ 12.24 hrs HW=309.58' (Free Discharge)

1=Culvert (Inlet Controls 2.89 cfs @ 3.68 fps)

2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 5P: EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Inflow Area = 1.630 ac, 20.58% Impervious, Inflow Depth > 2.58" for 10 YEAR event
 Inflow = 3.86 cfs @ 12.13 hrs, Volume= 0.350 af
 Outflow = 2.32 cfs @ 12.35 hrs, Volume= 0.349 af, Atten= 40%, Lag= 13.4 min
 Primary = 2.32 cfs @ 12.35 hrs, Volume= 0.349 af
 Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 326.48' @ 12.35 hrs Surf.Area= 3,869 sf Storage= 2,757 cf

Plug-Flow detention time= 18.8 min calculated for 0.349 af (100% of inflow)
 Center-of-Mass det. time= 16.3 min (848.6 - 832.4)

Volume	Invert	Avail.Storage	Storage Description
#1	325.50'	12,719 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 10 YEAR Rainfall=5.14"

Printed 11/23/2024

Page 9

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
325.50	0	0	0
326.00	3,700	925	925
328.00	4,400	8,100	9,025
328.75	5,450	3,694	12,719

Device	Routing	Invert	Outlet Devices
#1	Primary	325.50'	12.0" Round Culvert L= 38.0' Ke= 0.500 Inlet / Outlet Invert= 325.50' / 325.25' S= 0.0066 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	328.25'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68 2.72 2.81 2.92 2.97 3.07 3.32

Primary OutFlow Max=2.32 cfs @ 12.35 hrs HW=326.48' (Free Discharge)

1=Culvert (Barrel Controls 2.32 cfs @ 3.73 fps)

2=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 7P: EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 2.67" for 10 YEAR event

Inflow = 39.78 cfs @ 12.12 hrs, Volume= 3.081 af

Outflow = 19.80 cfs @ 12.33 hrs, Volume= 3.072 af, Atten= 50%, Lag= 12.9 min

Primary = 19.80 cfs @ 12.33 hrs, Volume= 3.072 af

Routed to Reach 7R : FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Peak Elev= 355.39' @ 12.33 hrs Surf.Area= 15,154 sf Storage= 34,144 cf

Plug-Flow detention time= 35.3 min calculated for 3.067 af (100% of inflow)

Center-of-Mass det. time= 33.5 min (863.2 - 829.7)

Volume	Invert	Avail.Storage	Storage Description
#1	351.00'	44,275 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
351.00	0	0	0
352.00	6,070	3,035	3,035
354.00	8,560	14,630	17,665
356.00	18,050	26,610	44,275

Device	Routing	Invert	Outlet Devices
#1	Primary	351.00'	12.0" Round Culvert L= 60.0' Ke= 0.500 Inlet / Outlet Invert= 351.00' / 349.00' S= 0.0333 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	355.00'	20.0' long x 4.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00

2.50	3.00	3.50	4.00	4.50	5.00	5.50
Coef. (English) 2.38 2.54 2.69 2.68 2.67 2.67 2.65 2.66 2.66						
2.68	2.72	2.73	2.76	2.79	2.88	3.07 3.32

Primary OutFlow Max=19.66 cfs @ 12.33 hrs HW=355.39' (Free Discharge)

1=Culvert (Inlet Controls 7.46 cfs @ 9.49 fps)

2=Broad-Crested Rectangular Weir (Weir Controls 12.21 cfs @ 1.57 fps)

Summary for Pond 8P: DET BASIN ON EAGLE LEASING

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 3.10" for 10 YEAR event

Inflow = 17.78 cfs @ 12.17 hrs, Volume= 1.559 af

Outflow = 6.71 cfs @ 12.53 hrs, Volume= 1.558 af, Atten= 62%, Lag= 21.4 min

Primary = 6.71 cfs @ 12.53 hrs, Volume= 1.558 af

Routed to Reach 8R : FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Peak Elev= 346.15' @ 12.53 hrs Surf.Area= 11,290 sf Storage= 13,617 cf

Plug-Flow detention time= 12.5 min calculated for 1.556 af (100% of inflow)

Center-of-Mass det. time= 12.3 min (834.8 - 822.5)

Volume	Invert	Avail.Storage	Storage Description
#1	342.50'	46,903 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
342.50	0	0	0
344.00	1,030	773	773
346.00	10,200	11,230	12,003
348.00	24,700	34,900	46,903

Device	Routing	Invert	Outlet Devices
#1	Primary	342.50'	12.0" Round Culvert L= 33.0' Ke= 0.500 Inlet / Outlet Invert= 342.50' / 342.10' S= 0.0121 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	347.00'	12.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 4.5' Crest Height

Primary OutFlow Max=6.71 cfs @ 12.53 hrs HW=346.15' (Free Discharge)

1=Culvert (Inlet Controls 6.71 cfs @ 8.54 fps)

2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

POSTDEVELOPMENT

Summary for Subcatchment 11S: POSTDEV FLOW FROM PARKING AREA

Runoff = 4.92 cfs @ 12.08 hrs, Volume= 0.396 af, Depth> 4.78"
 Routed to Pond 23P : INFILTRATION BASIN WITH 76 R902s

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
41,985	98	Paved parking, HSG B
280	74	>75% Grass cover, Good, HSG C
1,049	61	>75% Grass cover, Good, HSG B
43,314	97	Weighted Average
1,329		3.07% Pervious Area
41,985		96.93% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
6.0	Direct Entry,				

Summary for Subcatchment 12S: POSTDEV OVERLAND FLOW TO DETENTION BASIN

Runoff = 1.38 cfs @ 12.16 hrs, Volume= 0.117 af, Depth> 2.47"
 Routed to Pond 11P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
2,913	98	Water Surface, HSG B
12,916	70	Woods, Good, HSG C
189	55	Woods, Good, HSG B
7,152	74	>75% Grass cover, Good, HSG C
1,644	61	>75% Grass cover, Good, HSG B
24,814	74	Weighted Average
21,901		88.26% Pervious Area
2,913		11.74% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
10.5	50	0.0300	0.08	Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"	
0.5	58	0.1600	2.00	Shallow Concentrated Flow, Woodland Kv= 5.0 fps	

11.0 108 Total

Summary for Subcatchment 13S: POSTDEV OVERLAND FLOW TO PARKERVILLE ROAD

Runoff = 3.85 cfs @ 12.36 hrs, Volume= 0.454 af, Depth> 1.97"
 Routed to Reach 11R : PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
1,943	55	Woods, Good, HSG B
1,148	98	Roofs, HSG B
1,254	61	>75% Grass cover, Good, HSG B
183	70	Woods, Good, HSG C
1,148	98	Roofs, HSG C
5,275	74	>75% Grass cover, Good, HSG C
22,271	55	Woods, Good, HSG B
789	98	Roofs, HSG B
19,728	61	>75% Grass cover, Good, HSG B
26,543	70	Woods, Good, HSG C
4,032	98	Roofs, HSG C
36,320	74	>75% Grass cover, Good, HSG C
120,634	68	Weighted Average
113,517		94.10% Pervious Area
7,117		5.90% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
9.9	754	0.0640	1.26		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.9	243	0.0370	4.76	57.07	Channel Flow, 2' WIDE BOTTOM, 10:1 SIDE SLOPES,1'DEEP Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
24.6	1,047				Total

Summary for Subcatchment 14S: OVERLAND FLOW TO ROUTE 9

Runoff = 7.81 cfs @ 12.26 hrs, Volume= 0.810 af, Depth> 2.13"
 Routed to Reach 14R : ROUTE 9

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description		
31,704	70	Woods, Good, HSG C		
0	98	Roofs, HSG C		
4,306	98	Roofs, HSG C		
11,703	74	>75% Grass cover, Good, HSG C		
76,405	55	Woods, Good, HSG B		
44,135	98	Paved parking, HSG B		
30,229	61	>75% Grass cover, Good, HSG B		
198,482	70	Weighted Average		
150,041		75.59% Pervious Area		
48,441		24.41% Impervious Area		
Tc (min)	Length (feet)	Slope (ft/ft)		
Velocity (ft/sec)	Capacity (cfs)	Description		
6.2	50	0.0400	0.13	Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
1.1	242	0.0600	3.67	Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
9.1	709	0.0680	1.30	Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.9	365	0.0160	3.13	37.53 Channel Flow, Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
18.3	1,366	Total		

Summary for Subcatchment 15S: DRAINAGE COLLECTED BY CB'S SW OF SELF STORAGE BUILDING

Runoff = 1.96 cfs @ 12.09 hrs, Volume= 0.141 af, Depth> 3.40"
 Routed to Pond 15P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description	
6,345	61	>75% Grass cover, Good, HSG B	
3,301	74	>75% Grass cover, Good, HSG C	
6,254	98	Paved parking, HSG B	
5,860	98	Paved parking, HSG C	
21,760	84	Weighted Average	
9,646		44.33% Pervious Area	
12,114		55.67% Impervious Area	
Tc (min)	Length (feet)	Slope (ft/ft)	
Velocity (ft/sec)	Capacity (cfs)	Description	
6.0			Direct Entry,

Summary for Subcatchment 16S: OVERLAND FLOW TO EXISTING DETENTION BASIN

Runoff = 2.32 cfs @ 12.18 hrs, Volume= 0.209 af, Depth> 2.22"
 Routed to Pond 15P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
46,762	70	Woods, Good, HSG C
2,500	98	Water Surface, HSG C
49,262	71	Weighted Average
46,762		94.93% Pervious Area
2,500		5.07% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	50	0.0450	0.09		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
3.8	324	0.0800	1.41		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
12.7	374			Total	

Summary for Subcatchment 17S: RUNOFF COLLECTED BY SARSEN STONE WAY

Runoff = 31.84 cfs @ 12.12 hrs, Volume= 2.472 af, Depth> 2.92"
 Routed to Pond 17P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
317,393	84	1 acre lots, 20% imp, HSG D
125,360	68	1 acre lots, 20% imp, HSG B
442,753	79	Weighted Average
354,202		80.00% Pervious Area
88,551		20.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
2.0	214	0.1300	1.80		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.6	175	0.1000	4.74		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
0.5	210	0.1000	6.42		Shallow Concentrated Flow, Paved Kv= 20.3 fps
8.4	649			Total	

Summary for Subcatchment 18S: POSTDEV FLOW ON EAGLE LEASING

Runoff = 17.78 cfs @ 12.17 hrs, Volume= 1.559 af, Depth> 3.10"
 Routed to Pond 18P : DET BASIN ON EAGLE LEASING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
24,658	98	Paved parking, HSG B
8,220	61	>75% Grass cover, Good, HSG B
104,681	98	Paved parking, HSG C
34,894	74	>75% Grass cover, Good, HSG C
235	98	Paved parking, HSG D
6,197	80	>75% Grass cover, Good, HSG D
30,530	61	>75% Grass cover, Good, HSG B
5,140	98	Paved parking, HSG B
48,076	55	Woods, Good, HSG B
262,631	81	Weighted Average
127,917		48.71% Pervious Area
134,714		51.29% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
4.2	413	0.1100	1.66		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
2.9	360	0.0440	2.10		Shallow Concentrated Flow, Nearly Bare & Untilled Kv= 10.0 fps
12.4	823	Total			

Summary for Subcatchment 19S: OVERLAND FLOW TO DET BASIN BEHIND 5 & 7 SARSEN STONE

Runoff = 8.29 cfs @ 12.09 hrs, Volume= 0.609 af, Depth> 1.98"
 Routed to Pond 17P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
20,407	70	Woods, Good, HSG C
3,300	98	Water Surface, HSG B
36,775	55	Woods, Good, HSG B
13,560	85	1/2 acre lots, 25% imp, HSG D
87,016	70	1/2 acre lots, 25% imp, HSG B
161,058	68	Weighted Average
132,614		82.34% Pervious Area
28,444		17.66% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 25S: AREA CAPTURED IN MAIN DRIVE

Runoff = 5.47 cfs @ 12.22 hrs, Volume= 0.538 af, Depth> 3.69"
 Routed to Pond 24P : INFILTRATION STRUCTURE UNDER PARKING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
37,506	98	Paved parking, HSG C
11,007	98	Paved parking, HSG B
8,588	61	>75% Grass cover, Good, HSG B
16,641	74	>75% Grass cover, Good, HSG C
2,422	55	Woods, Good, HSG B
76,164	87	Weighted Average
27,651		36.30% Pervious Area
48,513		63.70% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
0.5	55	0.1400	1.87		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.0	79	0.0380	1.36		Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps
0.9	167	0.0240	3.14		Shallow Concentrated Flow, Paved Kv= 20.3 fps
16.2	351	Total			

Summary for Subcatchment 26S: DRIVEWAY AND 5 UNITS AT ENTRANCE

Runoff = 1.27 cfs @ 12.20 hrs, Volume= 0.123 af, Depth> 4.11"
 Routed to Reach 26R : FLOW PATH FROM OUTLET TO PARKERVILLE

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
4,449	74	>75% Grass cover, Good, HSG C
11,225	98	Paved parking, HSG C
15,674	91	Weighted Average
4,449		28.38% Pervious Area
11,225		71.62% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
14.3	50	0.0050	0.06		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
0.3	19	0.0050	1.06		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
14.6	69	Total			

Summary for Subcatchment 27S: BACK HALF OF ROOFS UNITS 9-11

Runoff = 0.18 cfs @ 12.07 hrs, Volume= 0.014 af, Depth> 4.90"
 Routed to Pond 27P : INFILTRATION STRUCTURE FOR 9-11

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
1,512	98	Roofs, HSG C
1,512		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 28S: BACK HALF OF ROOFS UNITS 22-24

Runoff = 0.18 cfs @ 12.07 hrs, Volume= 0.014 af, Depth> 4.90"
 Routed to Pond 28P : INFILTRATION STRUCTURE FOR 22-24

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
1,512	98	Roofs, HSG C
1,512		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 29S: ROOFS FROM 20,21,26-29

Runoff = 0.48 cfs @ 12.07 hrs, Volume= 0.038 af, Depth> 4.90"
 Routed to Pond 29P : INFILTRATION STRUCTURE FOR 20-21 & 26-29

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 YEAR Rainfall=5.14"

Area (sf)	CN	Description
4,032	98	Roofs, HSG C
4,032		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Reach 11R: PARKERVILLE ROAD

Inflow Area = 6.442 ac, 39.83% Impervious, Inflow Depth > 1.78" for 10 YEAR event
 Inflow = 6.84 cfs @ 12.35 hrs, Volume= 0.956 af
 Outflow = 6.84 cfs @ 12.35 hrs, Volume= 0.956 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 14R: ROUTE 9

Inflow Area = 26.078 ac, 27.71% Impervious, Inflow Depth > 2.66" for 10 YEAR event
 Inflow = 34.86 cfs @ 12.38 hrs, Volume= 5.781 af
 Outflow = 34.86 cfs @ 12.38 hrs, Volume= 5.781 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 17R: FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 2.66" for 10 YEAR event
 Inflow = 19.80 cfs @ 12.33 hrs, Volume= 3.072 af
 Outflow = 19.61 cfs @ 12.37 hrs, Volume= 3.069 af, Atten= 1%, Lag= 2.4 min
 Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Max. Velocity= 5.50 fps, Min. Travel Time= 1.2 min
 Avg. Velocity = 2.60 fps, Avg. Travel Time= 2.5 min

Peak Storage= 1,420 cf @ 12.35 hrs
 Average Depth at Peak Storage= 0.73' , Surface Width= 7.82'
 Bank-Full Depth= 2.00' Flow Area= 20.0 sf, Capacity= 198.41 cfs

2.00' x 2.00' deep channel, n= 0.040 Earth, cobble bottom, clean sides
 Side Slope Z-value= 4.0 ' / Top Width= 18.00'
 Length= 397.0' Slope= 0.0642 '/
 Inlet Invert= 349.00', Outlet Invert= 323.50'


Summary for Reach 18R: FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 3.10" for 10 YEAR event
Inflow = 6.71 cfs @ 12.53 hrs, Volume= 1.558 af
Outflow = 6.71 cfs @ 12.54 hrs, Volume= 1.558 af, Atten= 0%, Lag= 0.6 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 7.56 fps, Min. Travel Time= 0.3 min
Avg. Velocity = 3.89 fps, Avg. Travel Time= 0.7 min

Peak Storage= 139 cf @ 12.53 hrs
Average Depth at Peak Storage= 0.40', Surface Width= 3.41'
Bank-Full Depth= 2.00' Flow Area= 14.0 sf, Capacity= 271.03 cfs

1.00' x 2.00' deep channel, n= 0.025 Earth, clean & winding
Side Slope Z-value= 3.0 '/' Top Width= 13.00'
Length= 157.0' Slope= 0.1025 '/'
Inlet Invert= 342.10', Outlet Invert= 326.00'



Summary for Reach 22R: FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Inflow Area = 21.521 ac, 28.41% Impervious, Inflow Depth > 2.77" for 10 YEAR event
Inflow = 28.52 cfs @ 12.37 hrs, Volume= 4.975 af
Outflow = 28.34 cfs @ 12.40 hrs, Volume= 4.971 af, Atten= 1%, Lag= 1.9 min
Routed to Reach 14R : ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 6.81 fps, Min. Travel Time= 0.9 min
Avg. Velocity = 3.20 fps, Avg. Travel Time= 2.0 min

Peak Storage= 1,598 cf @ 12.38 hrs
Average Depth at Peak Storage= 0.51', Surface Width= 13.26'
Bank-Full Depth= 2.00' Flow Area= 46.0 sf, Capacity= 707.92 cfs

3.00' x 2.00' deep channel, n= 0.030 Earth, grassed & winding
Side Slope Z-value= 10.0 '/' Top Width= 43.00'
Length= 383.0' Slope= 0.0888 '/'
Inlet Invert= 349.00', Outlet Invert= 315.00'

‡

Summary for Reach 26R: FLOW PATH FROM OUTLET TO PARKERVILLE

Inflow Area = 2.108 ac, 65.05% Impervious, Inflow Depth > 2.19" for 10 YEAR event
Inflow = 2.04 cfs @ 12.26 hrs, Volume= 0.385 af
Outflow = 2.03 cfs @ 12.34 hrs, Volume= 0.385 af, Atten= 1%, Lag= 4.7 min
Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 2.46 fps, Min. Travel Time= 2.4 min
Avg. Velocity = 0.92 fps, Avg. Travel Time= 6.5 min

Peak Storage= 297 cf @ 12.30 hrs
Average Depth at Peak Storage= 0.10', Surface Width= 10.10'
Bank-Full Depth= 1.00' Flow Area= 26.0 sf, Capacity= 232.32 cfs

6.00' x 1.00' deep channel, n= 0.022 Earth, clean & straight
Side Slope Z-value= 20.0 '/' Top Width= 46.00'
Length= 360.0' Slope= 0.0375 '/'
Inlet Invert= 318.00', Outlet Invert= 304.50'

‡

Summary for Pond 11P: EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Inflow Area = 1.564 ac, 65.90% Impervious, Inflow Depth > 0.90" for 10 YEAR event
Inflow = 1.38 cfs @ 12.16 hrs, Volume= 0.117 af
Outflow = 0.99 cfs @ 12.29 hrs, Volume= 0.117 af, Atten= 29%, Lag= 7.8 min
Primary = 0.99 cfs @ 12.29 hrs, Volume= 0.117 af
Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Peak Elev= 309.01' @ 12.29 hrs Surf.Area= 2,381 sf Storage= 611 cf

Plug-Flow detention time= 9.4 min calculated for 0.117 af (100% of inflow)
Center-of-Mass det. time= 8.1 min (847.5 - 839.4)

Volume	Invert	Avail.Storage	Storage Description
#1	308.50'	20,440 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
308.50	0	0	0
310.00	6,960	5,220	5,220
312.00	8,260	15,220	20,440

Device	Routing	Invert	Outlet Devices
#1	Primary	308.50'	12.0" Round Culvert L= 30.0' Ke= 0.500 Inlet / Outlet Invert= 308.50' / 308.10' S= 0.0133 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	311.50'	20.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)

Primary OutFlow Max=0.99 cfs @ 12.29 hrs HW=309.01' (Free Discharge)

- 1=Culvert (Inlet Controls 0.99 cfs @ 2.44 fps)
- 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 15P: EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Inflow Area = 1.630 ac, 20.58% Impervious, Inflow Depth > 2.58" for 10 YEAR event
 Inflow = 3.86 cfs @ 12.13 hrs, Volume= 0.350 af
 Outflow = 2.32 cfs @ 12.35 hrs, Volume= 0.349 af, Atten= 40%, Lag= 13.4 min
 Primary = 2.32 cfs @ 12.35 hrs, Volume= 0.349 af

Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 326.48' @ 12.35 hrs Surf.Area= 3,869 sf Storage= 2,757 cf

Plug-Flow detention time= 18.8 min calculated for 0.349 af (100% of inflow)
 Center-of-Mass det. time= 16.3 min (848.6 - 832.4)

Volume	Invert	Avail.Storage	Storage Description
#1	325.50'	12,719 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
325.50	0	0	0
326.00	3,700	925	925
328.00	4,400	8,100	9,025
328.75	5,450	3,694	12,719

Device	Routing	Invert	Outlet Devices
#1	Primary	325.50'	12.0" Round Culvert L= 38.0' Ke= 0.500 Inlet / Outlet Invert= 325.50' / 325.25' S= 0.0066 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	328.25'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68

2.72 2.81 2.92 2.97 3.07 3.32

Primary OutFlow Max=2.32 cfs @ 12.35 hrs HW=326.48' (Free Discharge)
 1=Culvert (Barrel Controls 2.32 cfs @ 3.73 fps)
 2=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 17P: EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 2.67" for 10 YEAR event
 Inflow = 39.78 cfs @ 12.12 hrs, Volume= 3.081 af
 Outflow = 19.80 cfs @ 12.33 hrs, Volume= 3.072 af, Atten= 50%, Lag= 12.9 min
 Primary = 19.80 cfs @ 12.33 hrs, Volume= 3.072 af
 Routed to Reach 17R : FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 355.39' @ 12.33 hrs Surf.Area= 15,154 sf Storage= 34,144 cf

Plug-Flow detention time= 35.3 min calculated for 3.067 af (100% of inflow)
 Center-of-Mass det. time= 33.5 min (863.2 - 829.7)

Volume	Invert	Avail.Storage	Storage Description
#1	351.00'	44,275 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
351.00	0	0	0
352.00	6,070	3,035	3,035
354.00	8,560	14,630	17,665
356.00	18,050	26,610	44,275

Device	Routing	Invert	Outlet Devices
#1	Primary	351.00'	12.0" Round Culvert L= 60.0' Ke= 0.500 Inlet / Outlet Invert= 351.00' / 349.00' S= 0.0333 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	355.00'	20.0' long x 4.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.38 2.54 2.69 2.68 2.67 2.67 2.65 2.66 2.66 2.68 2.72 2.73 2.76 2.79 2.88 3.07 3.32

Primary OutFlow Max=19.66 cfs @ 12.33 hrs HW=355.39' (Free Discharge)
 1=Culvert (Inlet Controls 7.46 cfs @ 9.49 fps)
 2=Broad-Crested Rectangular Weir (Weir Controls 12.21 cfs @ 1.57 fps)

Summary for Pond 18P: DET BASIN ON EAGLE LEASING

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 3.10" for 10 YEAR event
 Inflow = 17.78 cfs @ 12.17 hrs, Volume= 1.559 af
 Outflow = 6.71 cfs @ 12.53 hrs, Volume= 1.558 af, Atten= 62%, Lag= 21.4 min
 Primary = 6.71 cfs @ 12.53 hrs, Volume= 1.558 af
 Routed to Reach 18R : FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 346.15' @ 12.53 hrs Surf.Area= 11,290 sf Storage= 13,617 cf

Plug-Flow detention time= 12.5 min calculated for 1.556 af (100% of inflow)
 Center-of-Mass det. time= 12.3 min (834.8 - 822.5)

Volume	Invert	Avail.Storage	Storage Description
#1	342.50'	46,903 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
342.50	0	0	0
344.00	1,030	773	773
346.00	10,200	11,230	12,003
348.00	24,700	34,900	46,903

Device	Routing	Invert	Outlet Devices
#1	Primary	342.50'	12.0" Round Culvert L= 33.0' Ke= 0.500 Inlet / Outlet Invert= 342.50' / 342.10' S= 0.0121 ' / Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	347.00'	12.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 4.5' Crest Height

Primary OutFlow Max=6.71 cfs @ 12.53 hrs HW=346.15' (Free Discharge)

1=Culvert (Inlet Controls 6.71 cfs @ 8.54 fps)
 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 23P: INFILTRATION BASIN WITH 76 R902s

Inflow Area = 0.994 ac, 96.93% Impervious, Inflow Depth > 4.78" for 10 YEAR event
 Inflow = 4.92 cfs @ 12.08 hrs, Volume= 0.396 af
 Outflow = 0.23 cfs @ 10.48 hrs, Volume= 0.266 af, Atten= 95%, Lag= 0.0 min
 Discarded = 0.23 cfs @ 10.48 hrs, Volume= 0.266 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af
 Routed to Pond 11P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD
 Secondary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af
 Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 306.73' @ 15.72 hrs Surf.Area= 2,790 sf Storage= 9,039 cf

Plug-Flow detention time= 265.0 min calculated for 0.266 af (67% of inflow)
 Center-of-Mass det. time= 167.2 min (921.9 - 754.7)

Volume	Invert	Avail.Storage	Storage Description
#1	302.50'	8,272 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 20,681 cf Overall x 40.0% Voids
#2	303.00'	4,966 cf	Cultec R-902HD v2 x 76 Effective Size= 69.1"W x 48.0"H => 17.30 sf x 3.67'L = 63.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap

76 Chambers in 4 Rows
 Cap Storage= 18.0 cf x 2 x 4 rows = 144.2 cf

13,238 cf Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
302.50	2,433	0	0
311.00	2,433	20,681	20,681

Device	Routing	Invert	Outlet Devices
#1	Discarded	302.50'	2.410 in/hr Exfiltration over Surface area
#2	Primary	310.00'	10.0" Round Culvert L= 51.0' Ke= 0.500 Inlet / Outlet Invert= 310.00' / 309.50' S= 0.0098 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.55 sf
#3	Secondary	307.50'	6.0" Round Culvert L= 86.0' Ke= 0.500 Inlet / Outlet Invert= 307.50' / 306.25' S= 0.0145 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.23 cfs @ 10.48 hrs HW=303.00' (Free Discharge)

↑ 1=Exfiltration (Exfiltration Controls 0.23 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=302.50' (Free Discharge)

↑ 2=Culvert (Controls 0.00 cfs)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=302.50' (Free Discharge)

↑ 3=Culvert (Controls 0.00 cfs)

Summary for Pond 24P: INFILTRATION STRUCTURE UNDER PARKING

Inflow Area = 1.748 ac, 63.70% Impervious, Inflow Depth > 3.69" for 10 YEAR event
 Inflow = 5.47 cfs @ 12.22 hrs, Volume= 0.538 af
 Outflow = 1.51 cfs @ 12.70 hrs, Volume= 0.498 af, Atten= 73%, Lag= 28.9 min
 Discarded = 0.18 cfs @ 9.92 hrs, Volume= 0.236 af
 Primary = 1.32 cfs @ 12.70 hrs, Volume= 0.262 af

Routed to Reach 26R : FLOW PATH FROM OUTLET TO PARKERVILLE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 324.21' @ 12.70 hrs Surf.Area= 3,284 sf Storage= 9,056 cf

Plug-Flow detention time= 123.4 min calculated for 0.497 af (92% of inflow)
 Center-of-Mass det. time= 85.6 min (893.6 - 808.0)

Volume	Invert	Avail.Storage	Storage Description
#1	320.50'	3,836 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 26,272 cf Overall - 16,683 cf Embedded = 9,589 cf x 40.0% Voids
#2	321.00'	12,422 cf	retain_it retain_it 5.0' x 46 Inside #1 Inside= 84.0"W x 60.0"H => 36.41 sf x 8.00'L = 291.3 cf Outside= 96.0"W x 68.0"H => 45.33 sf x 8.00'L = 362.7 cf 1 Rows adjusted for 976.7 cf perimeter wall

16,258 cf Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
320.50	3,284	0	0
328.50	3,284	26,272	26,272

Device	Routing	Invert	Outlet Devices
#1	Discarded	320.50'	2.410 in/hr Exfiltration over Surface area
#2	Primary	326.70'	8.0" Round Culvert L= 18.0' Ke= 0.500 Inlet / Outlet Invert= 326.70' / 319.00' S= 0.4278 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf
#3	Primary	322.00'	6.0" Round Culvert L= 18.0' Ke= 0.500 Inlet / Outlet Invert= 322.00' / 320.00' S= 0.1111 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.18 cfs @ 9.92 hrs HW=320.58' (Free Discharge)

1=Exfiltration (Exfiltration Controls 0.18 cfs)

Primary OutFlow Max=1.32 cfs @ 12.70 hrs HW=324.20' (Free Discharge)

2=Culvert (Controls 0.00 cfs)

3=Culvert (Inlet Controls 1.32 cfs @ 6.73 fps)

Summary for Pond 27P: INFILTRATION STRUCTURE FOR 9-11

Inflow Area = 0.035 ac, 100.00% Impervious, Inflow Depth > 4.90" for 10 YEAR event
 Inflow = 0.18 cfs @ 12.07 hrs, Volume= 0.014 af
 Outflow = 0.01 cfs @ 9.32 hrs, Volume= 0.009 af, Atten= 96%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 9.32 hrs, Volume= 0.009 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Peak Elev= 339.04' @ 15.25 hrs Surf.Area= 270 sf Storage= 322 cf

Plug-Flow detention time= 253.1 min calculated for 0.009 af (66% of inflow)

Center-of-Mass det. time= 151.8 min (898.0 - 746.3)

Volume	Invert	Avail.Storage	Storage Description
#1	337.00'	291 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 1,350 cf Overall - 623 cf Embedded = 727 cf x 40.0% Voids
#2	337.50'	464 cf	Shea Dry Well 300gal x 10 Inside #1 Inside= 42.2"W x 45.0"H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0"W x 51.0"H => 15.58 sf x 4.00'L = 62.3 cf 10 Chambers in 2 Rows
		754 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
337.00	270	0	0
342.00	270	1,350	1,350

Device	Routing	Invert	Outlet Devices
#1	Discarded	337.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 9.32 hrs HW=337.05' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.01 cfs)

Summary for Pond 28P: INFILTRATION STRUCTURE FOR 22-24

Inflow Area = 0.035 ac, 100.00% Impervious, Inflow Depth > 4.90" for 10 YEAR event
 Inflow = 0.18 cfs @ 12.07 hrs, Volume= 0.014 af
 Outflow = 0.01 cfs @ 9.32 hrs, Volume= 0.009 af, Atten= 96%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 9.32 hrs, Volume= 0.009 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 334.04' @ 15.25 hrs Surf.Area= 270 sf Storage= 322 cf

Plug-Flow detention time= 253.1 min calculated for 0.009 af (66% of inflow)
 Center-of-Mass det. time= 151.8 min (898.0 - 746.3)

Volume	Invert	Avail.Storage	Storage Description
#1	332.00'	291 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 1,350 cf Overall - 623 cf Embedded = 727 cf x 40.0% Voids
#2	332.50'	464 cf	Shea Dry Well 300gal x 10 Inside #1 Inside= 42.2"W x 45.0"H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0"W x 51.0"H => 15.58 sf x 4.00'L = 62.3 cf 10 Chambers in 2 Rows
			754 cf Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
332.00	270	0	0
337.00	270	1,350	1,350

Device	Routing	Invert	Outlet Devices
#1	Discarded	332.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 9.32 hrs HW=332.05' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.01 cfs)

Summary for Pond 29P: INFILTRATION STRUCTURE FOR 20-21 & 26-29

Inflow Area = 0.093 ac, 100.00% Impervious, Inflow Depth > 4.90" for 10 YEAR event
 Inflow = 0.48 cfs @ 12.07 hrs, Volume= 0.038 af
 Outflow = 0.01 cfs @ 8.76 hrs, Volume= 0.021 af, Atten= 97%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 8.76 hrs, Volume= 0.021 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 329.57' @ 15.81 hrs Surf.Area= 589 sf Storage= 932 cf

Plug-Flow detention time= 253.7 min calculated for 0.021 af (56% of inflow)
 Center-of-Mass det. time= 135.5 min (881.8 - 746.3)

Volume	Invert	Avail.Storage	Storage Description
#1	327.00'	697 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 3,240 cf Overall - 1,496 cf Embedded = 1,744 cf x 40.0% Voids
#2	327.50'	1,113 cf	Shea Dry Well 300gal x 24 Inside #1 Inside= 42.2" W x 45.0" H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0" W x 51.0" H => 15.58 sf x 4.00'L = 62.3 cf 24 Chambers in 4 Rows
1,811 cf			Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
327.00	589	0	0
332.50	589	3,240	3,240

Device	Routing	Invert	Outlet Devices
#1	Discarded	327.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 8.76 hrs HW=327.06' (Free Discharge)
↑ 1=Exfiltration (Exfiltration Controls 0.01 cfs)

25 YEAR STORM

PREDEVELOPMENT

Summary for Subcatchment 1S: PREDEV FLOW FROM PARKING AREA

Runoff = 6.03 cfs @ 12.08 hrs, Volume= 0.490 af, Depth> 5.91"
 Routed to Pond 1P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
41,985	98	Paved parking, HSG B
280	74	>75% Grass cover, Good, HSG C
1,049	61	>75% Grass cover, Good, HSG B
43,314	97	Weighted Average
1,329		3.07% Pervious Area
41,985		96.93% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
6.0	Direct Entry,				

Summary for Subcatchment 2S: PREDEV OVERLAND FLOW TO DETENTION BASIN

Runoff = 0.95 cfs @ 12.16 hrs, Volume= 0.083 af, Depth> 2.27"
 Routed to Pond 1P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
2,913	98	Water Surface, HSG B
1,161	70	Woods, Good, HSG C
14,991	55	Woods, Good, HSG B
19,065	62	Weighted Average
16,152		84.72% Pervious Area
2,913		15.28% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
10.5	50	0.0300	0.08	Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"	
0.5	58	0.1600	2.00	Shallow Concentrated Flow, Woodland Kv= 5.0 fps	
11.0	108	Total			

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 25 YEAR Rainfall=6.27"

Printed 11/23/2024

Page 2

Summary for Subcatchment 3S: PREDEV OVERLAND FLOW TO PARKERVILLE ROAD

Runoff = 9.32 cfs @ 12.36 hrs, Volume= 1.092 af, Depth> 2.53"
 Routed to Reach 1R : PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
144,569	70	Woods, Good, HSG C
63,690	55	Woods, Good, HSG B
16,200	61	>75% Grass cover, Good, HSG B
780	98	Roofs, HSG B

225,239	65	Weighted Average
224,459		99.65% Pervious Area
780		0.35% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
9.9	754	0.0640	1.26		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.9	243	0.0370	4.76	57.07	Channel Flow, 2' WIDE BOTTOM, 10:1 SIDE SLOPES,1'DEEP Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
24.6	1,047				Total

Summary for Subcatchment 4S: OVERLAND FLOW TO ROUTE 9

Runoff = 11.20 cfs @ 12.26 hrs, Volume= 1.143 af, Depth> 3.01"
 Routed to Reach 4R : ROUTE 9

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
54,059	55	Woods, Good, HSG B
24,068	55	Woods, Good, HSG B
36,060	70	Woods, Good, HSG C
33,500	61	>75% Grass cover, Good, HSG B
1,900	74	>75% Grass cover, Good, HSG C
42,307	98	Paved parking, HSG B
2,250	98	Paved parking, HSG B
4,349	98	Paved parking, HSG C
198,493	70	Weighted Average
149,587		75.36% Pervious Area
48,906		24.64% Impervious Area

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 25 YEAR Rainfall=6.27"

Printed 11/23/2024

Page 3

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.0400	0.13		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
1.1	242	0.0600	3.67		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
9.1	709	0.0680	1.30		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.9	365	0.0160	3.13	37.53	Channel Flow, Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
18.3	1,366				Total

Summary for Subcatchment 5S: DRAINAGE COLLECTED BY CB'S SW OF SELF STORAGE BUILDING

Runoff = 2.54 cfs @ 12.09 hrs, Volume= 0.185 af, Depth> 4.45"
 Routed to Pond 5P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
6,345	61	>75% Grass cover, Good, HSG B
3,301	74	>75% Grass cover, Good, HSG C
6,254	98	Paved parking, HSG B
5,860	98	Paved parking, HSG C
21,760	84	Weighted Average
9,646		44.33% Pervious Area
12,114		55.67% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 6S: OVERLAND FLOW TO EXISTING DETENTION BASIN

Runoff = 3.31 cfs @ 12.18 hrs, Volume= 0.293 af, Depth> 3.11"
 Routed to Pond 5P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
46,762	70	Woods, Good, HSG C
2,500	98	Water Surface, HSG C
49,262	71	Weighted Average
46,762		94.93% Pervious Area
2,500		5.07% Impervious Area

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 25 YEAR Rainfall=6.27"

Printed 11/23/2024

Page 4

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	50	0.0450	0.09		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
3.8	324	0.0800	1.41		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
12.7	374	Total			

Summary for Subcatchment 7S: RUNOFF COLLECTED BY SARSEN STONE WAY

Runoff = 42.58 cfs @ 12.12 hrs, Volume= 3.317 af, Depth> 3.92"

Routed to Pond 7P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
317,393	84	1 acre lots, 20% imp, HSG D
125,360	68	1 acre lots, 20% imp, HSG B
442,753	79	Weighted Average
354,202		80.00% Pervious Area
88,551		20.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
2.0	214	0.1300	1.80		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.6	175	0.1000	4.74		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
0.5	210	0.1000	6.42		Shallow Concentrated Flow, Paved Kv= 20.3 fps
8.4	649	Total			

Summary for Subcatchment 8S: PREDEV FLOW ON EAGLE LEASING

Runoff = 23.50 cfs @ 12.17 hrs, Volume= 2.071 af, Depth> 4.12"

Routed to Pond 8P : DET BASIN ON EAGLE LEASING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Type III 24-hr 25 YEAR Rainfall=6.27"

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 25 YEAR Rainfall=6.27"

Printed 11/23/2024

Page 5

Area (sf)	CN	Description
24,658	98	Paved parking, HSG B
8,220	61	>75% Grass cover, Good, HSG B
104,681	98	Paved parking, HSG C
34,894	74	>75% Grass cover, Good, HSG C
235	98	Paved parking, HSG D
6,197	80	>75% Grass cover, Good, HSG D
30,530	61	>75% Grass cover, Good, HSG B
5,140	98	Paved parking, HSG B
48,076	55	Woods, Good, HSG B
262,631	81	Weighted Average
127,917		48.71% Pervious Area
134,714		51.29% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
4.2	413	0.1100	1.66		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
2.9	360	0.0440	2.10		Shallow Concentrated Flow, Nearly Bare & Untilled Kv= 10.0 fps
12.4	823				Total

Summary for Subcatchment 9S: OVERLAND FLOW TO DET BASIN BEHIND 5 & 7 SARSEN STONE

Runoff = 12.06 cfs @ 12.09 hrs, Volume= 0.871 af, Depth> 2.83"

Routed to Pond 7P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
20,407	70	Woods, Good, HSG C
3,300	98	Water Surface, HSG B
36,775	55	Woods, Good, HSG B
13,560	85	1/2 acre lots, 25% imp, HSG D
87,016	70	1/2 acre lots, 25% imp, HSG B
161,058	68	Weighted Average
132,614		82.34% Pervious Area
28,444		17.66% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Reach 1R: PARKERVILLE ROAD

Inflow Area = 6.603 ac, 15.88% Impervious, Inflow Depth > 3.02" for 25 YEAR event
Inflow = 12.61 cfs @ 12.35 hrs, Volume= 1.664 af
Outflow = 12.61 cfs @ 12.35 hrs, Volume= 1.664 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 4R: ROUTE 9

Inflow Area = 26.078 ac, 27.75% Impervious, Inflow Depth > 3.62" for 25 YEAR event
Inflow = 57.74 cfs @ 12.29 hrs, Volume= 7.857 af
Outflow = 57.74 cfs @ 12.29 hrs, Volume= 7.857 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 7R: FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 3.62" for 25 YEAR event
Inflow = 38.15 cfs @ 12.22 hrs, Volume= 4.176 af
Outflow = 37.57 cfs @ 12.26 hrs, Volume= 4.172 af, Atten= 2%, Lag= 2.2 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Max. Velocity= 6.51 fps, Min. Travel Time= 1.0 min

Avg. Velocity = 2.77 fps, Avg. Travel Time= 2.4 min

Peak Storage= 2,298 cf @ 12.24 hrs

Average Depth at Peak Storage= 0.98', Surface Width= 9.83'

Bank-Full Depth= 2.00' Flow Area= 20.0 sf, Capacity= 198.41 cfs

2.00' x 2.00' deep channel, n= 0.040 Earth, cobble bottom, clean sides

Side Slope Z-value= 4.0 '/' Top Width= 18.00'

Length= 397.0' Slope= 0.0642 '/'

Inlet Invert= 349.00', Outlet Invert= 323.50'

‡

Summary for Reach 8R: FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 4.12" for 25 YEAR event
Inflow = 7.31 cfs @ 12.58 hrs, Volume= 2.070 af
Outflow = 7.31 cfs @ 12.59 hrs, Volume= 2.070 af, Atten= 0%, Lag= 0.6 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Max. Velocity= 7.74 fps, Min. Travel Time= 0.3 min

Avg. Velocity = 4.17 fps, Avg. Travel Time= 0.6 min

Peak Storage= 148 cf @ 12.58 hrs

Average Depth at Peak Storage= 0.42', Surface Width= 3.51'


Bank-Full Depth= 2.00' Flow Area= 14.0 sf, Capacity= 271.03 cfs

1.00' x 2.00' deep channel, n= 0.025 Earth, clean & winding

Side Slope Z-value= 3.0 '/' Top Width= 13.00'

Length= 157.0' Slope= 0.1025 '/'

Inlet Invert= 342.10', Outlet Invert= 326.00'



Summary for Reach 22R: FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Inflow Area = 21.521 ac, 28.41% Impervious, Inflow Depth > 3.75" for 25 YEAR event

Inflow = 47.36 cfs @ 12.26 hrs, Volume= 6.719 af

Outflow = 46.70 cfs @ 12.29 hrs, Volume= 6.714 af, Atten= 1%, Lag= 2.0 min

Routed to Reach 4R : ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Max. Velocity= 7.75 fps, Min. Travel Time= 0.8 min

Avg. Velocity = 3.41 fps, Avg. Travel Time= 1.9 min

Peak Storage= 2,319 cf @ 12.27 hrs

Average Depth at Peak Storage= 0.64', Surface Width= 15.85'


Bank-Full Depth= 2.00' Flow Area= 46.0 sf, Capacity= 707.92 cfs

3.00' x 2.00' deep channel, n= 0.030 Earth, grassed & winding

Side Slope Z-value= 10.0 '/' Top Width= 43.00'

Length= 383.0' Slope= 0.0888 '/'

Inlet Invert= 349.00', Outlet Invert= 315.00'



‡

Summary for Pond 1P: EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Inflow Area = 1.432 ac, 71.98% Impervious, Inflow Depth > 4.80" for 25 YEAR event
 Inflow = 6.77 cfs @ 12.09 hrs, Volume= 0.573 af
 Outflow = 3.32 cfs @ 12.27 hrs, Volume= 0.572 af, Atten= 51%, Lag= 11.1 min
 Primary = 3.32 cfs @ 12.27 hrs, Volume= 0.572 af
 Routed to Reach 1R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 309.77' @ 12.27 hrs Surf.Area= 5,904 sf Storage= 3,757 cf

Plug-Flow detention time= 11.9 min calculated for 0.572 af (100% of inflow)
 Center-of-Mass det. time= 10.9 min (777.3 - 766.4)

Volume	Invert	Avail.Storage	Storage Description
#1	308.50'	20,440 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
308.50	0	0	0
310.00	6,960	5,220	5,220
312.00	8,260	15,220	20,440

Device	Routing	Invert	Outlet Devices
#1	Primary	308.50'	12.0" Round Culvert L= 30.0' Ke= 0.500 Inlet / Outlet Invert= 308.50' / 308.10' S= 0.0133 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	311.50'	20.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)

Primary OutFlow Max=3.32 cfs @ 12.27 hrs HW=309.77' (Free Discharge)

1=Culvert (Inlet Controls 3.32 cfs @ 4.23 fps)

2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 5P: EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Inflow Area = 1.630 ac, 20.58% Impervious, Inflow Depth > 3.52" for 25 YEAR event
 Inflow = 5.29 cfs @ 12.13 hrs, Volume= 0.478 af
 Outflow = 3.04 cfs @ 12.36 hrs, Volume= 0.476 af, Atten= 43%, Lag= 14.0 min
 Primary = 3.04 cfs @ 12.36 hrs, Volume= 0.476 af
 Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 326.77' @ 12.36 hrs Surf.Area= 3,969 sf Storage= 3,867 cf

Plug-Flow detention time= 19.2 min calculated for 0.476 af (100% of inflow)
 Center-of-Mass det. time= 16.7 min (840.8 - 824.1)

Volume	Invert	Avail.Storage	Storage Description
#1	325.50'	12,719 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 25 YEAR Rainfall=6.27"

Printed 11/23/2024

Page 9

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
325.50	0	0	0
326.00	3,700	925	925
328.00	4,400	8,100	9,025
328.75	5,450	3,694	12,719

Device	Routing	Invert	Outlet Devices
#1	Primary	325.50'	12.0" Round Culvert L= 38.0' Ke= 0.500 Inlet / Outlet Invert= 325.50' / 325.25' S= 0.0066 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	328.25'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68 2.72 2.81 2.92 2.97 3.07 3.32

Primary OutFlow Max=3.04 cfs @ 12.36 hrs HW=326.77' (Free Discharge)

1=Culvert (Barrel Controls 3.04 cfs @ 3.94 fps)

2=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 7P: EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 3.63" for 25 YEAR event

Inflow = 54.09 cfs @ 12.11 hrs, Volume= 4.188 af

Outflow = 38.15 cfs @ 12.22 hrs, Volume= 4.176 af, Atten= 29%, Lag= 6.3 min

Primary = 38.15 cfs @ 12.22 hrs, Volume= 4.176 af

Routed to Reach 7R : FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Peak Elev= 355.68' @ 12.22 hrs Surf.Area= 16,553 sf Storage= 38,816 cf

Plug-Flow detention time= 32.7 min calculated for 4.169 af (100% of inflow)

Center-of-Mass det. time= 30.9 min (852.1 - 821.2)

Volume	Invert	Avail.Storage	Storage Description
#1	351.00'	44,275 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
351.00	0	0	0
352.00	6,070	3,035	3,035
354.00	8,560	14,630	17,665
356.00	18,050	26,610	44,275

Device	Routing	Invert	Outlet Devices
#1	Primary	351.00'	12.0" Round Culvert L= 60.0' Ke= 0.500 Inlet / Outlet Invert= 351.00' / 349.00' S= 0.0333 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	355.00'	20.0' long x 4.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00

2.50 3.00 3.50 4.00 4.50 5.00 5.50
 Coef. (English) 2.38 2.54 2.69 2.68 2.67 2.67 2.65 2.66 2.66
 2.68 2.72 2.73 2.76 2.79 2.88 3.07 3.32

Primary OutFlow Max=37.43 cfs @ 12.22 hrs HW=355.67' (Free Discharge)

1=Culvert (Inlet Controls 7.73 cfs @ 9.84 fps)

2=Broad-Crested Rectangular Weir (Weir Controls 29.70 cfs @ 2.20 fps)

Summary for Pond 8P: DET BASIN ON EAGLE LEASING

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 4.12" for 25 YEAR event

Inflow = 23.50 cfs @ 12.17 hrs, Volume= 2.071 af

Outflow = 7.31 cfs @ 12.58 hrs, Volume= 2.070 af, Atten= 69%, Lag= 24.4 min

Primary = 7.31 cfs @ 12.58 hrs, Volume= 2.070 af

Routed to Reach 8R : FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Peak Elev= 346.74' @ 12.58 hrs Surf.Area= 15,568 sf Storage= 21,543 cf

Plug-Flow detention time= 18.9 min calculated for 2.067 af (100% of inflow)

Center-of-Mass det. time= 18.7 min (833.1 - 814.4)

Volume	Invert	Avail.Storage	Storage Description
#1	342.50'	46,903 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
342.50	0	0	0
344.00	1,030	773	773
346.00	10,200	11,230	12,003
348.00	24,700	34,900	46,903

Device	Routing	Invert	Outlet Devices
#1	Primary	342.50'	12.0" Round Culvert L= 33.0' Ke= 0.500 Inlet / Outlet Invert= 342.50' / 342.10' S= 0.0121 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	347.00'	12.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 4.5' Crest Height

Primary OutFlow Max=7.31 cfs @ 12.58 hrs HW=346.74' (Free Discharge)

1=Culvert (Inlet Controls 7.31 cfs @ 9.31 fps)

2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

POSTDEVELOPMENT

Summary for Subcatchment 11S: POSTDEV FLOW FROM PARKING AREA

Runoff = 6.03 cfs @ 12.08 hrs, Volume= 0.490 af, Depth> 5.91"
 Routed to Pond 23P : INFILTRATION BASIN WITH 76 R902s

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
41,985	98	Paved parking, HSG B
280	74	>75% Grass cover, Good, HSG C
1,049	61	>75% Grass cover, Good, HSG B

43,314	97	Weighted Average
1,329		3.07% Pervious Area
41,985		96.93% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
6.0	Direct Entry,				

Summary for Subcatchment 12S: POSTDEV OVERLAND FLOW TO DETENTION BASIN

Runoff = 1.92 cfs @ 12.16 hrs, Volume= 0.162 af, Depth> 3.41"
 Routed to Pond 11P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
2,913	98	Water Surface, HSG B
12,916	70	Woods, Good, HSG C
189	55	Woods, Good, HSG B
7,152	74	>75% Grass cover, Good, HSG C
1,644	61	>75% Grass cover, Good, HSG B

24,814	74	Weighted Average
21,901		88.26% Pervious Area
2,913		11.74% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
10.5	50	0.0300	0.08	Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"	
0.5	58	0.1600	2.00	Shallow Concentrated Flow, Woodland Kv= 5.0 fps	

11.0 108 Total

Summary for Subcatchment 13S: POSTDEV OVERLAND FLOW TO PARKERVILLE ROAD

Runoff = 5.60 cfs @ 12.35 hrs, Volume= 0.650 af, Depth> 2.81"
 Routed to Reach 11R : PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
1,943	55	Woods, Good, HSG B
1,148	98	Roofs, HSG B
1,254	61	>75% Grass cover, Good, HSG B
183	70	Woods, Good, HSG C
1,148	98	Roofs, HSG C
5,275	74	>75% Grass cover, Good, HSG C
22,271	55	Woods, Good, HSG B
789	98	Roofs, HSG B
19,728	61	>75% Grass cover, Good, HSG B
26,543	70	Woods, Good, HSG C
4,032	98	Roofs, HSG C
36,320	74	>75% Grass cover, Good, HSG C
120,634	68	Weighted Average
113,517		94.10% Pervious Area
7,117		5.90% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
9.9	754	0.0640	1.26		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.9	243	0.0370	4.76	57.07	Channel Flow, 2' WIDE BOTTOM, 10:1 SIDE SLOPES,1'DEEP Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
24.6	1,047				Total

Summary for Subcatchment 14S: OVERLAND FLOW TO ROUTE 9

Runoff = 11.20 cfs @ 12.26 hrs, Volume= 1.143 af, Depth> 3.01"
 Routed to Reach 14R : ROUTE 9

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
31,704	70	Woods, Good, HSG C
0	98	Roofs, HSG C
4,306	98	Roofs, HSG C
11,703	74	>75% Grass cover, Good, HSG C
76,405	55	Woods, Good, HSG B
44,135	98	Paved parking, HSG B
30,229	61	>75% Grass cover, Good, HSG B
198,482	70	Weighted Average
150,041		75.59% Pervious Area
48,441		24.41% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.0400	0.13		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
1.1	242	0.0600	3.67		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
9.1	709	0.0680	1.30		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.9	365	0.0160	3.13	37.53	Channel Flow, Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
18.3	1,366				Total

Summary for Subcatchment 15S: DRAINAGE COLLECTED BY CB'S SW OF SELF STORAGE BUILDING

Runoff = 2.54 cfs @ 12.09 hrs, Volume= 0.185 af, Depth> 4.45"
 Routed to Pond 15P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
6,345	61	>75% Grass cover, Good, HSG B
3,301	74	>75% Grass cover, Good, HSG C
6,254	98	Paved parking, HSG B
5,860	98	Paved parking, HSG C
21,760	84	Weighted Average
9,646		44.33% Pervious Area
12,114		55.67% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 16S: OVERLAND FLOW TO EXISTING DETENTION BASIN

Runoff = 3.31 cfs @ 12.18 hrs, Volume= 0.293 af, Depth> 3.11"
 Routed to Pond 15P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
46,762	70	Woods, Good, HSG C
2,500	98	Water Surface, HSG C

49,262	71	Weighted Average
46,762		94.93% Pervious Area
2,500		5.07% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	50	0.0450	0.09		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
3.8	324	0.0800	1.41		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
12.7	374	Total			

Summary for Subcatchment 17S: RUNOFF COLLECTED BY SARSEN STONE WAY

Runoff = 42.58 cfs @ 12.12 hrs, Volume= 3.317 af, Depth> 3.92"
 Routed to Pond 17P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
317,393	84	1 acre lots, 20% imp, HSG D
125,360	68	1 acre lots, 20% imp, HSG B

442,753	79	Weighted Average
354,202		80.00% Pervious Area
88,551		20.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
2.0	214	0.1300	1.80		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.6	175	0.1000	4.74		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
0.5	210	0.1000	6.42		Shallow Concentrated Flow, Paved Kv= 20.3 fps
8.4	649	Total			

Summary for Subcatchment 18S: POSTDEV FLOW ON EAGLE LEASING

Runoff = 23.50 cfs @ 12.17 hrs, Volume= 2.071 af, Depth> 4.12"
 Routed to Pond 18P : DET BASIN ON EAGLE LEASING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
24,658	98	Paved parking, HSG B
8,220	61	>75% Grass cover, Good, HSG B
104,681	98	Paved parking, HSG C
34,894	74	>75% Grass cover, Good, HSG C
235	98	Paved parking, HSG D
6,197	80	>75% Grass cover, Good, HSG D
30,530	61	>75% Grass cover, Good, HSG B
5,140	98	Paved parking, HSG B
48,076	55	Woods, Good, HSG B
262,631	81	Weighted Average
127,917		48.71% Pervious Area
134,714		51.29% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
4.2	413	0.1100	1.66		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
2.9	360	0.0440	2.10		Shallow Concentrated Flow, Nearly Bare & Untilled Kv= 10.0 fps
12.4	823	Total			

Summary for Subcatchment 19S: OVERLAND FLOW TO DET BASIN BEHIND 5 & 7 SARSEN STONE

Runoff = 12.06 cfs @ 12.09 hrs, Volume= 0.871 af, Depth> 2.83"
 Routed to Pond 17P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
20,407	70	Woods, Good, HSG C
3,300	98	Water Surface, HSG B
36,775	55	Woods, Good, HSG B
13,560	85	1/2 acre lots, 25% imp, HSG D
87,016	70	1/2 acre lots, 25% imp, HSG B
161,058	68	Weighted Average
132,614		82.34% Pervious Area
28,444		17.66% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0	Direct Entry,				

Summary for Subcatchment 25S: AREA CAPTURED IN MAIN DRIVE

Runoff = 6.99 cfs @ 12.22 hrs, Volume= 0.694 af, Depth> 4.76"
 Routed to Pond 24P : INFILTRATION STRUCTURE UNDER PARKING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
37,506	98	Paved parking, HSG C
11,007	98	Paved parking, HSG B
8,588	61	>75% Grass cover, Good, HSG B
16,641	74	>75% Grass cover, Good, HSG C
2,422	55	Woods, Good, HSG B
76,164	87	Weighted Average
27,651		36.30% Pervious Area
48,513		63.70% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06	Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"	
0.5	55	0.1400	1.87	Shallow Concentrated Flow, Woodland Kv= 5.0 fps	
1.0	79	0.0380	1.36	Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps	
0.9	167	0.0240	3.14	Shallow Concentrated Flow, Paved Kv= 20.3 fps	
16.2	351	Total			

Summary for Subcatchment 26S: DRIVEWAY AND 5 UNITS AT ENTRANCE

Runoff = 1.59 cfs @ 12.19 hrs, Volume= 0.156 af, Depth> 5.21"
 Routed to Reach 26R : FLOW PATH FROM OUTLET TO PARKERVILLE

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
4,449	74	>75% Grass cover, Good, HSG C
11,225	98	Paved parking, HSG C
15,674	91	Weighted Average
4,449		28.38% Pervious Area
11,225		71.62% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
14.3	50	0.0050	0.06		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
0.3	19	0.0050	1.06		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
14.6	69	Total			

Summary for Subcatchment 27S: BACK HALF OF ROOFS UNITS 9-11

Runoff = 0.22 cfs @ 12.07 hrs, Volume= 0.017 af, Depth> 6.03"
 Routed to Pond 27P : INFILTRATION STRUCTURE FOR 9-11

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
1,512	98	Roofs, HSG C
1,512		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 28S: BACK HALF OF ROOFS UNITS 22-24

Runoff = 0.22 cfs @ 12.07 hrs, Volume= 0.017 af, Depth> 6.03"
 Routed to Pond 28P : INFILTRATION STRUCTURE FOR 22-24

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description
1,512	98	Roofs, HSG C
1,512		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 29S: ROOFS FROM 20,21,26-29

Runoff = 0.58 cfs @ 12.07 hrs, Volume= 0.047 af, Depth> 6.03"
 Routed to Pond 29P : INFILTRATION STRUCTURE FOR 20-21 & 26-29

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 25 YEAR Rainfall=6.27"

Area (sf)	CN	Description			
4,032	98	Roofs, HSG C			
4,032		100.00% Impervious Area			
Tc	Length (min)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Reach 11R: PARKERVILLE ROAD

Inflow Area = 6.442 ac, 39.83% Impervious, Inflow Depth > 2.63" for 25 YEAR event
 Inflow = 9.58 cfs @ 12.34 hrs, Volume= 1.414 af
 Outflow = 9.58 cfs @ 12.34 hrs, Volume= 1.414 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 14R: ROUTE 9

Inflow Area = 26.078 ac, 27.71% Impervious, Inflow Depth > 3.62" for 25 YEAR event
 Inflow = 57.74 cfs @ 12.29 hrs, Volume= 7.857 af
 Outflow = 57.74 cfs @ 12.29 hrs, Volume= 7.857 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 17R: FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 3.62" for 25 YEAR event
 Inflow = 38.15 cfs @ 12.22 hrs, Volume= 4.176 af
 Outflow = 37.57 cfs @ 12.26 hrs, Volume= 4.172 af, Atten= 2%, Lag= 2.2 min
 Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Max. Velocity= 6.51 fps, Min. Travel Time= 1.0 min
 Avg. Velocity = 2.77 fps, Avg. Travel Time= 2.4 min

Peak Storage= 2,298 cf @ 12.24 hrs
 Average Depth at Peak Storage= 0.98', Surface Width= 9.83'
 Bank-Full Depth= 2.00' Flow Area= 20.0 sf, Capacity= 198.41 cfs

2.00' x 2.00' deep channel, n= 0.040 Earth, cobble bottom, clean sides
 Side Slope Z-value= 4.0 '/' Top Width= 18.00'
 Length= 397.0' Slope= 0.0642 '/'
 Inlet Invert= 349.00', Outlet Invert= 323.50'


Summary for Reach 18R: FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 4.12" for 25 YEAR event
Inflow = 7.31 cfs @ 12.58 hrs, Volume= 2.070 af
Outflow = 7.31 cfs @ 12.59 hrs, Volume= 2.070 af, Atten= 0%, Lag= 0.6 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 7.74 fps, Min. Travel Time= 0.3 min
Avg. Velocity = 4.17 fps, Avg. Travel Time= 0.6 min

Peak Storage= 148 cf @ 12.58 hrs
Average Depth at Peak Storage= 0.42', Surface Width= 3.51'
Bank-Full Depth= 2.00' Flow Area= 14.0 sf, Capacity= 271.03 cfs

1.00' x 2.00' deep channel, n= 0.025 Earth, clean & winding
Side Slope Z-value= 3.0 '/' Top Width= 13.00'
Length= 157.0' Slope= 0.1025 '/'
Inlet Invert= 342.10', Outlet Invert= 326.00'



Summary for Reach 22R: FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Inflow Area = 21.521 ac, 28.41% Impervious, Inflow Depth > 3.75" for 25 YEAR event
Inflow = 47.36 cfs @ 12.26 hrs, Volume= 6.719 af
Outflow = 46.70 cfs @ 12.29 hrs, Volume= 6.714 af, Atten= 1%, Lag= 2.0 min
Routed to Reach 14R : ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 7.75 fps, Min. Travel Time= 0.8 min
Avg. Velocity = 3.41 fps, Avg. Travel Time= 1.9 min

Peak Storage= 2,319 cf @ 12.27 hrs
Average Depth at Peak Storage= 0.64', Surface Width= 15.85'
Bank-Full Depth= 2.00' Flow Area= 46.0 sf, Capacity= 707.92 cfs

3.00' x 2.00' deep channel, n= 0.030 Earth, grassed & winding
Side Slope Z-value= 10.0 '/' Top Width= 43.00'
Length= 383.0' Slope= 0.0888 '/'
Inlet Invert= 349.00', Outlet Invert= 315.00'

‡

Summary for Reach 26R: FLOW PATH FROM OUTLET TO PARKERVILLE

Inflow Area = 2.108 ac, 65.05% Impervious, Inflow Depth > 3.13" for 25 YEAR event
Inflow = 2.70 cfs @ 12.24 hrs, Volume= 0.549 af
Outflow = 2.68 cfs @ 12.31 hrs, Volume= 0.549 af, Atten= 1%, Lag= 4.2 min
Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 2.68 fps, Min. Travel Time= 2.2 min
Avg. Velocity = 1.00 fps, Avg. Travel Time= 6.0 min

Peak Storage= 360 cf @ 12.27 hrs
Average Depth at Peak Storage= 0.12', Surface Width= 10.77'
Bank-Full Depth= 1.00' Flow Area= 26.0 sf, Capacity= 232.32 cfs

6.00' x 1.00' deep channel, n= 0.022 Earth, clean & straight
Side Slope Z-value= 20.0 ' Top Width= 46.00'
Length= 360.0' Slope= 0.0375 '
Inlet Invert= 318.00', Outlet Invert= 304.50'

‡

Summary for Pond 11P: EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Inflow Area = 1.564 ac, 65.90% Impervious, Inflow Depth > 1.24" for 25 YEAR event
Inflow = 1.92 cfs @ 12.16 hrs, Volume= 0.162 af
Outflow = 1.35 cfs @ 12.29 hrs, Volume= 0.161 af, Atten= 30%, Lag= 7.9 min
Primary = 1.35 cfs @ 12.29 hrs, Volume= 0.161 af
Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Peak Elev= 309.11' @ 12.29 hrs Surf.Area= 2,846 sf Storage= 873 cf

Plug-Flow detention time= 9.6 min calculated for 0.161 af (100% of inflow)
Center-of-Mass det. time= 8.4 min (838.6 - 830.2)

Volume	Invert	Avail.Storage	Storage Description
#1	308.50'	20,440 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
308.50	0	0	0
310.00	6,960	5,220	5,220
312.00	8,260	15,220	20,440

Device	Routing	Invert	Outlet Devices
#1	Primary	308.50'	12.0" Round Culvert L= 30.0' Ke= 0.500 Inlet / Outlet Invert= 308.50' / 308.10' S= 0.0133 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	311.50'	20.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)

Primary OutFlow Max=1.34 cfs @ 12.29 hrs HW=309.11' (Free Discharge)

1=Culvert (Inlet Controls 1.34 cfs @ 2.66 fps)
 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 15P: EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Inflow Area = 1.630 ac, 20.58% Impervious, Inflow Depth > 3.52" for 25 YEAR event
 Inflow = 5.29 cfs @ 12.13 hrs, Volume= 0.478 af
 Outflow = 3.04 cfs @ 12.36 hrs, Volume= 0.476 af, Atten= 43%, Lag= 14.0 min
 Primary = 3.04 cfs @ 12.36 hrs, Volume= 0.476 af

Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 326.77' @ 12.36 hrs Surf.Area= 3,969 sf Storage= 3,867 cf

Plug-Flow detention time= 19.2 min calculated for 0.476 af (100% of inflow)
 Center-of-Mass det. time= 16.7 min (840.8 - 824.1)

Volume	Invert	Avail.Storage	Storage Description
#1	325.50'	12,719 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
325.50	0	0	0
326.00	3,700	925	925
328.00	4,400	8,100	9,025
328.75	5,450	3,694	12,719

Device	Routing	Invert	Outlet Devices
#1	Primary	325.50'	12.0" Round Culvert L= 38.0' Ke= 0.500 Inlet / Outlet Invert= 325.50' / 325.25' S= 0.0066 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	328.25'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68

2.72 2.81 2.92 2.97 3.07 3.32

Primary OutFlow Max=3.04 cfs @ 12.36 hrs HW=326.77' (Free Discharge)
 1=Culvert (Barrel Controls 3.04 cfs @ 3.94 fps)
 2=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 17P: EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 3.63" for 25 YEAR event
 Inflow = 54.09 cfs @ 12.11 hrs, Volume= 4.188 af
 Outflow = 38.15 cfs @ 12.22 hrs, Volume= 4.176 af, Atten= 29%, Lag= 6.3 min
 Primary = 38.15 cfs @ 12.22 hrs, Volume= 4.176 af
 Routed to Reach 17R : FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 355.68' @ 12.22 hrs Surf.Area= 16,553 sf Storage= 38,816 cf

Plug-Flow detention time= 32.7 min calculated for 4.169 af (100% of inflow)
 Center-of-Mass det. time= 30.9 min (852.1 - 821.2)

Volume	Invert	Avail.Storage	Storage Description
#1	351.00'	44,275 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
351.00	0	0	0
352.00	6,070	3,035	3,035
354.00	8,560	14,630	17,665
356.00	18,050	26,610	44,275

Device	Routing	Invert	Outlet Devices
#1	Primary	351.00'	12.0" Round Culvert L= 60.0' Ke= 0.500 Inlet / Outlet Invert= 351.00' / 349.00' S= 0.0333 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	355.00'	20.0' long x 4.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.38 2.54 2.69 2.68 2.67 2.67 2.65 2.66 2.66 2.68 2.72 2.73 2.76 2.79 2.88 3.07 3.32

Primary OutFlow Max=37.43 cfs @ 12.22 hrs HW=355.67' (Free Discharge)
 1=Culvert (Inlet Controls 7.73 cfs @ 9.84 fps)
 2=Broad-Crested Rectangular Weir (Weir Controls 29.70 cfs @ 2.20 fps)

Summary for Pond 18P: DET BASIN ON EAGLE LEASING

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 4.12" for 25 YEAR event
 Inflow = 23.50 cfs @ 12.17 hrs, Volume= 2.071 af
 Outflow = 7.31 cfs @ 12.58 hrs, Volume= 2.070 af, Atten= 69%, Lag= 24.4 min
 Primary = 7.31 cfs @ 12.58 hrs, Volume= 2.070 af
 Routed to Reach 18R : FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 346.74' @ 12.58 hrs Surf.Area= 15,568 sf Storage= 21,543 cf

Plug-Flow detention time= 18.9 min calculated for 2.067 af (100% of inflow)
 Center-of-Mass det. time= 18.7 min (833.1 - 814.4)

Volume	Invert	Avail.Storage	Storage Description
#1	342.50'	46,903 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
342.50	0	0	0
344.00	1,030	773	773
346.00	10,200	11,230	12,003
348.00	24,700	34,900	46,903

Device	Routing	Invert	Outlet Devices
#1	Primary	342.50'	12.0" Round Culvert L= 33.0' Ke= 0.500 Inlet / Outlet Invert= 342.50' / 342.10' S= 0.0121 ' / Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	347.00'	12.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 4.5' Crest Height

Primary OutFlow Max=7.31 cfs @ 12.58 hrs HW=346.74' (Free Discharge)

1=Culvert (Inlet Controls 7.31 cfs @ 9.31 fps)
 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 23P: INFILTRATION BASIN WITH 76 R902s

Inflow Area = 0.994 ac, 96.93% Impervious, Inflow Depth > 5.91" for 25 YEAR event
 Inflow = 6.03 cfs @ 12.08 hrs, Volume= 0.490 af
 Outflow = 0.55 cfs @ 12.93 hrs, Volume= 0.302 af, Atten= 91%, Lag= 50.8 min
 Discarded = 0.23 cfs @ 9.84 hrs, Volume= 0.248 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af
 Routed to Pond 11P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD
 Secondary = 0.41 cfs @ 12.93 hrs, Volume= 0.054 af
 Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 307.94' @ 12.93 hrs Surf.Area= 2,450 sf Storage= 10,261 cf

Plug-Flow detention time= 213.5 min calculated for 0.302 af (62% of inflow)
 Center-of-Mass det. time= 107.8 min (858.7 - 750.9)

Volume	Invert	Avail.Storage	Storage Description
#1	302.50'	8,272 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 20,681 cf Overall x 40.0% Voids
#2	303.00'	4,966 cf	Cultec R-902HD v2 x 76 Effective Size= 69.1"W x 48.0"H => 17.30 sf x 3.67'L = 63.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap

76 Chambers in 4 Rows
 Cap Storage= 18.0 cf x 2 x 4 rows = 144.2 cf
 13,238 cf Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
302.50	2,433	0	0
311.00	2,433	20,681	20,681

Device	Routing	Invert	Outlet Devices
#1	Discarded	302.50'	2.410 in/hr Exfiltration over Surface area
#2	Primary	310.00'	10.0" Round Culvert L= 51.0' Ke= 0.500 Inlet / Outlet Invert= 310.00' / 309.50' S= 0.0098 ' / Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.55 sf
#3	Secondary	307.50'	6.0" Round Culvert L= 86.0' Ke= 0.500 Inlet / Outlet Invert= 307.50' / 306.25' S= 0.0145 ' / Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.23 cfs @ 9.84 hrs HW=303.00' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.23 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=302.50' (Free Discharge)
 ↑2=Culvert (Controls 0.00 cfs)

Secondary OutFlow Max=0.41 cfs @ 12.93 hrs HW=307.94' (Free Discharge)
 ↑3=Culvert (Inlet Controls 0.41 cfs @ 2.26 fps)

Summary for Pond 24P: INFILTRATION STRUCTURE UNDER PARKING

Inflow Area = 1.748 ac, 63.70% Impervious, Inflow Depth > 4.76" for 25 YEAR event
 Inflow = 6.99 cfs @ 12.22 hrs, Volume= 0.694 af
 Outflow = 1.85 cfs @ 12.71 hrs, Volume= 0.641 af, Atten= 74%, Lag= 29.4 min
 Discarded = 0.18 cfs @ 9.20 hrs, Volume= 0.247 af
 Primary = 1.66 cfs @ 12.71 hrs, Volume= 0.393 af

Routed to Reach 26R : FLOW PATH FROM OUTLET TO PARKERVILLE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 325.35' @ 12.71 hrs Surf.Area= 3,284 sf Storage= 12,048 cf

Plug-Flow detention time= 116.6 min calculated for 0.639 af (92% of inflow)
 Center-of-Mass det. time= 77.5 min (878.5 - 800.9)

Volume	Invert	Avail.Storage	Storage Description
#1	320.50'	3,836 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 26,272 cf Overall - 16,683 cf Embedded = 9,589 cf x 40.0% Voids
#2	321.00'	12,422 cf	retain_it retain_it 5.0' x 46 Inside #1 Inside= 84.0"W x 60.0"H => 36.41 sf x 8.00'L = 291.3 cf Outside= 96.0"W x 68.0"H => 45.33 sf x 8.00'L = 362.7 cf 1 Rows adjusted for 976.7 cf perimeter wall
		16,258 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
320.50	3,284	0	0
328.50	3,284	26,272	26,272

Device	Routing	Invert	Outlet Devices
#1	Discarded	320.50'	2.410 in/hr Exfiltration over Surface area
#2	Primary	326.70'	8.0" Round Culvert L= 18.0' Ke= 0.500 Inlet / Outlet Invert= 326.70' / 319.00' S= 0.4278 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf
#3	Primary	322.00'	6.0" Round Culvert L= 18.0' Ke= 0.500 Inlet / Outlet Invert= 322.00' / 320.00' S= 0.1111 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.18 cfs @ 9.20 hrs HW=320.58' (Free Discharge)

1=Exfiltration (Exfiltration Controls 0.18 cfs)

Primary OutFlow Max=1.66 cfs @ 12.71 hrs HW=325.35' (Free Discharge)

2=Culvert (Controls 0.00 cfs)

3=Culvert (Inlet Controls 1.66 cfs @ 8.47 fps)

Summary for Pond 27P: INFILTRATION STRUCTURE FOR 9-11

Inflow Area = 0.035 ac, 100.00% Impervious, Inflow Depth > 6.03" for 25 YEAR event
 Inflow = 0.22 cfs @ 12.07 hrs, Volume= 0.017 af
 Outflow = 0.01 cfs @ 8.72 hrs, Volume= 0.010 af, Atten= 97%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 8.72 hrs, Volume= 0.010 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Peak Elev= 339.65' @ 15.81 hrs Surf.Area= 270 sf Storage= 427 cf

Plug-Flow detention time= 250.8 min calculated for 0.010 af (56% of inflow)

Center-of-Mass det. time= 131.8 min (875.0 - 743.2)

Volume	Invert	Avail.Storage	Storage Description
#1	337.00'	291 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 1,350 cf Overall - 623 cf Embedded = 727 cf x 40.0% Voids
#2	337.50'	464 cf	Shea Dry Well 300gal x 10 Inside #1 Inside= 42.2"W x 45.0"H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0"W x 51.0"H => 15.58 sf x 4.00'L = 62.3 cf 10 Chambers in 2 Rows
		754 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
337.00	270	0	0
342.00	270	1,350	1,350

Device	Routing	Invert	Outlet Devices
#1	Discarded	337.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 8.72 hrs HW=337.05' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.01 cfs)

Summary for Pond 28P: INFILTRATION STRUCTURE FOR 22-24

Inflow Area = 0.035 ac, 100.00% Impervious, Inflow Depth > 6.03" for 25 YEAR event
 Inflow = 0.22 cfs @ 12.07 hrs, Volume= 0.017 af
 Outflow = 0.01 cfs @ 8.72 hrs, Volume= 0.010 af, Atten= 97%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 8.72 hrs, Volume= 0.010 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 334.65' @ 15.81 hrs Surf.Area= 270 sf Storage= 427 cf

Plug-Flow detention time= 250.8 min calculated for 0.010 af (56% of inflow)
 Center-of-Mass det. time= 131.8 min (875.0 - 743.2)

Volume	Invert	Avail.Storage	Storage Description
#1	332.00'	291 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 1,350 cf Overall - 623 cf Embedded = 727 cf x 40.0% Voids
#2	332.50'	464 cf	Shea Dry Well 300gal x 10 Inside #1 Inside= 42.2"W x 45.0"H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0"W x 51.0"H => 15.58 sf x 4.00'L = 62.3 cf 10 Chambers in 2 Rows
			754 cf Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
332.00	270	0	0
337.00	270	1,350	1,350

Device	Routing	Invert	Outlet Devices
#1	Discarded	332.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 8.72 hrs HW=332.05' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.01 cfs)

Summary for Pond 29P: INFILTRATION STRUCTURE FOR 20-21 & 26-29

Inflow Area = 0.093 ac, 100.00% Impervious, Inflow Depth > 6.03" for 25 YEAR event
 Inflow = 0.58 cfs @ 12.07 hrs, Volume= 0.047 af
 Outflow = 0.01 cfs @ 8.20 hrs, Volume= 0.022 af, Atten= 98%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 8.20 hrs, Volume= 0.022 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 330.33' @ 16.52 hrs Surf.Area= 589 sf Storage= 1,226 cf

Plug-Flow detention time= 251.6 min calculated for 0.022 af (47% of inflow)
 Center-of-Mass det. time= 114.6 min (857.8 - 743.2)

Volume	Invert	Avail.Storage	Storage Description
#1	327.00'	697 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 3,240 cf Overall - 1,496 cf Embedded = 1,744 cf x 40.0% Voids
#2	327.50'	1,113 cf	Shea Dry Well 300gal x 24 Inside #1 Inside= 42.2" W x 45.0" H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0" W x 51.0" H => 15.58 sf x 4.00'L = 62.3 cf 24 Chambers in 4 Rows
1,811 cf			Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
327.00	589	0	0
332.50	589	3,240	3,240

Device	Routing	Invert	Outlet Devices
#1	Discarded	327.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 8.20 hrs HW=327.06' (Free Discharge)
↑1=Exfiltration (Exfiltration Controls 0.01 cfs)

100 YEAR STORM

PREDEVELOPMENT

Summary for Subcatchment 1S: PREDEV FLOW FROM PARKING AREA

Runoff = 7.73 cfs @ 12.08 hrs, Volume= 0.634 af, Depth> 7.65"
 Routed to Pond 1P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
41,985	98	Paved parking, HSG B
280	74	>75% Grass cover, Good, HSG C
1,049	61	>75% Grass cover, Good, HSG B
43,314	97	Weighted Average
1,329		3.07% Pervious Area
41,985		96.93% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 2S: PREDEV OVERLAND FLOW TO DETENTION BASIN

Runoff = 1.52 cfs @ 12.16 hrs, Volume= 0.130 af, Depth> 3.56"
 Routed to Pond 1P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
2,913	98	Water Surface, HSG B
1,161	70	Woods, Good, HSG C
14,991	55	Woods, Good, HSG B
19,065	62	Weighted Average
16,152		84.72% Pervious Area
2,913		15.28% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	50	0.0300	0.08		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
0.5	58	0.1600	2.00		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
11.0	108				Total

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 100 YEAR Rainfall=8.01"

Printed 11/23/2024

Page 2

Summary for Subcatchment 3S: PREDEV OVERLAND FLOW TO PARKERVILLE ROAD

Runoff = 14.51 cfs @ 12.35 hrs, Volume= 1.673 af, Depth> 3.88"
 Routed to Reach 1R : PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
144,569	70	Woods, Good, HSG C
63,690	55	Woods, Good, HSG B
16,200	61	>75% Grass cover, Good, HSG B
780	98	Roofs, HSG B

225,239	65	Weighted Average
224,459		99.65% Pervious Area
780		0.35% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
9.9	754	0.0640	1.26		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.9	243	0.0370	4.76	57.07	Channel Flow, 2' WIDE BOTTOM, 10:1 SIDE SLOPES,1'DEEP Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
24.6	1,047				Total

Summary for Subcatchment 4S: OVERLAND FLOW TO ROUTE 9

Runoff = 16.69 cfs @ 12.25 hrs, Volume= 1.693 af, Depth> 4.46"
 Routed to Reach 4R : ROUTE 9

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
54,059	55	Woods, Good, HSG B
24,068	55	Woods, Good, HSG B
36,060	70	Woods, Good, HSG C
33,500	61	>75% Grass cover, Good, HSG B
1,900	74	>75% Grass cover, Good, HSG C
42,307	98	Paved parking, HSG B
2,250	98	Paved parking, HSG B
4,349	98	Paved parking, HSG C
198,493	70	Weighted Average
149,587		75.36% Pervious Area
48,906		24.64% Impervious Area

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 100 YEAR Rainfall=8.01"

Printed 11/23/2024

Page 3

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.0400	0.13		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
1.1	242	0.0600	3.67		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
9.1	709	0.0680	1.30		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.9	365	0.0160	3.13	37.53	Channel Flow, Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
18.3	1,366				Total

Summary for Subcatchment 5S: DRAINAGE COLLECTED BY CB'S SW OF SELF STORAGE BUILDING

Runoff = 3.43 cfs @ 12.09 hrs, Volume= 0.254 af, Depth> 6.10"
 Routed to Pond 5P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
6,345	61	>75% Grass cover, Good, HSG B
3,301	74	>75% Grass cover, Good, HSG C
6,254	98	Paved parking, HSG B
5,860	98	Paved parking, HSG C
21,760	84	Weighted Average
9,646		44.33% Pervious Area
12,114		55.67% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 6S: OVERLAND FLOW TO EXISTING DETENTION BASIN

Runoff = 4.88 cfs @ 12.18 hrs, Volume= 0.431 af, Depth> 4.58"
 Routed to Pond 5P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
46,762	70	Woods, Good, HSG C
2,500	98	Water Surface, HSG C
49,262	71	Weighted Average
46,762		94.93% Pervious Area
2,500		5.07% Impervious Area

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 100 YEAR Rainfall=8.01"

Printed 11/23/2024

Page 4

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	50	0.0450	0.09		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
3.8	324	0.0800	1.41		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
12.7	374	Total			

Summary for Subcatchment 7S: RUNOFF COLLECTED BY SARSEN STONE WAY

Runoff = 59.36 cfs @ 12.12 hrs, Volume= 4.667 af, Depth> 5.51"
 Routed to Pond 7P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
317,393	84	1 acre lots, 20% imp, HSG D
125,360	68	1 acre lots, 20% imp, HSG B
442,753	79	Weighted Average
354,202		80.00% Pervious Area
88,551		20.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
2.0	214	0.1300	1.80		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.6	175	0.1000	4.74		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
0.5	210	0.1000	6.42		Shallow Concentrated Flow, Paved Kv= 20.3 fps
8.4	649	Total			

Summary for Subcatchment 8S: PREDEV FLOW ON EAGLE LEASING

Runoff = 32.38 cfs @ 12.17 hrs, Volume= 2.884 af, Depth> 5.74"
 Routed to Pond 8P : DET BASIN ON EAGLE LEASING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 100 YEAR Rainfall=8.01"

Printed 11/23/2024

Page 5

Area (sf)	CN	Description			
24,658	98	Paved parking, HSG B			
8,220	61	>75% Grass cover, Good, HSG B			
104,681	98	Paved parking, HSG C			
34,894	74	>75% Grass cover, Good, HSG C			
235	98	Paved parking, HSG D			
6,197	80	>75% Grass cover, Good, HSG D			
30,530	61	>75% Grass cover, Good, HSG B			
5,140	98	Paved parking, HSG B			
48,076	55	Woods, Good, HSG B			
262,631	81	Weighted Average			
127,917		48.71% Pervious Area			
134,714		51.29% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
4.2	413	0.1100	1.66		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
2.9	360	0.0440	2.10		Shallow Concentrated Flow, Nearly Bare & Untilled Kv= 10.0 fps
12.4	823				Total

Summary for Subcatchment 9S: OVERLAND FLOW TO DET BASIN BEHIND 5 & 7 SARSEN STONE

Runoff = 18.23 cfs @ 12.09 hrs, Volume= 1.306 af, Depth> 4.24"

Routed to Pond 7P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description			
20,407	70	Woods, Good, HSG C			
3,300	98	Water Surface, HSG B			
36,775	55	Woods, Good, HSG B			
13,560	85	1/2 acre lots, 25% imp, HSG D			
87,016	70	1/2 acre lots, 25% imp, HSG B			
161,058	68	Weighted Average			
132,614		82.34% Pervious Area			
28,444		17.66% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
6.0					Direct Entry,

Summary for Reach 1R: PARKERVILLE ROAD

Inflow Area = 6.603 ac, 15.88% Impervious, Inflow Depth > 4.42" for 100 YEAR event
Inflow = 18.40 cfs @ 12.35 hrs, Volume= 2.435 af
Outflow = 18.40 cfs @ 12.35 hrs, Volume= 2.435 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 4R: ROUTE 9

Inflow Area = 26.078 ac, 27.75% Impervious, Inflow Depth > 5.16" for 100 YEAR event
Inflow = 92.67 cfs @ 12.22 hrs, Volume= 11.205 af
Outflow = 92.67 cfs @ 12.22 hrs, Volume= 11.205 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 7R: FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 5.16" for 100 YEAR event
Inflow = 74.33 cfs @ 12.16 hrs, Volume= 5.957 af
Outflow = 67.27 cfs @ 12.19 hrs, Volume= 5.952 af, Atten= 10%, Lag= 1.9 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 7.61 fps, Min. Travel Time= 0.9 min
Avg. Velocity = 2.97 fps, Avg. Travel Time= 2.2 min

Peak Storage= 3,662 cf @ 12.17 hrs
Average Depth at Peak Storage= 1.29', Surface Width= 12.32'
Bank-Full Depth= 2.00' Flow Area= 20.0 sf, Capacity= 198.41 cfs

2.00' x 2.00' deep channel, n= 0.040 Earth, cobble bottom, clean sides
Side Slope Z-value= 4.0 '/' Top Width= 18.00'
Length= 397.0' Slope= 0.0642 '/'
Inlet Invert= 349.00', Outlet Invert= 323.50'

‡

Summary for Reach 8R: FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 5.74" for 100 YEAR event
Inflow = 13.68 cfs @ 12.48 hrs, Volume= 2.883 af
Outflow = 13.65 cfs @ 12.49 hrs, Volume= 2.883 af, Atten= 0%, Lag= 0.6 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Max. Velocity= 9.10 fps, Min. Travel Time= 0.3 min

Avg. Velocity = 4.50 fps, Avg. Travel Time= 0.6 min

Peak Storage= 236 cf @ 12.49 hrs

Average Depth at Peak Storage= 0.56', Surface Width= 4.36'


Bank-Full Depth= 2.00' Flow Area= 14.0 sf, Capacity= 271.03 cfs

1.00' x 2.00' deep channel, n= 0.025 Earth, clean & winding

Side Slope Z-value= 3.0 '/' Top Width= 13.00'

Length= 157.0' Slope= 0.1025 '/'

Inlet Invert= 342.10', Outlet Invert= 326.00'



Summary for Reach 22R: FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Inflow Area = 21.521 ac, 28.41% Impervious, Inflow Depth > 5.31" for 100 YEAR event

Inflow = 77.89 cfs @ 12.19 hrs, Volume= 9.518 af

Outflow = 76.38 cfs @ 12.22 hrs, Volume= 9.512 af, Atten= 2%, Lag= 1.3 min

Routed to Reach 4R : ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Max. Velocity= 8.82 fps, Min. Travel Time= 0.7 min

Avg. Velocity = 3.69 fps, Avg. Travel Time= 1.7 min

Peak Storage= 3,385 cf @ 12.20 hrs

Average Depth at Peak Storage= 0.80', Surface Width= 19.04'


Bank-Full Depth= 2.00' Flow Area= 46.0 sf, Capacity= 707.92 cfs

3.00' x 2.00' deep channel, n= 0.030 Earth, grassed & winding

Side Slope Z-value= 10.0 '/' Top Width= 43.00'

Length= 383.0' Slope= 0.0888 '/'

Inlet Invert= 349.00', Outlet Invert= 315.00'



‡

Summary for Pond 1P: EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Inflow Area = 1.432 ac, 71.98% Impervious, Inflow Depth > 6.40" for 100 YEAR event
 Inflow = 8.95 cfs @ 12.09 hrs, Volume= 0.763 af
 Outflow = 3.89 cfs @ 12.32 hrs, Volume= 0.762 af, Atten= 57%, Lag= 13.9 min
 Primary = 3.89 cfs @ 12.32 hrs, Volume= 0.762 af
 Routed to Reach 1R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 310.06' @ 12.32 hrs Surf.Area= 6,999 sf Storage= 5,636 cf

Plug-Flow detention time= 13.6 min calculated for 0.762 af (100% of inflow)
 Center-of-Mass det. time= 12.6 min (776.0 - 763.4)

Volume	Invert	Avail.Storage	Storage Description
#1	308.50'	20,440 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
308.50	0	0	0
310.00	6,960	5,220	5,220
312.00	8,260	15,220	20,440

Device	Routing	Invert	Outlet Devices
#1	Primary	308.50'	12.0" Round Culvert L= 30.0' Ke= 0.500 Inlet / Outlet Invert= 308.50' / 308.10' S= 0.0133 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	311.50'	20.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)

Primary OutFlow Max=3.89 cfs @ 12.32 hrs HW=310.06' (Free Discharge)

1=Culvert (Inlet Controls 3.89 cfs @ 4.96 fps)

2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 5P: EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Inflow Area = 1.630 ac, 20.58% Impervious, Inflow Depth > 5.04" for 100 YEAR event
 Inflow = 7.56 cfs @ 12.13 hrs, Volume= 0.685 af
 Outflow = 4.02 cfs @ 12.38 hrs, Volume= 0.683 af, Atten= 47%, Lag= 15.3 min
 Primary = 4.02 cfs @ 12.38 hrs, Volume= 0.683 af
 Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 327.28' @ 12.38 hrs Surf.Area= 4,147 sf Storage= 5,932 cf

Plug-Flow detention time= 20.3 min calculated for 0.683 af (100% of inflow)
 Center-of-Mass det. time= 18.0 min (832.5 - 814.5)

Volume	Invert	Avail.Storage	Storage Description
#1	325.50'	12,719 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

PREDEV at 250 Turnpike Road 4-15-24

Prepared by Expedited Engineering, LLC

HydroCAD® 10.20-5c s/n 13482 © 2023 HydroCAD Software Solutions LLC

Type III 24-hr 100 YEAR Rainfall=8.01"

Printed 11/23/2024

Page 9

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
325.50	0	0	0
326.00	3,700	925	925
328.00	4,400	8,100	9,025
328.75	5,450	3,694	12,719

Device	Routing	Invert	Outlet Devices
#1	Primary	325.50'	12.0" Round Culvert L= 38.0' Ke= 0.500 Inlet / Outlet Invert= 325.50' / 325.25' S= 0.0066 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	328.25'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68 2.72 2.81 2.92 2.97 3.07 3.32

Primary OutFlow Max=4.02 cfs @ 12.38 hrs HW=327.27' (Free Discharge)

1=Culvert (Barrel Controls 4.02 cfs @ 5.12 fps)

2=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 7P: EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 5.17" for 100 YEAR event

Inflow = 76.71 cfs @ 12.11 hrs, Volume= 5.973 af

Outflow = 74.33 cfs @ 12.16 hrs, Volume= 5.957 af, Atten= 3%, Lag= 2.9 min

Primary = 74.33 cfs @ 12.16 hrs, Volume= 5.957 af

Routed to Reach 7R : FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Peak Elev= 356.15' @ 12.16 hrs Surf.Area= 18,050 sf Storage= 44,275 cf

Plug-Flow detention time= 30.6 min calculated for 5.947 af (100% of inflow)

Center-of-Mass det. time= 28.8 min (840.1 - 811.3)

Volume	Invert	Avail.Storage	Storage Description
#1	351.00'	44,275 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
351.00	0	0	0
352.00	6,070	3,035	3,035
354.00	8,560	14,630	17,665
356.00	18,050	26,610	44,275

Device	Routing	Invert	Outlet Devices
#1	Primary	351.00'	12.0" Round Culvert L= 60.0' Ke= 0.500 Inlet / Outlet Invert= 351.00' / 349.00' S= 0.0333 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	355.00'	20.0' long x 4.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00

2.50 3.00 3.50 4.00 4.50 5.00 5.50
 Coef. (English) 2.38 2.54 2.69 2.68 2.67 2.67 2.65 2.66 2.66
 2.68 2.72 2.73 2.76 2.79 2.88 3.07 3.32

Primary OutFlow Max=73.98 cfs @ 12.16 hrs HW=356.15' (Free Discharge)

1=Culvert (Inlet Controls 8.15 cfs @ 10.38 fps)

2=Broad-Crested Rectangular Weir (Weir Controls 65.83 cfs @ 2.86 fps)

Summary for Pond 8P: DET BASIN ON EAGLE LEASING

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 5.74" for 100 YEAR event

Inflow = 32.38 cfs @ 12.17 hrs, Volume= 2.884 af

Outflow = 13.68 cfs @ 12.48 hrs, Volume= 2.883 af, Atten= 58%, Lag= 18.8 min

Primary = 13.68 cfs @ 12.48 hrs, Volume= 2.883 af

Routed to Reach 8R : FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Peak Elev= 347.28' @ 12.48 hrs Surf.Area= 19,484 sf Storage= 31,008 cf

Plug-Flow detention time= 23.4 min calculated for 2.879 af (100% of inflow)

Center-of-Mass det. time= 23.2 min (828.4 - 805.2)

Volume	Invert	Avail.Storage	Storage Description
#1	342.50'	46,903 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
342.50	0	0	0
344.00	1,030	773	773
346.00	10,200	11,230	12,003
348.00	24,700	34,900	46,903

Device	Routing	Invert	Outlet Devices
#1	Primary	342.50'	12.0" Round Culvert L= 33.0' Ke= 0.500 Inlet / Outlet Invert= 342.50' / 342.10' S= 0.0121 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	347.00'	12.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 4.5' Crest Height

Primary OutFlow Max=13.66 cfs @ 12.48 hrs HW=347.28' (Free Discharge)

1=Culvert (Inlet Controls 7.82 cfs @ 9.96 fps)

2=Sharp-Crested Rectangular Weir (Weir Controls 5.84 cfs @ 1.74 fps)

POSTDEVELOPMENT

Summary for Subcatchment 11S: POSTDEV FLOW FROM PARKING AREA

Runoff = 7.73 cfs @ 12.08 hrs, Volume= 0.634 af, Depth> 7.65"
 Routed to Pond 23P : INFILTRATION BASIN WITH 76 R902s

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
41,985	98	Paved parking, HSG B
280	74	>75% Grass cover, Good, HSG C
1,049	61	>75% Grass cover, Good, HSG B
43,314	97	Weighted Average
1,329		3.07% Pervious Area
41,985		96.93% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
6.0					Direct Entry,

Summary for Subcatchment 12S: POSTDEV OVERLAND FLOW TO DETENTION BASIN

Runoff = 2.77 cfs @ 12.15 hrs, Volume= 0.234 af, Depth> 4.93"
 Routed to Pond 11P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
2,913	98	Water Surface, HSG B
12,916	70	Woods, Good, HSG C
189	55	Woods, Good, HSG B
7,152	74	>75% Grass cover, Good, HSG C
1,644	61	>75% Grass cover, Good, HSG B
24,814	74	Weighted Average
21,901		88.26% Pervious Area
2,913		11.74% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
10.5	50	0.0300	0.08		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
0.5	58	0.1600	2.00		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
11.0	108				Total

Summary for Subcatchment 13S: POSTDEV OVERLAND FLOW TO PARKERVILLE ROAD

Runoff = 8.49 cfs @ 12.34 hrs, Volume= 0.974 af, Depth> 4.22"
 Routed to Reach 11R : PARKERVILLE ROAD

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
1,943	55	Woods, Good, HSG B
1,148	98	Roofs, HSG B
1,254	61	>75% Grass cover, Good, HSG B
183	70	Woods, Good, HSG C
1,148	98	Roofs, HSG C
5,275	74	>75% Grass cover, Good, HSG C
22,271	55	Woods, Good, HSG B
789	98	Roofs, HSG B
19,728	61	>75% Grass cover, Good, HSG B
26,543	70	Woods, Good, HSG C
4,032	98	Roofs, HSG C
36,320	74	>75% Grass cover, Good, HSG C
120,634	68	Weighted Average
113,517		94.10% Pervious Area
7,117		5.90% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
9.9	754	0.0640	1.26		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.9	243	0.0370	4.76	57.07	Channel Flow, 2' WIDE BOTTOM, 10:1 SIDE SLOPES,1'DEEP Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
24.6	1,047				Total

Summary for Subcatchment 14S: OVERLAND FLOW TO ROUTE 9

Runoff = 16.68 cfs @ 12.25 hrs, Volume= 1.692 af, Depth> 4.46"
 Routed to Reach 14R : ROUTE 9

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
31,704	70	Woods, Good, HSG C
0	98	Roofs, HSG C
4,306	98	Roofs, HSG C
11,703	74	>75% Grass cover, Good, HSG C
76,405	55	Woods, Good, HSG B
44,135	98	Paved parking, HSG B
30,229	61	>75% Grass cover, Good, HSG B
198,482	70	Weighted Average
150,041		75.59% Pervious Area
48,441		24.41% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.2	50	0.0400	0.13		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
1.1	242	0.0600	3.67		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
9.1	709	0.0680	1.30		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.9	365	0.0160	3.13	37.53	Channel Flow, Area= 12.0 sf Perim= 22.1' r= 0.54' n= 0.040 Earth, cobble bottom, clean sides
18.3	1,366				Total

Summary for Subcatchment 15S: DRAINAGE COLLECTED BY CB'S SW OF SELF STORAGE BUILDING

Runoff = 3.43 cfs @ 12.09 hrs, Volume= 0.254 af, Depth> 6.10"
 Routed to Pond 15P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
6,345	61	>75% Grass cover, Good, HSG B
3,301	74	>75% Grass cover, Good, HSG C
6,254	98	Paved parking, HSG B
5,860	98	Paved parking, HSG C
21,760	84	Weighted Average
9,646		44.33% Pervious Area
12,114		55.67% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 16S: OVERLAND FLOW TO EXISTING DETENTION BASIN

Runoff = 4.88 cfs @ 12.18 hrs, Volume= 0.431 af, Depth> 4.58"
 Routed to Pond 15P : EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
46,762	70	Woods, Good, HSG C
2,500	98	Water Surface, HSG C
49,262	71	Weighted Average
46,762		94.93% Pervious Area
2,500		5.07% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	50	0.0450	0.09		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 3.20"
3.8	324	0.0800	1.41		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
12.7	374	Total			

Summary for Subcatchment 17S: RUNOFF COLLECTED BY SARSEN STONE WAY

Runoff = 59.36 cfs @ 12.12 hrs, Volume= 4.667 af, Depth> 5.51"
 Routed to Pond 17P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
317,393	84	1 acre lots, 20% imp, HSG D
125,360	68	1 acre lots, 20% imp, HSG B
442,753	79	Weighted Average
354,202		80.00% Pervious Area
88,551		20.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
2.0	214	0.1300	1.80		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
0.6	175	0.1000	4.74		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
0.5	210	0.1000	6.42		Shallow Concentrated Flow, Paved Kv= 20.3 fps
8.4	649	Total			

Summary for Subcatchment 18S: POSTDEV FLOW ON EAGLE LEASING

Runoff = 32.38 cfs @ 12.17 hrs, Volume= 2.884 af, Depth> 5.74"
 Routed to Pond 18P : DET BASIN ON EAGLE LEASING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
24,658	98	Paved parking, HSG B
8,220	61	>75% Grass cover, Good, HSG B
104,681	98	Paved parking, HSG C
34,894	74	>75% Grass cover, Good, HSG C
235	98	Paved parking, HSG D
6,197	80	>75% Grass cover, Good, HSG D
30,530	61	>75% Grass cover, Good, HSG B
5,140	98	Paved parking, HSG B
48,076	55	Woods, Good, HSG B
262,631	81	Weighted Average
127,917		48.71% Pervious Area
134,714		51.29% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.3	50	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
4.2	413	0.1100	1.66		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
2.9	360	0.0440	2.10		Shallow Concentrated Flow, Nearly Bare & Untilled Kv= 10.0 fps
12.4	823	Total			

Summary for Subcatchment 19S: OVERLAND FLOW TO DET BASIN BEHIND 5 & 7 SARSEN STONE

Runoff = 18.23 cfs @ 12.09 hrs, Volume= 1.306 af, Depth> 4.24"
 Routed to Pond 17P : EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
20,407	70	Woods, Good, HSG C
3,300	98	Water Surface, HSG B
36,775	55	Woods, Good, HSG B
13,560	85	1/2 acre lots, 25% imp, HSG D
87,016	70	1/2 acre lots, 25% imp, HSG B
161,058	68	Weighted Average
132,614		82.34% Pervious Area
28,444		17.66% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.0					Direct Entry,

Summary for Subcatchment 25S: AREA CAPTURED IN MAIN DRIVE

Runoff = 9.32 cfs @ 12.21 hrs, Volume= 0.939 af, Depth> 6.44"
 Routed to Pond 24P : INFILTRATION STRUCTURE UNDER PARKING

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
37,506	98	Paved parking, HSG C
11,007	98	Paved parking, HSG B
8,588	61	>75% Grass cover, Good, HSG B
16,641	74	>75% Grass cover, Good, HSG C
2,422	55	Woods, Good, HSG B
76,164	87	Weighted Average
27,651		36.30% Pervious Area
48,513		63.70% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.8	50	0.0600	0.06		Sheet Flow, Woods: Dense underbrush n= 0.800 P2= 3.20"
0.5	55	0.1400	1.87		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
1.0	79	0.0380	1.36		Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps
0.9	167	0.0240	3.14		Shallow Concentrated Flow, Paved Kv= 20.3 fps
16.2	351				Total

Summary for Subcatchment 26S: DRIVEWAY AND 5 UNITS AT ENTRANCE

Runoff = 2.08 cfs @ 12.19 hrs, Volume= 0.208 af, Depth> 6.92"
 Routed to Reach 26R : FLOW PATH FROM OUTLET TO PARKERVILLE

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
4,449	74	>75% Grass cover, Good, HSG C
11,225	98	Paved parking, HSG C
15,674	91	Weighted Average
4,449		28.38% Pervious Area
11,225		71.62% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
14.3	50	0.0050	0.06		Sheet Flow, Grass: Dense n= 0.240 P2= 3.20"
0.3	19	0.0050	1.06		Shallow Concentrated Flow, Grassed Waterway Kv= 15.0 fps
14.6	69	Total			

Summary for Subcatchment 27S: BACK HALF OF ROOFS UNITS 9-11

Runoff = 0.28 cfs @ 12.07 hrs, Volume= 0.022 af, Depth> 7.77"
 Routed to Pond 27P : INFILTRATION STRUCTURE FOR 9-11

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
1,512	98	Roofs, HSG C
1,512		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 28S: BACK HALF OF ROOFS UNITS 22-24

Runoff = 0.28 cfs @ 12.07 hrs, Volume= 0.022 af, Depth> 7.77"
 Routed to Pond 28P : INFILTRATION STRUCTURE FOR 22-24

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
1,512	98	Roofs, HSG C
1,512		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 29S: ROOFS FROM 20,21,26-29

Runoff = 0.74 cfs @ 12.07 hrs, Volume= 0.060 af, Depth> 7.77"
 Routed to Pond 29P : INFILTRATION STRUCTURE FOR 20-21 & 26-29

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Type III 24-hr 100 YEAR Rainfall=8.01"

Area (sf)	CN	Description
4,032	98	Roofs, HSG C
4,032		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Reach 11R: PARKERVILLE ROAD

Inflow Area = 6.442 ac, 39.83% Impervious, Inflow Depth > 4.08" for 100 YEAR event
 Inflow = 14.72 cfs @ 12.33 hrs, Volume= 2.191 af
 Outflow = 14.72 cfs @ 12.33 hrs, Volume= 2.191 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 14R: ROUTE 9

Inflow Area = 26.078 ac, 27.71% Impervious, Inflow Depth > 5.16" for 100 YEAR event
 Inflow = 92.67 cfs @ 12.22 hrs, Volume= 11.205 af
 Outflow = 92.67 cfs @ 12.22 hrs, Volume= 11.205 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Summary for Reach 17R: FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 5.16" for 100 YEAR event
 Inflow = 74.33 cfs @ 12.16 hrs, Volume= 5.957 af
 Outflow = 67.27 cfs @ 12.19 hrs, Volume= 5.952 af, Atten= 10%, Lag= 1.9 min
 Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Max. Velocity= 7.61 fps, Min. Travel Time= 0.9 min
 Avg. Velocity = 2.97 fps, Avg. Travel Time= 2.2 min

Peak Storage= 3,662 cf @ 12.17 hrs
 Average Depth at Peak Storage= 1.29', Surface Width= 12.32'
 Bank-Full Depth= 2.00' Flow Area= 20.0 sf, Capacity= 198.41 cfs

2.00' x 2.00' deep channel, n= 0.040 Earth, cobble bottom, clean sides
 Side Slope Z-value= 4.0' Top Width= 18.00'
 Length= 397.0' Slope= 0.0642 '
 Inlet Invert= 349.00', Outlet Invert= 323.50'


Summary for Reach 18R: FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 5.74" for 100 YEAR event
Inflow = 13.68 cfs @ 12.48 hrs, Volume= 2.883 af
Outflow = 13.65 cfs @ 12.49 hrs, Volume= 2.883 af, Atten= 0%, Lag= 0.6 min
Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 9.10 fps, Min. Travel Time= 0.3 min
Avg. Velocity = 4.50 fps, Avg. Travel Time= 0.6 min

Peak Storage= 236 cf @ 12.49 hrs
Average Depth at Peak Storage= 0.56', Surface Width= 4.36'
Bank-Full Depth= 2.00' Flow Area= 14.0 sf, Capacity= 271.03 cfs

1.00' x 2.00' deep channel, n= 0.025 Earth, clean & winding
Side Slope Z-value= 3.0 '/' Top Width= 13.00'
Length= 157.0' Slope= 0.1025 '/'
Inlet Invert= 342.10', Outlet Invert= 326.00'



Summary for Reach 22R: FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Inflow Area = 21.521 ac, 28.41% Impervious, Inflow Depth > 5.31" for 100 YEAR event
Inflow = 77.89 cfs @ 12.19 hrs, Volume= 9.518 af
Outflow = 76.38 cfs @ 12.22 hrs, Volume= 9.512 af, Atten= 2%, Lag= 1.3 min
Routed to Reach 14R : ROUTE 9

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 8.82 fps, Min. Travel Time= 0.7 min
Avg. Velocity = 3.69 fps, Avg. Travel Time= 1.7 min

Peak Storage= 3,385 cf @ 12.20 hrs
Average Depth at Peak Storage= 0.80', Surface Width= 19.04'
Bank-Full Depth= 2.00' Flow Area= 46.0 sf, Capacity= 707.92 cfs

3.00' x 2.00' deep channel, n= 0.030 Earth, grassed & winding
Side Slope Z-value= 10.0 '/' Top Width= 43.00'
Length= 383.0' Slope= 0.0888 '/'
Inlet Invert= 349.00', Outlet Invert= 315.00'

‡

Summary for Reach 26R: FLOW PATH FROM OUTLET TO PARKERVILLE

Inflow Area = 2.108 ac, 65.05% Impervious, Inflow Depth > 4.64" for 100 YEAR event
Inflow = 4.59 cfs @ 12.50 hrs, Volume= 0.816 af
Outflow = 4.57 cfs @ 12.56 hrs, Volume= 0.815 af, Atten= 0%, Lag= 3.6 min
Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Max. Velocity= 3.14 fps, Min. Travel Time= 1.9 min
Avg. Velocity = 1.12 fps, Avg. Travel Time= 5.4 min

Peak Storage= 524 cf @ 12.53 hrs
Average Depth at Peak Storage= 0.16', Surface Width= 12.35'
Bank-Full Depth= 1.00' Flow Area= 26.0 sf, Capacity= 232.32 cfs

6.00' x 1.00' deep channel, n= 0.022 Earth, clean & straight
Side Slope Z-value= 20.0 '/' Top Width= 46.00'
Length= 360.0' Slope= 0.0375 '/'
Inlet Invert= 318.00', Outlet Invert= 304.50'

‡

Summary for Pond 11P: EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD

Inflow Area = 1.564 ac, 65.90% Impervious, Inflow Depth > 1.80" for 100 YEAR event
Inflow = 2.77 cfs @ 12.15 hrs, Volume= 0.234 af
Outflow = 1.88 cfs @ 12.29 hrs, Volume= 0.234 af, Atten= 32%, Lag= 8.3 min
Primary = 1.88 cfs @ 12.29 hrs, Volume= 0.234 af
Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
Peak Elev= 309.25' @ 12.29 hrs Surf.Area= 3,503 sf Storage= 1,322 cf

Plug-Flow detention time= 9.9 min calculated for 0.234 af (100% of inflow)
Center-of-Mass det. time= 8.8 min (828.3 - 819.5)

Volume	Invert	Avail.Storage	Storage Description
#1	308.50'	20,440 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
308.50	0	0	0
310.00	6,960	5,220	5,220
312.00	8,260	15,220	20,440

Device	Routing	Invert	Outlet Devices
#1	Primary	308.50'	12.0" Round Culvert L= 30.0' Ke= 0.500 Inlet / Outlet Invert= 308.50' / 308.10' S= 0.0133 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	311.50'	20.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)

Primary OutFlow Max=1.88 cfs @ 12.29 hrs HW=309.25' (Free Discharge)

- 1=Culvert (Inlet Controls 1.88 cfs @ 2.96 fps)
- 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 15P: EXISTING DETENTION BASIN SOUTH OF SELF STORAGE BUILDING

Inflow Area = 1.630 ac, 20.58% Impervious, Inflow Depth > 5.04" for 100 YEAR event
 Inflow = 7.56 cfs @ 12.13 hrs, Volume= 0.685 af
 Outflow = 4.02 cfs @ 12.38 hrs, Volume= 0.683 af, Atten= 47%, Lag= 15.3 min
 Primary = 4.02 cfs @ 12.38 hrs, Volume= 0.683 af

Routed to Reach 22R : FLOW PATH FROM BASIN OUTLET TO ROUTE 9

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 327.28' @ 12.38 hrs Surf.Area= 4,147 sf Storage= 5,932 cf

Plug-Flow detention time= 20.3 min calculated for 0.683 af (100% of inflow)
 Center-of-Mass det. time= 18.0 min (832.5 - 814.5)

Volume	Invert	Avail.Storage	Storage Description
#1	325.50'	12,719 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
325.50	0	0	0
326.00	3,700	925	925
328.00	4,400	8,100	9,025
328.75	5,450	3,694	12,719

Device	Routing	Invert	Outlet Devices
#1	Primary	325.50'	12.0" Round Culvert L= 38.0' Ke= 0.500 Inlet / Outlet Invert= 325.50' / 325.25' S= 0.0066 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	328.25'	10.0' long x 3.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 Coef. (English) 2.44 2.58 2.68 2.67 2.65 2.64 2.64 2.68 2.68

2.72 2.81 2.92 2.97 3.07 3.32

Primary OutFlow Max=4.02 cfs @ 12.38 hrs HW=327.27' (Free Discharge)
 1=Culvert (Barrel Controls 4.02 cfs @ 5.12 fps)
 2=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Summary for Pond 17P: EXISTING DET BASIN ON 5 & 7 SARSEN STONE WAY

Inflow Area = 13.862 ac, 19.38% Impervious, Inflow Depth > 5.17" for 100 YEAR event
 Inflow = 76.71 cfs @ 12.11 hrs, Volume= 5.973 af
 Outflow = 74.33 cfs @ 12.16 hrs, Volume= 5.957 af, Atten= 3%, Lag= 2.9 min
 Primary = 74.33 cfs @ 12.16 hrs, Volume= 5.957 af
 Routed to Reach 17R : FLOW PATH FROM SARSEN STONE BASIN TO OUTLET OF BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 356.15' @ 12.16 hrs Surf.Area= 18,050 sf Storage= 44,275 cf

Plug-Flow detention time= 30.6 min calculated for 5.947 af (100% of inflow)
 Center-of-Mass det. time= 28.8 min (840.1 - 811.3)

Volume	Invert	Avail.Storage	Storage Description
#1	351.00'	44,275 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
351.00	0	0	0
352.00	6,070	3,035	3,035
354.00	8,560	14,630	17,665
356.00	18,050	26,610	44,275

Device	Routing	Invert	Outlet Devices
#1	Primary	351.00'	12.0" Round Culvert L= 60.0' Ke= 0.500 Inlet / Outlet Invert= 351.00' / 349.00' S= 0.0333 '/' Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	355.00'	20.0' long x 4.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.38 2.54 2.69 2.68 2.67 2.67 2.65 2.66 2.66 2.68 2.72 2.73 2.76 2.79 2.88 3.07 3.32

Primary OutFlow Max=73.98 cfs @ 12.16 hrs HW=356.15' (Free Discharge)
 1=Culvert (Inlet Controls 8.15 cfs @ 10.38 fps)
 2=Broad-Crested Rectangular Weir (Weir Controls 65.83 cfs @ 2.86 fps)

Summary for Pond 18P: DET BASIN ON EAGLE LEASING

Inflow Area = 6.029 ac, 51.29% Impervious, Inflow Depth > 5.74" for 100 YEAR event
 Inflow = 32.38 cfs @ 12.17 hrs, Volume= 2.884 af
 Outflow = 13.68 cfs @ 12.48 hrs, Volume= 2.883 af, Atten= 58%, Lag= 18.8 min
 Primary = 13.68 cfs @ 12.48 hrs, Volume= 2.883 af
 Routed to Reach 18R : FLOW PATH FROM EAGLE LEASING BASIN TO DET BASIN ON SITE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 347.28' @ 12.48 hrs Surf.Area= 19,484 sf Storage= 31,008 cf

Plug-Flow detention time= 23.4 min calculated for 2.879 af (100% of inflow)
 Center-of-Mass det. time= 23.2 min (828.4 - 805.2)

Volume	Invert	Avail.Storage	Storage Description
#1	342.50'	46,903 cf	Custom Stage Data (Prismatic) Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
342.50	0	0	0
344.00	1,030	773	773
346.00	10,200	11,230	12,003
348.00	24,700	34,900	46,903

Device	Routing	Invert	Outlet Devices
#1	Primary	342.50'	12.0" Round Culvert L= 33.0' Ke= 0.500 Inlet / Outlet Invert= 342.50' / 342.10' S= 0.0121 ' / Cc= 0.900 n= 0.012 Concrete pipe, finished, Flow Area= 0.79 sf
#2	Primary	347.00'	12.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 4.5' Crest Height

Primary OutFlow Max=13.66 cfs @ 12.48 hrs HW=347.28' (Free Discharge)

1=Culvert (Inlet Controls 7.82 cfs @ 9.96 fps)

2=Sharp-Crested Rectangular Weir (Weir Controls 5.84 cfs @ 1.74 fps)

Summary for Pond 23P: INFILTRATION BASIN WITH 76 R902s

Inflow Area = 0.994 ac, 96.93% Impervious, Inflow Depth > 7.65" for 100 YEAR event
 Inflow = 7.73 cfs @ 12.08 hrs, Volume= 0.634 af
 Outflow = 1.19 cfs @ 12.57 hrs, Volume= 0.428 af, Atten= 85%, Lag= 29.0 min
 Discarded = 0.23 cfs @ 9.00 hrs, Volume= 0.260 af
 Primary = 0.05 cfs @ 12.57 hrs, Volume= 0.001 af
 Routed to Pond 11P : EXISTING DETENTION BASIN NEAR PARKERVILLE ROAD
 Secondary = 1.00 cfs @ 12.57 hrs, Volume= 0.167 af
 Routed to Reach 11R : PARKERVILLE ROAD

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 310.12' @ 12.57 hrs Surf.Area= 2,450 sf Storage= 12,377 cf

Plug-Flow detention time= 168.4 min calculated for 0.427 af (67% of inflow)
 Center-of-Mass det. time= 70.4 min (817.1 - 746.7)

Volume	Invert	Avail.Storage	Storage Description
#1	302.50'	8,272 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 20,681 cf Overall x 40.0% Voids
#2	303.00'	4,966 cf	Cultec R-902HD v2 x 76 Effective Size= 69.1" W x 48.0" H => 17.30 sf x 3.67'L = 63.4 cf Overall Size= 78.0" W x 48.0" H x 4.10'L with 0.44' Overlap

76 Chambers in 4 Rows
 Cap Storage= 18.0 cf x 2 x 4 rows = 144.2 cf

13,238 cf Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
302.50	2,433	0	0
311.00	2,433	20,681	20,681

Device	Routing	Invert	Outlet Devices
#1	Discarded	302.50'	2.410 in/hr Exfiltration over Surface area
#2	Primary	310.00'	10.0" Round Culvert L= 51.0' Ke= 0.500 Inlet / Outlet Invert= 310.00' / 309.50' S= 0.0098 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.55 sf
#3	Secondary	307.50'	6.0" Round Culvert L= 86.0' Ke= 0.500 Inlet / Outlet Invert= 307.50' / 306.25' S= 0.0145 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.23 cfs @ 9.00 hrs HW=303.00' (Free Discharge)

1=Exfiltration (Exfiltration Controls 0.23 cfs)

Primary OutFlow Max=0.05 cfs @ 12.57 hrs HW=310.11' (Free Discharge)

2=Culvert (Barrel Controls 0.05 cfs @ 1.56 fps)

Secondary OutFlow Max=1.00 cfs @ 12.57 hrs HW=310.11' (Free Discharge)

3=Culvert (Barrel Controls 1.00 cfs @ 5.11 fps)

Summary for Pond 24P: INFILTRATION STRUCTURE UNDER PARKING

Inflow Area = 1.748 ac, 63.70% Impervious, Inflow Depth > 6.44" for 100 YEAR event
 Inflow = 9.32 cfs @ 12.21 hrs, Volume= 0.939 af
 Outflow = 3.93 cfs @ 12.57 hrs, Volume= 0.871 af, Atten= 58%, Lag= 21.0 min
 Discarded = 0.18 cfs @ 8.40 hrs, Volume= 0.263 af
 Primary = 3.75 cfs @ 12.57 hrs, Volume= 0.608 af

Routed to Reach 26R : FLOW PATH FROM OUTLET TO PARKERVILLE

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 327.84' @ 12.57 hrs Surf.Area= 3,284 sf Storage= 15,392 cf

Plug-Flow detention time= 106.5 min calculated for 0.871 af (93% of inflow)
 Center-of-Mass det. time= 68.9 min (861.7 - 792.8)

Volume	Invert	Avail.Storage	Storage Description
#1	320.50'	3,836 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 26,272 cf Overall - 16,683 cf Embedded = 9,589 cf x 40.0% Voids
#2	321.00'	12,422 cf	retain_it retain_it 5.0' x 46 Inside #1 Inside= 84.0"W x 60.0"H => 36.41 sf x 8.00'L = 291.3 cf Outside= 96.0"W x 68.0"H => 45.33 sf x 8.00'L = 362.7 cf 1 Rows adjusted for 976.7 cf perimeter wall

16,258 cf Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
320.50	3,284	0	0
328.50	3,284	26,272	26,272

Device	Routing	Invert	Outlet Devices
#1	Discarded	320.50'	2.410 in/hr Exfiltration over Surface area
#2	Primary	326.70'	8.0" Round Culvert L= 18.0' Ke= 0.500 Inlet / Outlet Invert= 326.70' / 319.00' S= 0.4278 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.35 sf
#3	Primary	322.00'	6.0" Round Culvert L= 18.0' Ke= 0.500 Inlet / Outlet Invert= 322.00' / 320.00' S= 0.1111 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf

Discarded OutFlow Max=0.18 cfs @ 8.40 hrs HW=320.58' (Free Discharge)
 ↑ 1=Exfiltration (Exfiltration Controls 0.18 cfs)

Primary OutFlow Max=3.74 cfs @ 12.57 hrs HW=327.84' (Free Discharge)
 ↑ 2=Culvert (Inlet Controls 1.51 cfs @ 4.32 fps)
 3=Culvert (Inlet Controls 2.23 cfs @ 11.38 fps)

Summary for Pond 27P: INFILTRATION STRUCTURE FOR 9-11

Inflow Area = 0.035 ac, 100.00% Impervious, Inflow Depth > 7.77" for 100 YEAR event
 Inflow = 0.28 cfs @ 12.07 hrs, Volume= 0.022 af
 Outflow = 0.01 cfs @ 7.88 hrs, Volume= 0.010 af, Atten= 98%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 7.88 hrs, Volume= 0.010 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 340.64' @ 16.73 hrs Surf.Area= 270 sf Storage= 598 cf

Plug-Flow detention time= 249.7 min calculated for 0.010 af (46% of inflow)
 Center-of-Mass det. time= 105.6 min (845.5 - 739.9)

Volume	Invert	Avail.Storage	Storage Description
#1	337.00'	291 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 1,350 cf Overall - 623 cf Embedded = 727 cf x 40.0% Voids
#2	337.50'	464 cf	Shea Dry Well 300gal x 10 Inside #1 Inside= 42.2"W x 45.0"H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0"W x 51.0"H => 15.58 sf x 4.00'L = 62.3 cf 10 Chambers in 2 Rows
754 cf			Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
337.00	270	0	0
342.00	270	1,350	1,350

Device	Routing	Invert	Outlet Devices
#1	Discarded	337.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 7.88 hrs HW=337.05' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.01 cfs)

Summary for Pond 28P: INFILTRATION STRUCTURE FOR 22-24

Inflow Area = 0.035 ac, 100.00% Impervious, Inflow Depth > 7.77" for 100 YEAR event
 Inflow = 0.28 cfs @ 12.07 hrs, Volume= 0.022 af
 Outflow = 0.01 cfs @ 7.88 hrs, Volume= 0.010 af, Atten= 98%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 7.88 hrs, Volume= 0.010 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 335.64' @ 16.73 hrs Surf.Area= 270 sf Storage= 598 cf

Plug-Flow detention time= 249.7 min calculated for 0.010 af (46% of inflow)
 Center-of-Mass det. time= 105.6 min (845.5 - 739.9)

Volume	Invert	Avail.Storage	Storage Description
#1	332.00'	291 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 1,350 cf Overall - 623 cf Embedded = 727 cf x 40.0% Voids
#2	332.50'	464 cf	Shea Dry Well 300gal x 10 Inside #1 Inside= 42.2"W x 45.0"H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0"W x 51.0"H => 15.58 sf x 4.00'L = 62.3 cf 10 Chambers in 2 Rows
		754 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
332.00	270	0	0
337.00	270	1,350	1,350

Device	Routing	Invert	Outlet Devices
#1	Discarded	332.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 7.88 hrs HW=332.05' (Free Discharge)
 ↑1=Exfiltration (Exfiltration Controls 0.01 cfs)

Summary for Pond 29P: INFILTRATION STRUCTURE FOR 20-21 & 26-29

Inflow Area = 0.093 ac, 100.00% Impervious, Inflow Depth > 7.77" for 100 YEAR event
 Inflow = 0.74 cfs @ 12.07 hrs, Volume= 0.060 af
 Outflow = 0.01 cfs @ 7.12 hrs, Volume= 0.023 af, Atten= 98%, Lag= 0.0 min
 Discarded = 0.01 cfs @ 7.12 hrs, Volume= 0.023 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 332.05' @ 17.55 hrs Surf.Area= 589 sf Storage= 1,704 cf

Plug-Flow detention time= 254.4 min calculated for 0.023 af (39% of inflow)
 Center-of-Mass det. time= 88.2 min (828.1 - 739.9)

Volume	Invert	Avail.Storage	Storage Description
#1	327.00'	697 cf	Custom Stage Data (Prismatic) Listed below (Recalc) 3,240 cf Overall - 1,496 cf Embedded = 1,744 cf x 40.0% Voids
#2	327.50'	1,113 cf	Shea Dry Well 300gal x 24 Inside #1 Inside= 42.2"W x 45.0"H => 13.25 sf x 3.50'L = 46.4 cf Outside= 54.0"W x 51.0"H => 15.58 sf x 4.00'L = 62.3 cf 24 Chambers in 4 Rows
1,811 cf			Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
327.00	589	0	0
332.50	589	3,240	3,240

Device	Routing	Invert	Outlet Devices
#1	Discarded	327.00'	1.020 in/hr Exfiltration over Surface area

Discarded OutFlow Max=0.01 cfs @ 7.12 hrs HW=327.06' (Free Discharge)
↑=Exfiltration (Exfiltration Controls 0.01 cfs)

NOAA's National Weather Service
Hydrometeorological Design Studies Center
Precipitation Frequency Data Server (PFDS)

www.nws.noaa.gov

Home Site Map Organization Search [] NWS All NOAA Go

General Information
Homepage
Progress Reports
FAQ
Glossary

Precipitation Frequency
Data Server
GIS Grids
Maps
Time Series
Temporals
Documents

Probable Maximum Precipitation
Documents

Miscellaneous
Publications
Storm Analysis
Record Precipitation

Contact Us
Inquiries

USA.gov

NOAA ATLAS 14 POINT PRECIPITATION FREQUENCY ESTIMATES: MA

Data description
Data type: [Precipitation depth] Units: [English] Time series type: [Partial duration]

Select location

1) Manually:
a) By location (decimal degrees, use "-" for S and W): Latitude: Longitude: Submit
b) By station (list of MA stations): Select station
c) By address 250 Tumple Road, Southborough, MA

2) Use map:

a) Select location
Move crosshair or double click
b) Click on station icon
 Show stations on map

Location information:
Name: Southborough, Massachusetts USA
Latitude: 42.2893°
Longitude: -71.5377°
Elevation: 324 ft **

* Source: ESRI Maps
** Source: USGS

POINT PRECIPITATION FREQUENCY (PF) ESTIMATES
WITH 90% CONFIDENCE INTERVALS AND SUPPLEMENTARY INFORMATION
NOAA Atlas 14, Volume 10, Version 3

PF tabular PF graphical Supplementary information

Duration	Average recurrence interval (years)									
	1	2	5	10	25	50	100	200	500	1000
5-min	0.336 (0.258-0.434)	0.402 (0.308-0.520)	0.510 (0.390-0.652)	0.599 (0.455-0.781)	0.722 (0.533-0.982)	0.814 (0.598-1.13)	0.911 (0.643-1.31)	1.02 (0.684-1.50)	1.18 (0.761-1.79)	1.30 (0.826-2.03)
10-min	0.476 (0.365-0.615)	0.569 (0.435-0.736)	0.721 (0.550-0.935)	0.848 (0.645-1.11)	1.02 (0.755-1.39)	1.16 (0.835-1.60)	1.29 (0.911-1.86)	1.45 (0.970-2.13)	1.67 (1.08-2.54)	1.85 (1.17-2.87)
15-min	0.580 (0.430-0.723)	0.670 (0.513-0.866)	0.850 (0.649-1.10)	0.988 (0.758-1.30)	1.20 (0.888-1.64)	1.36 (0.983-1.88)	1.52 (1.072-2.19)	1.70 (1.142-2.50)	1.96 (1.27-2.98)	2.17 (1.38-3.38)
30-min	0.764 (0.587-0.987)	0.915 (0.701-1.18)	1.16 (0.887-1.51)	1.36 (1.04-1.78)	1.64 (1.21-2.24)	1.86 (1.34-2.58)	2.08 (1.46-2.99)	2.32 (1.56-3.42)	2.68 (1.74-4.08)	2.97 (1.88-4.62)
60-min	0.859 (0.744-1.25)	1.16 (0.889-1.50)	1.47 (1.12-1.91)	1.73 (1.32-2.26)	2.08 (1.54-2.84)	2.35 (1.70-3.27)	2.63 (1.88-3.80)	2.95 (1.98-4.34)	3.40 (2.20-5.18)	3.77 (2.38-5.86)
2-hr	1.22 (0.942-1.56)	1.48 (1.14-1.90)	1.90 (1.46-2.44)	2.24 (1.72-2.91)	2.72 (2.03-3.70)	3.08 (2.25-4.28)	3.46 (2.47-5.00)	3.92 (2.84-5.74)	4.61 (3.09-6.97)	5.19 (3.28-8.00)
3-hr	1.40 (1.08-1.78)	1.70 (1.32-2.18)	2.20 (1.70-2.82)	2.61 (2.00-3.37)	3.17 (2.37-4.30)	3.59 (2.84-4.98)	4.04 (2.90-5.84)	4.59 (3.10-6.70)	5.43 (3.53-8.19)	6.15 (3.91-9.45)

https://hdsc.nws.noaa.gov/pfds/pfds_map_cont.html?bkmrk=ma

PF Map: Contiguous US

6-hr	1.79 (1.40-2.28)	2.18 (1.70-2.78)	2.82 (2.19-3.60)	3.35 (2.59-4.30)	4.08 (3.07-5.48)	4.62 (3.41-6.36)	5.20 (3.76-7.47)	5.92 (4.00-8.57)	7.02 (4.58-10.5)	7.97 (5.08-12.1)
12-hr	2.28 (1.79-2.88)	2.77 (2.17-3.50)	3.57 (2.79-4.53)	4.24 (3.28-5.40)	5.15 (3.89-6.88)	6.83 (4.32-7.96)	6.56 (4.75-9.33)	7.45 (5.06-10.7)	8.80 (5.76-13.1)	8.95 (6.37-15.1)
24-hr	2.72 (2.15-3.42)	3.33 (2.63-4.18)	4.32 (3.40-5.44)	5.14 (4.02-6.51)	6.27 (4.77-8.33)	7.11 (5.30-9.65)	8.01 (5.84-11.3)	9.12 (6.22-13.0)	10.8 (7.10-15.9)	12.3 (7.87-18.4)
2-day	3.05 (2.42-3.80)	3.78 (3.00-4.71)	4.97 (3.93-6.22)	5.85 (4.69-7.49)	7.31 (5.80-9.67)	8.31 (6.25-11.2)	9.41 (6.92-13.3)	10.8 (7.38-15.3)	12.9 (8.51-18.9)	14.8 (9.53-22.0)
3-day	3.30 (2.64-4.10)	4.08 (3.26-5.08)	5.38 (4.26-6.88)	6.42 (5.07-8.05)	7.88 (6.05-10.4)	8.95 (6.76-12.1)	10.1 (7.47-14.3)	11.6 (7.98-16.4)	13.9 (9.18-20.3)	15.9 (10.3-23.6)
4-day	3.55 (2.84-4.38)	4.36 (3.49-5.40)	6.69 (4.53-7.07)	6.79 (5.38-8.49)	8.31 (6.39-10.9)	9.42 (7.12-12.7)	10.6 (7.86-14.9)	12.2 (8.36-17.1)	14.5 (9.60-21.1)	16.6 (10.7-24.5)
7-day	4.24 (3.42-5.23)	6.11 (4.11-6.30)	6.52 (5.22-8.07)	7.70 (6.13-9.57)	9.31 (7.19-12.1)	10.5 (7.98-14.0)	11.8 (8.70-16.3)	13.4 (9.22-18.7)	15.7 (10.4-22.7)	17.8 (11.5-26.1)
10-day	4.92 (3.67-6.04)	5.82 (4.69-7.15)	7.28 (5.85-8.98)	8.50 (6.79-10.5)	10.2 (7.87-13.2)	11.4 (8.85-15.1)	12.8 (9.39-17.5)	14.3 (9.91-19.8)	16.6 (11.1-23.8)	18.6 (12.0-27.2)
20-day	6.85 (5.65-8.47)	7.91 (6.42-9.85)	9.48 (7.67-11.6)	10.8 (8.67-13.3)	12.6 (9.76-16.1)	13.9 (10.6-18.1)	15.3 (11.2-20.6)	15.9 (11.7-23.2)	19.0 (12.7-27.0)	20.6 (13.4-30.0)
30-day	8.62 (7.04-10.5)	9.62 (7.85-11.7)	11.3 (9.15-13.7)	12.6 (10.2-15.5)	14.6 (11.3-18.4)	15.9 (12.1-20.5)	17.4 (12.7-23.1)	18.8 (13.2-25.8)	20.8 (13.9-29.4)	22.2 (14.5-32.2)
45-day	10.7 (8.76-12.9)	11.7 (9.61-14.2)	13.5 (11.0-16.3)	14.9 (12.1-18.2)	16.8 (13.1-21.2)	18.4 (14.0-23.5)	19.8 (14.5-28.1)	21.2 (14.9-29.0)	23.0 (15.4-32.4)	24.2 (15.8-34.8)
60-day	12.4 (10.2-15.0)	13.6 (11.1-16.3)	15.3 (12.5-18.5)	16.7 (13.6-20.4)	18.8 (14.7-23.5)	20.4 (15.5-25.9)	21.9 (16.0-28.5)	23.2 (16.3-31.5)	24.8 (16.7-34.8)	25.9 (16.9-37.1)

¹ Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS).

Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values.

Please refer to NOAA Atlas 14 document for more information.

Estimates from the table in CSV format: [Precipitation frequency estimates](#)

Main Link Categories:
[Home](#) | [OWP](#)

US Department of Commerce
 National Oceanic and Atmospheric Administration
 National Weather Service
 Office of Water Prediction (OWP)
 1325 East West Highway
 Silver Spring, MD 20910
 Page Author: HDSC webmaster
 Page last modified: April 21, 2017

[Map Disclaimer](#)
[Disclaimer](#)
[Credits](#)
[Glossary](#)

[Privacy P](#)
[About](#)
[Career Opportun](#)



Commonwealth of Massachusetts

City/Town of Southborough

Form 11 - Soil Suitability Assessment for On-Site Sewage Disposal

A. Facility Information

FD 250 Turnpike, LLC	Owner Name
250 Turnpike Road	Street Address
Southborough	City
MA	State
	Zip Code

B. Site Information

1. (Check one) <input checked="" type="checkbox"/> New Construction <input type="checkbox"/> Upgrade <input type="checkbox"/> Repair	2. Soil Survey Available? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	If yes: Woodbridge(near edge of mapped Canton) Soil Name Till Soil Parent material	3. Surficial Geological Report Available? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	If yes: Year Published/Source Map Unit
Description of Geologic Map Unit:				
4. Flood Rate Insurance Map	Within a regulatory floodway?	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
5. Within a velocity zone?	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			
6. Within a Mapped Wetland Area?	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			
7. Current Water Resource Conditions (USGS):	11/13/23 Month/Day/ Year	If yes, MassGIS Wetland Data Layer: Range: <input type="checkbox"/> Above Normal <input checked="" type="checkbox"/> Normal <input type="checkbox"/> Below Normal		
8. Other references reviewed:				

DH 21822
11-13-2023

Web soil survey
Source
310B
Soil Map Unit

severe
Soil Limitations

Uncertain
Landform

Year Published/Source
Map Unit

Form 11 - Soil Suitability Assessment for On-Site Sewage Disposal

D. Determination of High Groundwater Elevation

1. Method Used:

- Depth observed standing water in observation hole
- Depth weeping from side of observation hole
- Depth to soil redoximorphic features (mottles)
- Depth to adjusted seasonal high groundwater (S_h) (USGS methodology)

Index Well Number _____

Reading Date _____

Obs. Hole # 21 Obs. Hole # 22
 NJT 85 inches NJT 85 inches
 NJT 85 inches NJT 85 inches
66 inches 42 inches
66 inches 42 inches
 inches inches

$$S_h = S_c - [S_r \times (OW_c - OW_{max})/OW_r]$$

Obs. Hole/Well# _____ S_c _____ S_r _____

2. Estimated Depth to High Groundwater: _____ inches

E. Depth of Pervious Material

1. Depth of Naturally Occurring Pervious Material


a. Does at least four feet of naturally occurring pervious material exist in all areas observed throughout the area proposed for the soil absorption system?

Yes No

b. If yes, at what depth was it observed (exclude A and O Horizons)?

c. If no, at what depth was impervious material observed?

Upper boundary: 30 inches Lower boundary: 23 inches
 Upper boundary: 14 inches Lower boundary: 72 inches



Form 11 - Soil Suitability Assessment for On-Site Sewage Disposal

F. Certification

I certify that I am currently approved by the Department of Environmental Protection pursuant to 310 CMR 15.017 to conduct soil evaluations and that the above analysis has been performed by me consistent with the required training, expertise and experience described in 310 CMR 15.017. I further certify that the results of my soil evaluation, as indicated in the attached Soil Evaluation Form, are accurate and in accordance with 310 CMR 15.100 through 15.107.


Signature of Soil Evaluator
James Lettsbach


Typed or Printed Name of Soil Evaluator / License #


Name of Approving Authority / Witness

Approving Authority / Witness

Note: In accordance with 310 CMR 15.018(2) this form must be submitted to the approving authority within 60 days of the date of field testing, and to the designer and the property owner with Percolation Test Form 12.

Field Diagrams: Use this area for field diagrams:





Commonwealth of Massachusetts

City/Town of Southborough

Form 11 - Soil Suitability Assessment for On-Site Sewage Disposal

A. Facility Information

FD 250 Turnpike, LLC	Owner Name
250 Turnpike Road	Street Address
Southborough	City
MA	State
01772	Zip Code

B. Site Information

1. (Check one) <input checked="" type="checkbox"/> New Construction <input type="checkbox"/> Upgrade <input type="checkbox"/> Repair	Web soil survey Source	310B Soil Map Unit
2. Soil Survey Available? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	If yes: Woodbridge(near edge of mapped Canton) Soil Name Till	DA 23 11/13/2023
3. Surficial Geological Report Available? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	If yes: Soil Parent material Till Landform	Year Published/Source Map Unit
Description of Geologic Map Unit:		
4. Flood Rate Insurance Map	Within a regulatory floodway? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
5. Within a velocity zone? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
6. Within a Mapped Wetland Area? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	If yes, MassGIS Wetland Data Layer:	
7. Current Water Resource Conditions (USGS):	11/13/23 Month/Day/ Year	Range: <input type="checkbox"/> Above Normal <input checked="" type="checkbox"/> Normal <input type="checkbox"/> Below Normal Wetland Type
8. Other references reviewed:		

Form 11 - Soil Suitability Assessment for On-Site Sewage Disposal

C. On-Site Review (minimum of two holes required at every proposed primary and reserve disposal area)

Deep Observation Hole Number: 23 Date 11/13/23 Time 10:10 Weather Cloudy Latitude 42° 33' N Longitude 71° 45' W

1. Land Use (e.g., woodland, agricultural field, vacant lot, etc.) WOODS AND DECIDUOUS TREES Vegetation Surface Stones (e.g., cobbles, stones, boulders, etc.) Slope (%) 5%

Description of Location: NEAR THE TIE OF SLOPES BOTH NORTH & SOUTH

2. Soil Parent Material: TILL Landform UNCONFINED Position on Landscape (SU, SH, BS, FS, TS) UNCONFINED

3. Distances from: Open Water Body 60 feet Drainage Way — feet Wetlands 40 feet

Property Line 80 feet Drinking Water Well — feet Other — feet


4. Unsuitable Materials Present: Yes No Disturbed Soil Fill Material Weathered/Fractured Rock Bedrock

5. Groundwater Observed: Yes No If yes: — feet Depth Weeping from Pit — feet Depth Standing Water in Hole — feet

Soil Log

Depth (in)	Soil Horizon Layer	Soil Texture (USDA)	Soil Matrix: Color-Moist (Munsell)	Redoxmorphic Features			Coarse Fragments % by Volume		Soil Structure	Soil Consistency (Moist)	Other
				Depth	Color	Percent	Gravel	Cobbles & Stones			
0-6"	A P	SANDY	10YR2/2								
6-12"	B	SANDY	10YR2/6								
12-18"	C 1	SANDY	10YR2/3								
18-24"	C 2	LOAMY	10YR7/3								
24-30"											
30-36"											
36-42"											
42-48"											
48-54"											
54-60"											
60-66"											
66-72"											
72-78"											
78-84"											
84-90"											
90-96"											
96-102"											
102-108"											
108-114"											
114-120"											
120-126"											
126-132"											
132-138"											
138-144"											
144-150"											
150-156"											
156-162"											
162-168"											
168-174"											
174-180"											
180-186"											
186-192"											
192-198"											
198-204"											
204-210"											
210-216"											
216-222"											
222-228"											
228-234"											
234-240"											
240-246"											
246-252"											
252-258"											
258-264"											
264-270"											
270-276"											
276-282"											
282-288"											
288-294"											
294-300"											
300-306"											
306-312"											
312-318"											
318-324"											
324-330"											
330-336"											
336-342"											
342-348"											
348-354"											
354-360"											
360-366"											
366-372"											
372-378"											
378-384"											
384-390"											
390-396"											
396-402"											
402-408"											
408-414"											
414-420"											
420-426"											
426-432"											
432-438"											
438-444"											
444-450"											
450-456"											
456-462"											
462-468"											
468-474"											
474-480"											
480-486"											
486-492"											
492-498"											
498-504"											
504-510"											
510-516"											
516-522"											
522-528"											
528-534"											
534-540"											
540-546"											
546-552"											
552-558"											
558-564"											
564-570"											
570-576"											
576-582"											
582-588"											
588-594"											
594-596"											

Additional Notes: Very similar to D22



Commonwealth of Massachusetts City/Town of Southborough

卷之三


Form 11 - Soil Suitability Assessment for On-Site Sewage Disposal

C. On-Site Review (minimum of two holes required at every proposed primary and reserve disposal area)

Form 11 - Soil Suitability Assessment for On-Site Sewage Disposal

C. On-Site Review (minimum of two holes required at every proposed primary and reserve disposal area)									
Deep Observation Hole Number: _____									
1. Land Use:	Hole # _____ (e.g., woodland, agricultural field, vacant lot, etc.)			Date _____	Time _____	Weather _____	Latitude _____	Longitude _____	
Description of Location: _____									
2. Soil Parent Material:				Landform _____	Position on Landscape (SU, SH, BS, FS, TS)				
3. Distances from:	Open Water Body _____ feet	Property Line _____ feet	Drinking Water Well _____ feet	Drainage Way _____ feet	Wetlands _____ feet	Other _____ feet			
4. Unsuitable Materials Present:	<input type="checkbox"/> Yes <input type="checkbox"/> No		If Yes: <input type="checkbox"/> Disturbed Soil <input type="checkbox"/> Fill Material	<input type="checkbox"/> Weathered/Fractured Rock	<input type="checkbox"/> Bedrock				
5. Groundwater Observed:	<input type="checkbox"/> Yes <input type="checkbox"/> No		If yes: _____ Depth Weeping from Pit _____ Depth Standing Water in Hole _____						
Soil Log									
Depth (in)	Soil Horizon /Layer	Soil Texture (USDA)	Soil Matrix: Color-Moist (Munsell)	Redoximorphic Features		Coarse Fragments % by Volume	Soil Structure	Soil Consistence (Moist)	Other
				Depth	Color				

Additional Notes:



Commonwealth of Massachusetts

City/Town of Southborough

Form 11 - Soil Suitability Assessment for On-Site Sewage Disposal

D. Determination of High Groundwater Elevation

1. Method Used:

- Depth observed standing water in observation hole
- Depth weeping from side of observation hole
- Depth to soil redoximorphic features (mottles)
- Depth to adjusted seasonal high groundwater (S_h) (USGS methodology)

$S_h = S_r - [S_r \times (OW_c - OW_{max})/OW_r]$

Obs. Hole/Well# _____ S_c _____ S_r _____ OW_c _____ OW_{max} _____ OW_r _____ S_h _____

2. Estimated Depth to High Groundwater: _____ inches

1. Method Used:

- Depth observed standing water in observation hole
- Depth weeping from side of observation hole
- Depth to soil redoximorphic features (mottles)
- Depth to adjusted seasonal high groundwater (S_h) (USGS methodology)

Obs. Hole # 23 inches

</div

Form 11 - Soil Suitability Assessment for On-Site Sewage Disposal

F. Certification

I certify that I am currently approved by the Department of Environmental Protection pursuant to 310 CMR 15.017 to conduct soil evaluations and that the above analysis has been performed by me consistent with the required training, expertise and experience described in 310 CMR 15.017. I further certify that the results of my soil evaluation, as indicated in the attached Soil Evaluation Form, are accurate and in accordance with 310 CMR 15.100 through 15.107.


Signature of Soil Evaluator


Signature of Approving Authority Witness


Signature of Approving Authority



Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority



Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority



Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority



Signature of Approving Authority



Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority



Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority


Signature of Approving Authority